BID SPECIFICATIONS FOR SKID STEER LOADER WITH MULCHER ATTACHMENT TEREX PT100G FORESTRY \$112,483.00 (INCLUDING OPTIONS)

GENERAL

These specifications shall be construed as the minimum acceptable standards for a skid steer loader with mulcher attachment. Should the manufacturer's current published data or specifications exceed these standards, the manufacturer's standards shall be considered minimum and shall be furnished. All integral parts not specifically mentioned in the scope of these specifications that are necessary to provide a complete working unit shall be furnished. Additionally, the machine offered for bid shall include all standard manufacturers' equipment. The skid steer loader with mulcher attachment must be a new current production model and shall meet all EPA and other applicable standards at the time of manufacture.

The use of specific names or numbers in the specifications is not intended to restrict the bidder or any seller or manufacturer, but is intended solely for the purpose of indicating the type, size, and quality of equipment considered best adapted to the uses of counties participating in this joint bid.

BID SUBMITTAL FORM

Each bidder must submit his or her bid on the Bid Submittal Form included in the invitation to bid package. All written warranties to be submitted shall be attached to the Bid Submittal Form.

BID PRICE

The price bid shall include all destination charges, delivery charges, title fees, rebates and all other applicable costs and refunds.

MANUALS

Each unit shall be provided with one (1) copy of the operator's manual. One day training to be provided by manufacturer's representative

WARRANTY

Bidders shall submit a copy of the manufacturer's standard warranty along with a complete explanation of the warranty with their bid. Mulcher attachment must have (1) year warranty with no hour limit. Skid Steer Loader must have (1) year warranty with no hour limit with the exception of the rubber tracks. Warranty on rubber tracks shall be a minimum (1) year warranty with a 1000 hour limit.

MINIMUM SPECIFICATIONS FOR SKID STEER LOADER

Height	85″	Yes No Page #
Width	69"	Yes No Page #
Length without Bucket	117"	Yes No Page #
Length with Bucket	149″	Yes No Page #

Ground Clearance	14"	Yes No Page #
Shipping Weight without bucket	10,400 lbs.	Yes No Page #
Operating Weight with bucket	11,425 lbs.	Yes No Page #
Top Speed	Two speed 5 & 10 mph	Yes No Page #
Ground Pressure at operating weight	4.37 lbs. per sq. in.	Yes No Page #
Ground Contact Area	2,550 sq. in.	Yes No Page #
Track Base (Ground Contact Length)	71″	Yes No Page #
Track Width	18″	Yes No Page #
Minimum Performance Tipping Load	7,600 lbs.	Yes No Page #
Operating Capacity @ 50% of Tipping Load	3,800 lbs.	Yes No Page #
Operating Capacity @ 35% of Tipping Load	2,660 lbs.	Yes No Page #
Breakout Force, Lift Cylinders	6,400 lbs.	Yes No Page #
Breakout Force, Bucket Cylinders	5,500 lbs.	Yes No Page #
Lift Height to Hinge Pin	125″	Yes No Page #

Quick-Attach	Hydraulic Powered, Universal Type	Yes No Page #
Transmission and Final Drive Drive Pumps		
Displacement	38.5 cc/rev	Yes No Page #
Relief Pressure	5,500 psi, 380 Bar	Yes No Page #
Power Management	Posi-Power Control System (Anti-Stall Device)	Yes No Page #
<u>Engine</u> 4 cylinder turbo diesel, liquid cooled		Yes No Page #
Displacement	4.4 L (268 cid)	Yes No Page #
Gross Horsepower	99 hp @ 2300 rpm	Yes No Page #
Peak Torque	300 lb-ft	Yes No Page #
Radiator and oil cooler must be side by side		Yes No Page #
Auto reversing cooling fan		Yes No Page #
<u>Auxiliary (Implement) Pump</u> Type	Variable Displacement	Yes No Page #
	Axial Piston	Yes No Page #
Displacement	38 cc/rev	Yes No Page #

Low Flow	20 gpm @ 2,300 rpm	Yes No Page #
High Flow	40 gpm @ 2,300 rpm	Yes No Page #
Pressure (Low Flow)	3,300 psi	Yes No Page #
Pressure (High Flow)	3,800 psi	Yes No Page #
Load sensing hydraulic system		Yes No Page #
Deluxe Cab Area Protection System	ROPS/FOPS Approved	Yes No Page #
Seat	Seat Belt & Lab Bar	Yes No Page #
Controls	Hydraulic Pilot Joysticks	Yes No Page #
Air Conditioning		Yes No Page #
Heater		Yes No Page #
Interior Dome Light		Yes No Page #
Lexan Complete Cab Enclosure/Front Door		Yes No Page #
Wiper Motor on front door		Yes No Page #
Front and rear emergency exits Audible back-up alarm		Yes No Page #
<u>Minimum Capacities</u> Fuel Tank	25 gal	Yes No Page #

Hydraulic Reservoir	20 gal	Yes No Page #
Coolant	4 gal	Yes No Page #
Engine Oil with Filter	9 qt	Yes No Page #
Undercarriage Suspension	Two Rubber Torsion Axles	Yes No Page #
Drive-Type	Internal	Yes No Page #
Number of Wheels Supporting and Guiding Each Track 21	Yes No	Page #
Wheel Lubrication	Sealed, oil filled bearings	Yes No Page #
Molded rubber with composite reinforcement molded internal (no steel in track)	hip drive	Yes No Page #
Positive Drive Self cleaning, internal drive sprocket drives the track via stee engaging the molded rubber drive hip lugs on interior of track		Yes No Page #
Instrumentation Fuel Level		Yes No Page #
Water Temperature Indicator		Yes No Page #
Hour Meter		Yes No Page #
Engine Oil Pressure Indicator		Yes No Page #
Amp Meter Indicator		Yes No Page #
Hot Hydraulic Oil Indicator		Yes No Page #
Glow Plug Indicator 5		Yes No

		Page #
Slope Indicator		Yes No Page #
<u>Electrical System</u> Lights	2 front, 2 rear	Yes No Page #
Battery	12 volt, 950 CCA	Yes No Page #
Alternator	65 Amp	Yes No Page #
Additional Features Dual Stage Air Cleaner		Yes No Page #
Service Access	Tilt-up ROPS	Yes No Page #
Auxiliary Hydraulic Connectors	Flat – Face	Yes No Page #
Hitch	2" Receiver Type, Rear	Yes No Page #
Wiring Harness	Braided type with Automotive – style fuse Box, pre-wired for Accessories	Yes No Page #
Lifting Eyes	4	Yes No Page #
MINIMUM SPECIFICATIONS FOR MULCHING ATTACHME	<u>NT</u>	
Weight 2,250 lbs.		Yes No Page #
Horsepower rating	165	Yes No Page #
RPM speed of spindle shaft	2,000	Yes No Page #
Cutting width	60″	Yes No Page #
Overall width	74"	Yes No Page #

Fixed replaceable carbide cutting hammers (qty)	45	Yes No Page #
Rated hydraulic flow	30 – 60 gal	Yes No Page #
Hydraulic deflector door		Yes No Page #
4" diameter hydraulic pressure sight gauge which read	ds UP TO 6000 psi.	Yes No Page #
Adjustable flex Variable Displacement motor		Yes No Page #
Rotor diameter including hammers	17.5″	Yes No Page #
Rotor tube wall thickness	3⁄4″	Yes No Page #
Rotor shaft diameter	2 3/8"	Yes No Page #
Rotor shaft attached inside of tube with (4) sweat colla	ars	Yes No
Lower bearing boxes equipped with dual spherical bea lock system	arings with tapered	Page # Yes No Page #
Upper bearing box assembly for hydraulic motor equip bearings	oped with dual tapered	Yes No Page #
PD drive belt and matching drive pulley system		Yes No Page #
2 – Position adjustable lower skid plates		Yes No Page #
3 – Position adjustable push bar		Yes No Page #
Pogo stick Hose Retention		Yes No Page #
FORESTRY GUARDING PACKAGE Limb risers		Yes No Page #
Rear brush guard, removable	-	Yes No

	Page #
Skid plates, hinged	Yes No Page #
Light guards	Yes No Page #
Hood guarding	Yes No Page #
Window guards	Yes No Page #
Climate control system and condenser guards	Yes No Page #
Sound insulation	Yes No Page #

Options

Bid must include the cost for each of the following options, itemized separately on the bid:

Mulching Attachment	Yes No Page #
Forestry Guarding Package	Yes No Page #
72" Loader Bucket (w/ cutting edge)	Yes No Page #
Rotating Beacon	Yes No Page #

NOTE: Award will be made on the basis of the total cost of machine with all options included. However, a county may, at its discretion, deduct the above-referenced options from the unit, and in such event, the cost of the options as stated on the bid shall be deducted from the total cost of the unit. There shall be no other deductions and no additions made to the unit by the purchasing county or by the vendor.

OPTION COST SHEET FOR SKID STEER LOADER WITH MULCHER ATTACHMENT

<u>Option</u>	Option Price
Mulching Attachment	\$ <u>25,088.00</u>
Forestry Guarding Package	\$ <u>2,000.00</u>
72" Loader Bucket (w/cutting edge)	\$ <u>1,440.00</u>
Rotating Beacon	\$ <u>413.00</u>

NOTE: Award will be made on the basis of the total cost of the machine with all options included. However, a county may, at its discretion, deduct one or more of the above-referenced options from the machine, and in such event, the cost of the option as stated on the bid shall be deducted from the total cost of the machine. There shall be no other deductions and no additions made to the machine by the purchasing county or by the vendor.

COUNTY JOINT BID PROGRAM PURCHASE PROCEDURES

Effective January 1, 2008

All purchases by counties pursuant to the County Joint Bid Program shall be made by (1) mailing or faxing the appropriate Purchase Order to the vendor who has been awarded the contract for the item to be ordered <u>and</u> (2) faxing a copy of the Purchase Order to the Association of County Commissions of Alabama (ACCA) office at 334-263-7678. Purchase Order Forms and all necessary information regarding the vendor and items available can be obtained at the ACCA website (<u>www.alabamacounties.org</u>).

Each purchase order shall be signed by the person authorized by the county to sign and shall include the County Joint Bid Program Item Number. A copy of the form submitted shall be retained by the county.

The county shall deal directly with the company representative for the vendor in making purchases under this program. The vendor shall complete all orders in compliance with its agreement under the program, and shall deal directly with each county in processing and completing their orders and in complying with service and warranty requirements. Road sign vendors should keep in mind that they are required to deliver all items to the location identified by the county ordering them within thirty (30) calendar days from the date of order, and the cost of any items not delivered within this time period will be reduced in price by 10%.

It is important to remember that under <u>Code of Alabama 1975</u>, § 41-16-50(b), all purchases made pursuant to this program shall be subject to the terms and conditions of Alabama's Competitive Bid Law. Therefore, counties are only authorized to purchase the specific items awarded under the program according to the bid specifications and must comply with these procedures in placing all orders.

There can be no deletions or additions to items purchased under this program, except as specifically provided for in the bid specifications. Optional equipment authorized under the bid specifications on certain heavy equipment orders may be deleted by the county at the time of purchase, and in that event, the cost of that item as provided by the vendor shall be deducted from the total cost of the item.

COUNTY JOINT BID PROGRAM HEAVY EQUIPMENT PURCHASE FOR SKID STEER LOADER WITH MULCHER ATTACHMENT

This form must be mailed or faxed to the Vendor with Copy faxed to the ACCA Office at 334-263-7678

Date of Order:	County Purchase Order No
County:	County Contact Person:
County Address:	
County Phone Number: _	
County Fax Number:	
E-mail Address:	
Equipment Model or Item	Name and Number: TEREX_PT100G_FORESTRY
optional equipment, state	ns, check the Options Cost Sheet for that item. If item is being purchased without any or all which item or items to be deleted and the cost of each such item:
Number of items ordered:	Final Price per item:
Vendor: Coastal Machine	ry Company Contact: Chris Dixion
	701 Mobile Highway ensacola, Fl 32526
Deliver to the Attention of	·
Delivery Address:	
- Requested delivery date:	
Name of person making p	urchase request:
Title:	
	ure:
Initial confirming form sen	t to ACCA: