

BID SUBMITTAL FORM
Alabama County Joint Bidding Program
BID ITEM – 16' DUMP BODY- OPTION E MANUAL

Company Name: Childersburg Truck Service, Inc.

Address: 33790 U.S. Hwy. 280

Childersburg, AL 35044

Bid Submitted by: Roger Justice
(Name of company representative)

Title: General Manager e-mail address: roger.justice@childersburg-truck.com

Phone: 256-378-3101 Fax: 256-378-5660

By submitting this bid, we agree:

Initials

That the equipment model number identified below meets the bid specs for this bid item

R.J.

That the bid price will be honored for all counties for the period from Jan. 1, 2019 to Dec. 31, 2019

R.J.

That the equipment will be delivered at the bid price to all counties participating in the joint bid program

R.J.

That the company representative listed above will be the contact person for purchasing this bid item under the joint bid program

R.J.

That the bid is accompanied by a current catalog or model specification document for the model number identified below

R.J.

That the bid is accompanied by a copy of the manufacturer's standard warranty as required in the bid specifications

R.J.

That the bid includes the e-verify documentation required by Alabama law

R.J.

That, if awarded the bid, a performance bond will be provided upon request

R.J.

That an option sheet with individual pricing is attached

R.J.

Total Bid Price including options: \$ 26,080.⁰⁰ Tier 4

Equipment Model #: 16' 21 Yard Maverick

Description: 16' Maverick Dump Body

Signature of company representative submitting bid: [Signature]

Title: General Manager

OPTION COST SHEET FOR 16' STEEL DUMP BODY – OPTION E (MANUAL TRANSMISSION)

Tri Axle Option Items

Option Price

Silent Drive or Equal Lift Axle

\$ 3700.⁰⁰

Four Steel Disc, Ten hole, hub piloted, bud style
22.5x8.25 wheels on lift axle

\$ 380.⁰⁰

Four 11R22.5 recap tires on lift axle

\$ 754.⁰⁰

Other Options

Option Price

High lift tail gate

\$ 1000.⁰⁰

Bed body vibrator

\$ 445.⁰⁰

25 ton heavy duty Pintle Hitch

\$ 725.⁰⁰


Chip Spreader bar mounted

\$ 271.⁰⁰

NOTE: Award will be made on the basis of the total cost of the machine with all options included. However, a county may, at its discretion, deduct one or more of the above-referenced options from the machine, and in such event, the cost of the option as stated on the bid shall be deducted from the total cost of the machine. There shall be no other deductions and no additions made to the machine by the purchasing county or by the vendor.

Equipment Model #: 16' 21 Yard Maverick

Description: 16' Maverick Dump Body

Signature of company representative submitting bid: 

Title: General Manager

BID SPECIFICATIONS 16' STEEL DUMP BODY OPTION E (MANUAL TRANSMISSION)

GENERAL

These specifications shall be construed as the minimum acceptable standards for a 16' Steel Dump Body. Should the manufacturer's current published data or specifications exceed these standards, the manufacturer's standards shall be considered minimum and shall be furnished. All integral parts not specifically mentioned in the scope of these specifications that are necessary to provide a complete working unit shall be furnished. Additionally, the machine offered for bid shall include all standard manufacturer's equipment. The 16' Steel Dump Body must be a new current production model.

The use of specific names or numbers in the specifications is not intended to restrict the bidder or any seller or manufacturer, but is intended solely for the purpose of indicating the type, size, and quality of equipment considered best adapted to the uses of counties participating in this joint bid.

BID SUBMITTAL FORM

Each bidder must submit his or her bid on the Bid Submittal Form included in the invitation to bid package. All written warranties to be submitted shall be attached to the Bid Submittal Form.

BID PRICE

The price bid shall include all destination charges, delivery charges, title fees, rebates and all other applicable costs and refunds.

REPLACEMENT PARTS AVAILABILITY

Parts must be available for 5 years or 500,000 miles of use for the piece of equipment bid.

ASSEMBLY AND DELIVERY

The dump body will be purchased for use with a heavy duty dump truck chassis (with Manual Transmission) bid separately. The dump body company will be responsible for assembly and installation of the dump body and related optional equipment, including the cost of the same. The selling truck chassis dealer will be responsible for delivery of the chassis to the dump body company, for installation and for delivery of the complete dump truck unit to the county following installation, and assembly of the dump body and related options onto the truck chassis. Freight to and from the dump body company will be included in the truck bidder's proposal. Dump body installation and assembly costs will be included in the dump body bidder's proposal.

WARRANTY

Bidders shall submit a copy of the manufacturer's standard warranty.

Yes ☒ No ☐
Page# 1-3
Or
Attachment ☐

DUMP BODY

Dump body shall meet all federal and state, health and safety regulations and must conform to American National Standard Institute (A.N.S.I.) Regulations (A.N.S.I.Z145) 1975.

Yes ☒ No ☐

Page # _____

Dump body supplier must have their own service and parts facility.

Yes ☒ No ☐

Page # _____

Dump body supplier must have a minimum of five (5) years' experience in sales, service and repair of dump bodies.

Yes ☒ No ☐

Page # _____

Body must be covered by product liability insurance.

Yes ☒ No ☐

Page # _____

GENERAL OPERATING SPECIFICATIONS AND DIMENSIONS

21 cubic yard capacity; 16 feet long; 60-inch high sides; 60- inch high tailgate; sides, tail-gate, floor shall be ¼ inch AR 450 steel; tailgate shall be sloping with a six (6) inch slope; 8" x 2" Rectangular Tubing Long Sills (Main Runners); 1.5" x 3" rectangular tubing cross-members on 12" centers; HYVA 74133 hoist that shall be class 120 hoist with a minimum four (4) active stages and minimum 60,000 pound capacity; direct mount integral pump and P.T.O. combination with air control on the P.T.O.; air tailgate latch control; electric tarp with vinyl asphalt type tarp; 42 inch cab shield, eight (8) inch wide schedule 80-pipe push bar asphalt apron across rear of body; 3.5 inch inverted angle on top of sides and top of tailgate; rib reinforced sidewalls and three (3) pane tailgate design; and Metro light kit.

Yes ☒ No ☐

Page # 4

TRI AXLE OR HEAVY DUTY DUMP TRUCK CHASSIS OPTIONS

The chassis (with Manual Transmission) will be used as a tri axle dump or a heavy duty tandem dump. All bids shall include the cost for each of the following options to be selected for a tri axle dump, itemized separately on the bid:

Silent Drive Lift (Pusher) axle (20,000 lb minimum Capacity) or Equal. This axle shall be air up and air down with a control valve and regulator located in the cab within reach of the operator.

Yes ☒ No ☐

Page # 5-6

Four (4) steel disc, ten (10) hole, hub piloted, bud style 22.5x8.25, wheels on lift axle.

Yes ☒ No ☐

Page # _____

Four 11R22.5 recap tires on lift axle.

Yes ☒ No ☐

Page # _____

OTHER OPTIONS

Bid must include the cost for each of the following options, itemized separately on the bid:

High lift tail gate

Yes ☒ No ☐
Page # 4

Bed body vibrator

Yes ☒ No ☐
Page #

25 ton heavy duty Pintle Hitch, swivel type, spring loaded, with safety chain rings, six (6) prong trailer light socket and air brakes hookup. Mounted 26 inches from ground with truck empty.

Yes ☒ No ☐
Page # 7

Chip spreader bar mounted at end of frame.

Yes ☒ No ☐
Page #

NOTE: Award will be made on the basis of the total cost of the dump body with all options included. However, a county may, at its discretion, deduct one or more of the above-referenced options from the dump body, and in such event, the cost of the options as stated on the bid shall be deducted from the total cost of the dump body. There shall be no other deductions and no additions made to the dump body by the purchasing county or by the vendor.