BID SUBMITTAL FORM Alabama County Joint Bidding Program BID ITEM – HEAVY DUTY BACKHOE-OPTION C

Company Name: Warrior Tractor & Equipment Company, Inc.
Address: 6801 McFarland Blvd. W.
Northport, AL 35476
Bid Submitted by: David Patterson (Name of company representative)
Title: Sales Manager e-mail address: davidp@warriortractor.com
Phone: 205-339-0300 Fax: 205-333-0101
By submitting this bid, we agree:
The equipment model number identified below meets the bid specs for this bid item
That the bid price will be honored for all counties for the period from Jan. 1, 2019 to Dec. 31, 2019.
The equipment will be delivered at the bid price to all counties participating in the joint bid program
The company representative listed above will be the contact person for purchasing this bid item under the joint bid program
The bid is accompanied by a current catalog or model specification document for the model number identified below
The bid is accompanied by a copy of the manufacturer's standard warranty as required in the bid specifications
The bid includes the e-verify documentation required by Alabama law
If awarded the bid, a performance bond will be provided upon request
The bid documents include the Manufacturer's Suggested Retail Price Sheet (MSRP) for the Standard Machine

HEAVY DUTY BACKHOE-OPTION C

Total Bid Price for Standard Machine: \$\\\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
Freight Preparation and Delivery: \$ 4,500.00 (Included in Standard Machine Bid Price)
Manufacturer's Suggested Retail Price for Standard Machine: $$142,540.00$
Equipment Model #:JOHN DEERE 410L
Description: BACKHOE
Signature of company representative submitting bid:
Title: Sales Manager

^{*} NOTE: Award will be made based on the total cost of the Standard Machine. The total cost of the standard machine is to include the freight preparation, delivery and standard warranty cost. Freight preparation, delivery will be excluded from the total bid price of the standard machine in determining the percentage discount for any available options.

BID SUBMITTAL FORM: OPTION COST SHEET HEAVY DUTY BACKHOE-OPTION C

To offer any available options at the percent difference between the Manufacturer's Suggested Retail Price Sheet and the actual bid price on the Standard Machine*

Title:

The bid documents include the Manufacturer's Suggested Retail Price Sheet (MSRP)

By submitting this bid, we agree:

with any available Options for the Standard Machine	1
Equipment Model #: _John Deere 410L	
Equipment would #	
Description: Backhoe	
Signature of company representative submitting bid:	

*Note: The percent difference between the Manufacturer's Suggested Retail Price Sheet (MSRP) for the standard machine as specified by these Bid Specifications and the actual price bid by the vendor will be calculated to determine the percentage discount to be applied to any available options. The bid price of the freight preparation, delivery cost shall be excluded in determining the percentage discount to be applied to available options. Any individual county may choose to add any available option to the standard machine at the percentage discount at the time of purchase.

Sales Manager

BID SPECIFICATIONS FOR HEAVY DUTY BACKHOE-OPTION C

GENERAL

These specifications shall be construed as the minimum acceptable standards for a heavy-duty backhoe. Should the manufacturer's current published data or specifications exceed these standards, the manufacturer's standards shall be considered minimum and shall be furnished. All integral parts not specifically mentioned in the scope of these specifications that are necessary to provide a complete working unit shall be furnished. Additionally, the machine offered for bid shall include all standard manufacturer's equipment. The heavy-duty loader/backhoes must be a new current production model and shall meet all EPA and other applicable standards at the time of manufacture.

The use of specific names or numbers in the specifications is not intended to restrict the bidder or any seller or manufacturer but is intended solely for the purpose of indicating the type, size and quality of equipment considered best adapted to the uses of counties participating in this joint bid.

BID SUBMITTAL FORM

Each bidder must submit his or her bid on the Bid Submittal Form included in the invitation to bid package. All written warranties to be submitted shall be attached to the Bid Submittal Form.

BID PRICE

The price bid shall include all destination charges, delivery charges, title fees, rebates and all other applicable costs and refunds.

MANUALS

Each unit shall be provided with one (1) copy of the operator's manual and one (1) copy of the current parts manual. Units will not be accepted for delivery until manuals as outlined above are received by the purchaser.

REPLACEMENT PARTS AVAILABILITY

Parts must be available for 5 years or 7,500 hours of use for the piece of equipment bid. If replacement parts are not delivered within three (3) working days of an order being placed, the bidder will deliver an equivalent machine for the County to use at no cost to the county until such time as the parts are delivered to the County so it can affect repairs to its machine.

WARRANTY

Bidders shall submit a copy of the manufacturer's standard warranty. Warranty shall include service response time of maximum of 36 hours within notification by county.

YesX_	No
Page#_	
or	
Attachn	nent X

ENGINE

Four-cylinder, four stroke cycle, minimum 276 cubic inch diesel engine, capable of developing a minimum of 112 NET flywheel horsepower with turbo charger.	Yes X No Page #_30
Must have an alternator with a minimum charging capacity of 120 amps.	Yes <u>X</u> No Page #_31
TRANSMISSION	
Power shuttle/Power Shift transmission.	Yes X No Page #_3 0
Minimum of four (5) speeds forward and four (3) reverse speeds.	Yes X No Page #_3 0
Minimum travel speed: 24 mph.	Yes <u>X</u> No Page #_ 3 0
CONTROLS AND HYDRAULICS	
Excavator style pilot-operated joystick controls with closed center, variable displacement load sensing hydraulic system.	Yes X No Page #_ 31
Adjustable steering column.	Yes X No Page #_SEE_ATTACHED
Air suspension seat.	Yes _X_No Page # <u>SEE</u> ATTACHED
FRONTEND LOADER	
Loader Bucket 1.25 min. cu yd. heavy-duty	Yes X No Page #_ 35
Loader breakout force (lbs.) – 10,500 lbs.	Yes _X_ No Page #_33
Loader lift capacity max. Height (lbs.) – 7,100 lbs.	Yes <u>x</u> No Page #_ 33
Loader pin height 11 ft. 4 in.	Yes <u>X</u> No
Loader dump height 8 ft. 10 in.	Page #_33 Yes <u>X_No</u> Page #_33

BACKHOE – TWO LEVEL CONTROL SYSTEM (FIXED LENGTH DIPPER STICK)

Backhoe Bucket 24 in. heavy duty bucket (5 teeth)	Yes X No Page #_32
Bucket breakout force (lbs.) – 15,500 lbs.	Yes <u>X</u> No Page #_ 3.2
Backhoe stick digging force (lbs.)10,900 lbs.	Yes <u>X</u> No Page #_3.2
Boom Lift @ 12 ft. (lbs.) – 3,200 lbs.	Yes <u>X</u> No Page #_ 3.2
Backhoe maximum digging depth 15 ft. 10 in.	Yes <u>X</u> No Page #_ 32
Backhoe maximum dumping height 13 ft. 01in.	Yes <u>X</u> No Page #_ <u>3 2</u>
BRAKES	
Service brakes – hydraulic wet disk.	Yes <u>X</u> No Page #3 0
Parking brake.	Yes <u>X</u> No Page #_ 3 0
All wheel braking shall be available.	Yes X No Page #_ 3 0
EDON'T AVI E	
FRONT AXLE Standard 2-wheel drive	Yes <u>X</u> No Page #_SEE
TIRES AND OUTRIGGERS	ATTACHED/39
Reversible type for use on both paved and non-paved surfaces.	Yes <u>X</u> No Page # <u>3 9</u>
Minimum 19.5L – 24/10 PR rear tires and wheels.	Yes <u>X</u> No Page #_ <u>31</u>
Minimum 12.5/80 – 18/10 PR front tires and wheels.	Yes <u>x</u> No Page # <u>_ 3 1</u>
FUEL TANK	
Minimum Capacity 37 Gallons	Yes <u>X</u> No Page #_31

OPEN ROPS CANOPY	Page #_SEE_
WEIGHT (STANDARD OPERATING)	ATTACHED/39
The factory specified operating weight only without options. No additional weights may be added for the purpose of meeting these specifications. Minimum 17,500 lbs. SAE standard.	Yes X No Page # 31
SAFETY DEVICES	1 age #
Include a fire extinguisher that meets current minimum OSHA requirements complete with Mounting hardware installed on the machine.	Yes X No Page #_39
Include a rotating or flashing safety beacon installed on top of the cab.	Yes X No Page # 39