

BID SUBMITTAL FORM
Alabama County Joint Bidding Program
BID ITEM – 100 HP HYDROSTATIC BULLDOZER – OPTION D

Company Name: Tractor & Equipment Company Inc.
Address: P.O. Box 12326
Birmingham, AL 35212
Bid Submitted by: Antony McMillan Jr.
(Name of company representative)
Title: V.P. e-mail address: amcmillan@TEC1943.com
Phone: 205-591-2131 Fax: 205-591-8321

By submitting this bid, we agree:

Initials

The equipment model number identified below meets the bid specs for this bid item

AM

That the bid price will be honored for all counties for the period from Jan. 1, 2019 to Dec. 31, 2019.

AM

The equipment will be delivered at the bid price to all counties participating in the joint bid program

AM

The company representative listed above will be the contact person for purchasing this bid item under the joint bid program

AM

The bid is accompanied by a current catalog or model specification document for the model number identified below

AM

The bid is accompanied by a copy of the manufacturer's standard warranty as required in the bid specifications

AM

The bid includes the e-verify documentation required by Alabama law

AM

If awarded the bid, a performance bond will be provided upon request

AM

The bid documents include the **Manufacturer's Suggested Retail Price Sheet (MSRP) for the Standard Machine**

AM

100 HP HYDROSTATIC BULLDOZER – OPTION D


Total Bid Price for Standard Machine: \$ 140,600⁰⁰
(Total Bid Price for Standard Machine Includes Freight Preparation, Delivery and Standard Warranty Costs)*

Freight Preparation and Delivery: \$ 4,000⁰⁰
(Included in Standard Machine Bid Price)

Manufacturer's Suggested Retail Price for Standard Machine: \$ 210,807⁰⁰

Equipment Model #: Komatsu D38PX-24

Description: 100 H.P. hydrostatic Bulldozer - Option D

Signature of company representative submitting bid: 

Title: V.P.

* **NOTE:** Award will be made based on the total cost of the **Standard Machine**. The total cost of the standard machine is to include the freight preparation, delivery and standard warranty cost. Freight preparation, delivery will be excluded from the total bid price of the standard machine in determining the percentage discount for any available options.

BID SUBMITTAL FORM: OPTION COST SHEET 100 HP HYDROSTATIC BULLDOZER – OPTION D

By submitting this bid, we agree:

To offer any available options at the percent difference between the Manufacturer's Suggested Retail Price Sheet and the actual bid price on the Standard Machine*

Am

The bid documents include the Manufacturer's Suggested Retail Price Sheet (MSRP) with **any available Options** for the Standard Machine

Am

Equipment Model #: Komatsu D38PX-24

Description: 100 H.P. Bulldozer - Option D

Signature of company representative submitting bid: _____

Arty M. Myers

Title: _____

V.P.

***Note:** The percent difference between the **Manufacturer's Suggested Retail Price Sheet (MSRP)** for the standard machine as specified by these **Bid Specifications** and the actual price bid by the vendor will be calculated to determine the percentage discount to be applied to any available options. The bid price of the freight preparation, delivery cost shall be excluded in determining the percentage discount to be applied to available options. Any individual county may choose to add any available option to the standard machine at the percentage discount at the time of purchase.

BID SPECIFICATIONS FOR 100 HP HYDROSTATIC BULLDOZER – OPTION D

GENERAL

These specifications shall be construed as the minimum acceptable standards for a 100 hp hydrostatic low ground pressure bulldozer. Should the manufacturer's current published data or specifications exceed these standards, the manufacturer's standards shall be considered minimum and shall be furnished. All integral parts not specifically mentioned in the scope of these specifications that are necessary to provide a complete working unit shall be furnished. Additionally, the machine offered for bid shall include all standard manufacturer's equipment. The bulldozers must be a new current production model and shall meet all EPA and other applicable standards at the time of manufacture.

The use of specific names and numbers in the specifications is not intended to restrict the bidder or any seller or manufacturer, but is intended solely for the purpose of indicating the type, size and quality of equipment considered best adapted to the uses of counties participating in this joint bid.

BID SUBMITTAL FORM

Each bidder must submit his or her bid on the Bid Submittal Form included in the invitation to bid package. All written warranties to be submitted shall be attached to the Bid Submittal Form.

BID PRICE

The price bid shall include all destination charges, delivery charges, title fees, rebates, and all other applicable costs and refunds.

MANUALS

Each unit shall be provided with one (1) copy of the operator's manual and one (1) copy of the current parts manual. Units will not be accepted for delivery until the manuals as outlined above are received by the purchaser.

REPLACEMENT PARTS AVAILABILITY

Parts must be available for 5 years or 7,500 hours of use for the piece of equipment bid. If replacement parts are not delivered within three (3) working days of an order being placed, the bidder will deliver an equivalent machine for the county to use at no cost to the county until such time as the parts are delivered to the county so it can affect repairs to its machine.

WARRANTY

Bidders shall submit a copy of the manufacturer's standard warranty. Warranty shall include service response time of maximum of 36 hours within notification by county.

Yes ☒ No ☐
Page#
or
Attachment ☒

ENGINE

Shall be a turbocharged diesel engine with a displacement of not less than **199 cubic inches**, capable of developing a minimum of **105 net** flywheel horsepower (SAE J1349).

Yes ☒ No ☐
Page # 14

Engine shall be manufactured by the equipment manufacturer.

Yes ☒ No ☐
Page # 14

WEIGHT

Operating weight with blade, operator, full fuel tank, and ROPS canopy shall not be less than **22,800 lbs.**

Yes ☒ No ☐
Page # 14

Minimum Ground Clearance shall be 15 inches

Yes ☒ No ☐
Page # 15

ELECTRICAL SYSTEM

Shall be equipped with a minimum **85-amp** alternator.

Yes ☒ No ☐
Page # 16

TRANSMISSION

Shall be equipped with a hydrostatic type transmission.

Yes ☒ No ☐
Page # 14

STEERING

All steering functions must be able to be performed using one hand only.

Yes ☒ No ☐
Page # 14

UNDERCARRIAGE

The tractor shall be equipped with sealed and lubricated tracks. Minimum shoe width shall be **27.5 inches**. Track sag shall be hydraulically adjusted.

Yes ☒ No ☐
Page # 14

BLADE

The machine shall be equipped with a six-way (pat) blade with a minimum capacity of **3.14 cubic yards**. And a minimum blade width of **128 inches**.

Yes ☒ No ☐
Page # 15

VANDALISM PROTECTION

Machine shall be equipped with all standard and optional factory vandalism protection available for the machine bid.

Yes ☒ No ☐
Page # 16

Hydraulics

Minimum pump flow shall be **26 gpm** and minimum system pressure of **3900 psi**.

Yes ☒ No ☐
Page # 14

SAFETY EQUIPMENT

Gauges and indicators shall be provided to monitor critical (fuel level, coolant temperature, powertrain oil temperature, and hydraulic oil temperature) operational systems of the machine and alert the operator when potential problems occur.

Yes ☒ No ☐
Page # 16

Rear view mirror; backup alarm.

Yes ☒ No ☐
Page # 16

Heavy duty hinged radiator guard

Yes ☒ No ☐
Page # 10

Crankcase guard

Yes ☒ No ☐
Page # 16

Track center guiding guard

Yes ☒ No ☐
Page # 14, 15

Pre-cleaner guard

Yes ☒ No ☐
Page # 16

Front tow hooks

Yes ☒ No ☐
Page # 16

Heavy duty rear drawbar

Yes ☒ No ☐
Page # 16

Fire extinguisher

Yes ☒ No ☐
Page # 16

Water separator

Yes ☒ No ☐
Page # 16

supplied by dealer