# BID SUBMITTAL FORM Alabama County Joint Bidding Program BID ITEM – 3 CY WHEEL LOADER - OPTION C

Company Name: Cowin Equipment Company Inc.	and the second
Address:3120 Hayneville Road	
Montgomery AI 36108	
Bid Submitted by:John Edwards	_
(Name of company representative)	
Title: Governmental Sales Manager e-mail address: jedwards@cowin.com	
Phone: 850-685-7055 Fax: 334-834-2272	
By submitting this bid, we agree:	Initials
The equipment model number identified below meets the bid specs for this bid item	JE_
That the bid price will be honored for all counties for the period from Jan. 1, 2019 to Dec. 31, 2019.	JE
The equipment will be delivered at the bid price to all counties participating in the joint bid program	JE
The company representative listed above will be the contact person for purchasing this bid item under the joint bid program	JE.
The bid is accompanied by a current catalog or model specification document for the model number identified below	gE
The bid is accompanied by a copy of the manufacturer's standard warranty as required in the bid specifications	JE
The bid includes the e-verify documentation required by Alabama law	gE
If awarded the bid, a performance bond will be provided upon request	gE
The bid documents include the Manufacturer's Suggested Retail Price Sheet (MSRP) for the Standard Machine	JE_

# 3 CY WHEEL LOADER - OPTION C

<sup>\*</sup> NOTE: Award will be made based on the total cost of the Standard Machine. The total cost of the standard machine is to include the freight preparation, delivery and standard warranty cost. Freight preparation, delivery will be excluded from the total bid price of the standard machine in determining the percentage discount for any available options.

# BID SUBMITTAL FORM: OPTION COST SHEET 3 CY WHEEL LOADER - OPTION C

By submitting this bid, we agree:	
To offer any available options at the percent difference between the Manufacturer's Suggested Retail Price Sheet and the actual bid price on the Standard Machine*	H
The bid documents include the Manufacturer's Suggested Retail Price Sheet (MSRP) with any available Options for the Standard Machine	96
Equipment Model #:Volvo L70H	
Description:Wheel Loader	
Signature of company representative submitting bid:	
Title: Governmental Sales Manager	

\*Note: The percent difference between the Manufacturer's Suggested Retail Price Sheet (MSRP) for the standard machine as specified by these Bid Specifications and the actual price bid by the vendor will be calculated to determine the percentage discount to be applied to any available options. The bid price of the freight preparation, delivery cost shall be excluded in determining the percentage discount to be applied to available options. Any individual county may choose to add any available option to the standard machine at the percentage discount at the time of purchase.

# BID SPECIFICATIONS FOR 3 CY WHEEL LOADER - OPTION C

#### **GENERAL**

These specifications shall be construed as the minimum acceptable standards for a 3-yard wheel loader. Should the manufacturer's current published data or specifications exceed these standards, the manufacturer's standards shall be considered minimum and shall be furnished. All integral parts not specifically mentioned in the scope of these specifications that are necessary to provide a complete working unit shall be furnished. Additionally, the machine offered for bid shall include all standard manufacturer's equipment. The wheel loader must be a new current production model and shall meet all EPA and other applicable standards at the time of manufacturer.

The use of specific names and numbers in the specification is not intended to restrict the bidder or any seller or manufacturer, but is intended solely for the purpose of indicating the type, size and quality of equipment considered best adapted to the uses of counties participating in this joint bid.

#### **BID SUBMITTAL FORM**

Each bidder must submit his or her bid on the Bid Submittal Form included in the Invitation to Bid package. All written warranties to be submitted shall be attached to the Bid Submittal Form.

#### **BID PRICE**

The bid price shall include all destination charges, delivery charges, title fees, rebates, and all other applicable costs and refunds.

#### **MANUALS**

Each unit shall be provided with one (1) copy of the operator's manual, one (1) copy of the repair manual and one (1) copy of the current parts manual. Units will not be accepted for delivery until the manuals as outlined above are received by the purchaser.

#### REPLACEMENT PARTS AVAILABILITY

Parts must be available for 5 years or 7,500 hours of use for the piece of equipment bid. If replacement parts are not delivered within three (3) working days of an order being placed, the bidder will deliver ann equivalent machine for the county to use at no cost to the county until such time as the parts are delivered to the county so it can affect repairs on its machine.

#### WARRANTY

Bidders shall submit a copy of the manufacturer's standard warranty. Warranty shall include service response time of maximum of 36 hours within notification by county.

Yes \_\_\_\_\_ No Page #\_\_\_\_ or Attachment \_\_\_\_

## **DUMP CLEARANCE**

The wheel loader dump clearance shall be no less than **9' 1"** at full height and 45 degree dump angle with a double arm Z bar configuration

Yes \_\_\_No\_\_\_ Page #\_\_22

### **STEERING**

The wheel loader shall have a 40-degree full turn articulation steering angle both right and left of center.

Yes \_\_\_\_\_No \_\_\_\_ Page #\_\_\_19

### **OPERATOR STATION**

-Cab shall be designed and built by the loader manufacturer.

Yes \_\_\_\_No \_\_\_ Page #\_\_18

-Cab shall be enclosed and equipped with heater, air conditioner

Yes \_\_\_\_No \_\_\_ Page #\_\_26

Loader shall meet ROPS/FOPS regulations standard in North America.

Yes No\_\_\_\_ Page #\_\_\_19

-Loader shall have easy to read gauges, gear selection, direction and RPM readings.

Yes \_\_\_\_No \_\_\_ Page #\_\_\_19 -Loader shall have a standard hydraulic joystick which controls both lift and tilt functions. A remote transmission control switch on joystick to be standard.

Yes	/	No	
Page	#	26	

Loader shall have fully adjustable, air suspension seat. Loader shall be equipped with a Fire Extinguisher

-Loader shall have retractable 3" seat belt.

**POWERTRAIN** 

-Engine must have a minimum of six (6) cylinders and turbocharged and designed and manufactured by machine manufacturer.

-The loader shall be equipped with crankcase and powertrain guards.

-All powertrain components shall be designed and built by loader manufacturer.

-The engine shall have a minimum net HP of 165 at 1800 RPM with a minimum displacement of 348 cubic inches and 610 lbs. /ft. torque.

-The engine shall meet all Tier 4/final emission requirements

Loader shall have electronic module to control engine timing and monitoring of vital engine systems.

Loader shall have fixed front axle with locking differential and oscillating rear axle (±11°) with open differential.		
	Yes No	
	YesNo Page #_17	
-Loader shall have fully enclosed, adjustment free oil-disc brakes.		
	YesNo Page #17	
	Page # <u>17</u>	
-Unit shall be equipped with 20.5 R25 L3 XHA tires.	Yes <u>•</u> No Page #_19	
	r age #	
-Loader shall have powershift transmission designed and built by manufacturer.  The loader shall have at minimum <b>4-forward/4</b> reverse with a minimum travel speed forw	ard	
of 27 mph and reverse of 27 mph.		
	Yes <u>~No</u> Page #17	
	raye #_ 13	
-Loader shall have computer-controlled modulation for smoother shifting.		
	Yes No	
	YesNo Page #17	
-Loader shall have manual shifting as well as auto shifting options. Auto shift will have full	throttle (aggressive	
operation) and variable shift (economy mode) options.	(-39	
	Yes <u> </u>	
INSTRUMENTATION	Page #_1/	
INSTRUMENTATION -The wheel loader shall include the following gauges: hour meter, fuel, transmission or torque converter oil		
temperature and engine coolant temperature.	-	
	Yes • No	
	Yes No Page #17	

ne wheel loader shall also include the following indicator lights: battery charge, engine oil pressure, lov plant level, parking brake warning, and low		
brake pressure.	Yes No	
	Page #_17	
HYDRAULIC SYSTEM:		
-Shall have a minimum flow of <b>40</b> gallons/minute.		
· ·	Yes VNo	
	Page #18	
WORK TOOLS -Bucket shall be designed and built by the loader manufacturer.	Yes <u></u> √No	
Buoket shall be designed and balk by the leader manadetaien	Page #_ 22	
-Bucket shall be in 3.0 CYD capacity (with bolt-on cutting edges and teeth).  SERVICEABILITY	Yes <u></u> No Page #_ 22	
-All daily service points shall be accessible from the ground level and shall have sight ga coolant, hydraulic oil and transmission oil.		
-All filters shall be vertically mounted and spin-on for ease of service and to prevent spilli	ng during service.	
	Yes <u>►</u> No Page # 24-25	
GENERAL Unit shall be equipped with vandalism protection with locking service ports, cushioned steering stops, front fenders, and toolbox in addition to all other Standard equipment		
	Yes <u>✓</u> No Page #_25	

# **OPERATING WEIGHT AND LIFT CAPACITIES**

-Unit shall be minimum of **29,000** lbs. operating and proper ballasting for **3.0** cubic yard bucket and 20.5-25 radial (L-3) tires.

-Straight static tipping load shall be a minimum of 21,700 lbs.

-Full turn (40°) static tipping load shall be a minimum of 18,700 lbs.

-Breakout force shall be a minimum of 22,000 lbs.