

BID SUBMITTAL FORM
Alabama County Joint Bidding Program
BID ITEM – TRACK-MOUNTED EXCAVATOR OPTION A3

Company Name: THOMPSON TRACTOR COMPANY

Address: P.O. BOX 10367

BIRMINGHAM, AL 35202-0367

Bid Submitted by: JAY SMITH
(Name of company representative)

Title: SALES OPERATIONS MANAGER e-mail address: JAYSMITH@THOMPSONTRACTOR.COM

Phone: (205) 849-4242 Fax: (205) 849-4394

By submitting this bid, we agree:

Initials

The equipment model number identified below meets the bid specs for this bid item

JAS

That the bid price will be honored for all counties for the period from Jan. 1, 2019 to Dec. 31, 2019.

JAS

The equipment will be delivered at the bid price to all counties participating in the joint bid program

JAS

The company representative listed above will be the contact person for purchasing this bid item under the joint bid program

JAS

The bid is accompanied by a current catalog or model specification document for the model number identified below

JAS

The bid is accompanied by a copy of the manufacturer's standard warranty as required in the bid specifications

JAS

The bid includes the e-verify documentation required by Alabama law

JAS

If awarded the bid, a performance bond will be provided upon request

JAS

The bid documents include the **Manufacturer's Suggested Retail Price Sheet (MSRP) for the Standard Machine**

JAS

TRACK-MOUNTED EXCAVATOR OPTION A3

Total Bid Price for Standard Machine: \$ 259,185


(Total Bid Price for Standard Machine Includes Freight Preparation, Delivery and Standard Warranty Costs)*

Freight Preparation and Delivery: \$ 6,922
(Included in Standard Machine Bid Price)

Manufacturer's Suggested Retail Price for Standard Machine: \$ 334,123 ✓

Equipment Model #: 330

Description: HYDRAULIC EXCAVATOR

Signature of company representative submitting bid: 

Title: SALES OPERATIONS MANAGER

* **NOTE:** Award will be made based on the total cost of the **Standard Machine**. The total cost of the standard machine is to include the freight preparation, delivery and standard warranty cost. Freight preparation, delivery will be excluded from the total bid price of the standard machine in determining the percentage discount for any available options.

BID SUBMITTAL FORM: OPTION COST SHEET TRACK-MOUNTED EXCAVATOR OPTION A3

By submitting this bid, we agree:

To offer any available options at the percent difference between the Manufacturer's Suggested Retail Price Sheet and the actual bid price on the Standard Machine*

QAS

The bid documents include the Manufacturer's Suggested Retail Price Sheet (MSRP) with **any available Options** for the Standard Machine

QAS

Equipment Model #: 330

Description: HYDRAULIC EXCAVATOR

Signature of company representative submitting bid: _____



Title: SALES OPERATIONS MANAGER

***Note:** The percent difference between the **Manufacturer's Suggested Retail Price Sheet (MSRP)** for the standard machine as specified by these **Bid Specifications** and the actual price bid by the vendor will be calculated to determine the percentage discount to be applied to any available options. The bid price of the freight preparation, delivery cost shall be excluded in determining the percentage discount to be applied to available options. Any individual county may choose to add any available option to the standard machine at the percentage discount at the time of purchase.

BID SPECIFICATIONS FOR TRACK-MOUNTED EXCAVATOR OPTION A3

GENERAL

These specifications shall be construed as the minimum acceptable standards for a track mounted hydraulic excavator with long undercarriage. Should the manufacturer's current published data or specifications exceed these standards, the manufacturer's standards shall be considered minimum and shall be furnished. All integral parts not specifically mentioned in the scope of these specifications that are necessary to provide a complete working unit shall be furnished. Additionally, the machine offered for bid shall include all standard manufacturers' equipment. The excavator must be a new current production model and shall meet or exceed all EPA and other applicable standards at the time of manufacture.

Use of specific names and numbers in the specifications is not intended to restrict the bidder or any seller or manufacturer, but is intended solely for the purpose of indicating the type, size and quality of equipment considered best adapted to the uses of the counties participating in this joint bid.

BID SUBMITTAL FORM

Each bidder must submit his or her bid on the bid submittal form included in the invitation to bid package. All written warranties to be submitted shall be attached to the bid submittal form.

BID PRICE

The price bid shall include all destination charges, delivery charges, title fees, rebates, and all other applicable costs and refunds.

MANUALS

Each unit shall be provided with one (1) copy of the operator's manual, one [1] repair manual, and one (1) copy of the current parts manual. Units will not be accepted for delivery until the manuals as outlined above are received by the purchaser.

REPLACEMENT PARTS AVAILABILITY

Parts must be available for 5 years or 7,500 hours of use for the piece of equipment. If any replacement parts are not delivered within three (3) working days of an order being placed, the bidder will deliver an equivalent machine for the county to use at no cost to the county until such time as the parts are delivered to the county so it can affect repairs to its machine.

WARRANTY

Bidders shall submit a copy of the manufacturer's standard warranty. Warranty shall include service response time of maximum of 36 hours within notification by county.

Yes ☒ No ☐
Page#
or
Attachment ☒

WEIGHT

Minimum 66,000 lbs. equipped with minimum 31 inch wide track shoes. ✓

Yes X No
Page # 1

ENGINE

Turbocharged, 6 cylinders with a minimum 420 cubic inch displacement diesel engine capable of a minimum 235 net horsepower.

Yes X No
Page # 6, 18 ✓

Engine shall be manufactured by the equipment manufacturer.

Yes X No
Page # 6, 7, 17 ✓

SWING MECHANISM

Maximum Swing Torque shall be a minimum of 77,000 lbf-ft.

60,628 18-ft

Yes No X
Page # 18

UNDERCARRIAGE

Track length shall be minimum 15' 11".

Yes X No
Page # 19

Track shoe width shall be minimum 31" (Triple grouser Shoes)

Yes X No
Page # 22

Minimum nine (9) track rollers per side.

Yes X No
Page # 18

Minimum two (2) carrier rollers per side.

Yes X No
Page # 18

STARTING SYSTEM

24 volt system with a minimum 115 amp alternator.

Yes X No
Page # 33

CAPACITIES

Fuel Tank Capacity – 136 gallon minimum

Yes X No
Page # 18

Hydraulic Tank Capacity – 45 gallon minimum

Yes X No
Page # 18

Engine Coolant – 7 gallon minimum

Yes X No
Page # 18

BOOM AND STICK

One piece boom with minimum 20' length

Yes X No
Page # 19

Stick shall be a minimum 10' long

Yes X No
Page # 19, 20, 23

DIMENSIONS

Reach at ground level – 35' minimum

Yes X No
Page # 20

Bucket breakout force (SAE) – minimum 35,500 lbs.

Yes X No
Page # 23

Stick digging force (SAE) – minimum 27,500 lbs.

Yes X No
Page # 23

Bucket:

Standard with no bucket. Buckets will be considered optional attachment's.

HYDRAULICS

Hydraulic pump output shall be a minimum of 130 GPM

Yes X No
Page # 18

CAB

Enclosed ROPS cab:

Yes X No
Page # 33

Heater

Yes X No
Page # 5, 15

Factory installed air conditioning

Yes X No
Page # 5, 15

AM/FM radio

Yes X No
Page # 33

Suspension seat

Yes X No
Page # 34

Defroster

Yes X No
Page # 5, 15

Shall be equipped with a 12-volt converter capable of powering a two-way radio.

Yes X No
Page # 5