BID SUBMITTAL FORM

Alabama County Joint Bidding Program BID ITEM – 16' STEEL DUMP BODY OPTION D (AUTOMATIC)

Company Name: Warren Truck & Trailer, Inc.	
Address: 3716 Richard Arrington Jr. Blvd. N.	
Birmingham, AL 35234	
Bid Submitted by: Drew Dearman (Name of company representative)	
Title: Sales Manager e-mail address: DDEARMAN@DUMF	TRUCKS.COM
Phone: 205-254-9700 Fax: 205-591-3012	
By submitting this bid, we agree:	Initials
That the equipment model number identified below meets the bid specs for this bid item	DD
That the bid price will be honored for all counties for the period from Jan. 1, 2020 to Dec. 31, 2020.	DD
That the equipment will be delivered at the bid price to all counties participating in the joint bid program	DD
That the company representative listed above will be the contact person for purchasing this bid item under the joint bid program	<u>DD</u>
That the bid is accompanied by a current catalog or model specification document for the model number identified below	DD
That the bid is accompanied by a copy of the manufacturer's standard warranty as required in the bid specifications	DD
That the bid includes the e-verify documentation required by Alabama law	DD
That, if awarded the bid, a performance bond will be provided upon request	DD
That an option sheet with individual pricing is attached	<u>DD</u>
Total Bid Price including options: \$ 27,642.00	
Equipment Model #: WAR-16	
Description: 16' ELLIPTICAL DUMP BODY	
Signature of company representative submitting bid:	-

OPTION COST SHEET FOR 16' STEEL DUMP BODY OPTION D (AUTOMATIC TRANSMISSION)

Tri Axle Option Items	Option Price	
Silent Drive or equal lift axle	\$ <u>4682.00</u>	
Four Steel Disc, Ten hole, hub piloted, bud style 22.5x8.25 wheels on lift axle	\$ <u>320.00</u>	
Four 11R22.5 recap tires on lift axle	<u>\$720.00</u>	
Other Options	Option Price	
High lift tail gate	\$ <u>995.00</u>	
Bed body vibrator	\$ <u>500.00</u>	
25 ton heavy duty Pintle Hitch	\$ <u>995.00</u>	
Chip Spreader bar mounted	<u>\$150.00</u>	
NOTE: Award will be made on the basis of the total cost of the machine with all options included. However, a county may, at its discretion, deduct one or more of the above-referenced options from the machine, and in such event, the cost of the option as stated on the bid shall be deducted from the total cost of the machine. There shall be no other deductions and no additions made to the machine by the purchasing county or by the vendor.		
Equipment Model #: WAR-16		
Description: 16' ELLIPTICAL DUMP BODY		
Signature of company representative submitting bid:		
Title: Sales Manager		

BID SPECIFICATIONS FOR 16' STEEL DUMP BODY OPTION D (AUTOMATIC TRANSMISSION)

GENERAL

These specifications shall be construed as the minimum acceptable standards for a 16' Steel Dump Body. Should the manufacturer's current published data or specifications exceed these standards, the manufacturer's standards shall be considered minimum and shall be furnished. All integral parts not specifically mentioned in the scope of these specifications that are necessary to provide a complete working unit shall be furnished. Additionally, the machine offered for bid shall include all standard manufacturer's equipment. The 16' Steel Dump Body must be a new current production model.

The use of specific names or numbers in the specifications is not intended to restrict the bidder or any seller or manufacturer, but is intended solely for the purpose of indicating the type, size, and quality of equipment considered best adapted to the uses of counties participating in this joint bid.

BID SUBMITTAL FORM

Each bidder must submit his or her bid on the Bid Submittal Form included in the invitation to bid package. All written warranties to be submitted shall be attached to the Bid Submittal Form.

BID PRICE

The price bid shall include all destination charges, delivery charges, title fees, rebates and all other applicable costs and refunds.

REPLACEMENT PARTS AVAILABILITY

Parts must be available for 5 years or 500,000 miles of use for the piece of equipment bid.

ASSEMBLY AND DELIVERY

The dump body will be purchased for use with a heavy duty dump truck chassis (with Automatic Transmission) bid separately. The dump body company will be responsible for assembly and installation of the dump body and related optional equipment, including the cost of the same. The selling truck chassis dealer will be responsible for delivery of the chassis to the dump body company, for installation and for delivery of the complete dump truck unit to the county following installation, and assembly of the dump body and related options onto the truck chassis. Freight to and from the dump Body Company will be included in the truck bidder's proposal. Dump body installation and assembly costs will be included in the dump body bidder's proposal.

WARRANTY

Bidders shall submit a copy of the manufacturer's standard warranty.

Yes___No___ Page#_4 or Attachment **DUMP BODY** Dump body shall meet all federal and state, health and safety regulations and must conform to American National Standard Institute (A.N.S.I.) Regulations Yes V No Page #4 (A.N.S.I.Z145) 1975. Yes V No Page #4-5 Dump body supplier must have their own service and parts facility. Dump body supplier must have a minimum of five (5) years experience in sales, Yes____No ___ Page #_4-5 service and repair of dump bodies. Yes<u>✓</u>No ___ Page #<u>5</u> Body must be covered by product liability insurance. GENERAL SPECIFICATIONS AND DIMENSIONS 21.0 cubic yard capacity; elliptical dump body design with 26 inch radius beginning at body main rails; 16 feet long; 62-inch high sides; 62- inch high tailgate; sides, floor and tail-gate shall be 1/4 inch AR450 Steel; 8-inch I-beam long runners; tailgate shall be vertical (NO SLOPE); single panel (picture-frame) tailgate design; hoist shall be class 120 hoist with a minimum four (4) active stages and minimum 60,000 pound capacity; direct mount integral pump and P.T.O. combination with air control on the P.T.O.; air tailgate latch control; tailgate shall be built for future high lift tailgate conversion; electric tarp with vinyl asphalt type tarp; 42 inch cab shield; eight (8) inch wide schedule 80-pipe push bar asphalt apron across rear of body; inverted angle on top of sides and top of tailgate; and Metro light kit. TRI AXLE OR HEAVY DUTY DUMP TRUCK CHASSIS OPTIONS

The chassis (with Automatic Transmission) will be used as a tri axle dump or a heavy duty tandem dump. All bids shall include the cost for each of the following options to be selected for a tri axle dump, itemized separately on the bid:

Silent Drive Lift (Pusher) axle (20,000 lb minimum Capacity) or equal. This axle shall be air up and air down with a control valve and regulator located in the cab within reach of the operator.

Yes ______No _____
Page #2

Four (4) steel disc, ten (10) hole, hub piloted, bud style 22.5x8.25, wheels on lift axle.

Yes ______No ____
Page #2

Four 11R22.5 recap tires on lift axle.

Yes ______No ____
Page #2

Yes ______No ____
Page #2

OTHER OPTIONS

Bid must include the cost for each of the following options, itemized separately on the bid:

High lift tail gate	Yes No Page #1
Bed body vibrator	Yes VNo Page #2
25 ton heavy duty Pintle Hitch, swivel type, spring loaded, with safety chain rings, mounted on 1" minimum steel plate supported by ½" X 4" gussets; ¾" D rings; Glad Hands mounted with 5" X 3/8" air brake line to a ½" bulkhead fitting through the plate with cut off valves on side of plate; seven (7) prong trailer light socket and air brakes hookup. Mounted 26 inches ground with truck empty.	back
Chip spreader bar mounted at end of frame.	Yes VNo Page #2

NOTE: Award will be made on the basis of the total cost of the dump body with all options included. However, a county may, at its discretion, deduct one or more of the above-referenced options from the dump body, and in such event, the cost of the options as stated on the bid shall be deducted from the total cost of the dump body. There shall be no other deductions and no additions made to the dump body by the purchasing county or by the vendor.