

BID SUBMITTAL FORM
Alabama County Joint Bidding Program
Heavy Equipment – Bid Items: Skid Steer Attachments

Company Name: CAPITAL TRACTOR, INC.

Address: 1498 FURNACE ST.

MONTGOMERY, AL 36104

Bid Submitted by: CALEB GREER
(Name of company representative)

Title: SALES REP. e-mail address: CALEBGREER@CAPITALTRACTOR.COM

Phone: 334-264-0086 Fax: 334-264-0094

By submitting this bid, we agree:

Initials

The equipment model number identified below meets the bid specs for this bid item



That the bid price will be honored for all counties for the period from Jan. 1, 2020 to Dec. 31, 2020.



The equipment will be delivered at the bid price to all counties participating in the joint bid program.



The company acknowledges the freight preparation and delivery price is to be included in the total bid price for the standard machine.



The company representative listed above will be the contact person for purchasing this bid item under the joint bid program.



The bid is accompanied by a current catalog or model specification document for the model number identified below.



The bid is accompanied by a copy of the manufacturer's standard warranty as required in the bid specifications.



The bid includes the e-verify documentation required by Alabama law.




If awarded the bid, a performance bond will be provided upon request.



The bid documents include the **Manufacturer's Suggested Retail Price Sheet (MSRP) for the Standard Machine.**



SKID STEER LOADER ATTACHMENTS



SKID STEER LOADER ATTACHMENTS

Attachment 4: ANGLE BROOM


Total Bid Price for Standard Machine: \$ 7,230.00
(Total Bid Price for Standard Machine Includes Freight Preparation, Delivery and Standard Warranty Costs) *

Freight Preparation and Delivery: \$ 300.00
(Included in Standard Machine Bid Price)

Manufacturer's Suggested Retail Price for Standard Machine: \$ 7,869.00


Equipment Model #: 22084MH-0022

Description: 84" ANGLE BROOM

Signature of company representative submitting bid: 

Title: SALES REP.

SKID STEER LOADER ATTACHMENTS



SKID STEER LOADER ATTACHMENTS

*** NOTE:** Award will be made based on the total cost of the **Standard Machine**. The total cost of the standard machine is to include the freight preparation, delivery and standard warranty cost. Freight preparation, delivery will be excluded from the total bid price of the standard machine in determining the percentage discount for any available options.

BID SUBMITTAL FORM: OPTION COST SHEET

By submitting this bid, we agree:

To offer any available options at the percent difference between the Manufacturer's Suggested Retail Price Sheet and the actual bid price on the Standard Machine*



The bid documents include the **Manufacturer's Suggested Retail Price Sheet (MSRP)** for the Standard Machine



Equipment Model #: 22084, 105063, 105067, 103030

Description: SWEEPER, VIB. ROLLER, PAD FOOT ROLLER, COLD PLANK

Signature of company representative submitting bid: Donald E. Green

Title: SALES REP.

***Note:** The percent difference between the **Manufacturer's Suggested Retail Price Sheet (MSRP)** for the standard machine as specified by these **Bid Specifications** and the actual price bid by the vendor will be calculated to determine the percentage discount to be applied to any available options. The bid price of the freight preparation, delivery cost shall be excluded in determining the percentage discount to be applied to available options. Any individual county may choose to add any available option to the standard machine at the percentage discount at the time of purchase.

SPECIFICATIONS FOR SKID STEER LOADER ATTACHMENTS

GENERAL

These specifications shall be construed as the minimum acceptable standards for attachments compatible with the skid steer loader specifications. Should the manufacturer's current published data or specifications exceed these standards, the manufacturer's standards shall be considered minimum and shall be furnished. All integral parts not specifically mentioned in the scope of these specifications that are necessary to provide complete working unit(s) shall be furnished. Additionally, the attachments offered for bid shall include all standard manufacturers' equipment. The attachments bid must be a new current production model and shall meet all EPA and other applicable standards at the time of manufacture.

The use of specific names or numbers in the specifications is not intended to restrict the bidder or any seller or manufacturer, but is intended solely for the purpose of indicating the type, size, and quality of equipment considered best adapted to the uses of counties participating in this joint bid.

Bidder is not required to bid on every attachment listed in this bid specification. Each attachment will be awarded individually to the lowest responsible bidder for that item.

BID SUBMITTAL FORM

Each bidder must submit his or her bid on the Bid Submittal Form included in the invitation to bid package. All written warranties to be submitted shall be attached to the Bid Submittal Form.

BID PRICE

The price bid for each attachment bid shall include all destination charges, delivery charges, title fees, rebates and all other applicable costs and refunds.

MANUALS

Each attachment shall be provided with one (1) copy of the owner/operator's manual for that attachment.

WARRANTY

Bidders shall submit a copy of the manufacturer's standard warranty along with a complete explanation of the warranty with their bid. All attachments must have (1) year warranty with no hour limit.

Yes ☒ No ☐
Page# 1
or
Attachment ☒

All skid steer attachments listed below must be of the universal quick attach type and must be fully compatible with the skid steer loader to be awarded. As such, the attachment must be compatible with the bid specifications for the skid steer loader.

Yes ☒ No ☐
Page # 407

Yes ☒ No ☐
Page # 407

ATTACHMENT #3 GRADER BLADE

Motorgrader style 8' moldboard with replaceable cutting edges

Yes ☐ No ☐
Page # ☐

No Bid

2 front guide wheels with center oscillating pivot point

Yes ☐ No ☐
Page # ☐

In-cab hydraulic control box of blade height, angle, and tilt

Yes ☐ No ☐
Page # ☐

Proportional current valve for gradual adjustment of blade

Yes ☐ No ☐
Page # ☐

2 removable blade end plates

Yes ☐ No ☐
Page # ☐

Compatible with laser control system

Yes ☐ No ☐
Page # ☐

Weight 1200 lbs.

Yes ☐ No ☐
Page # ☐

Length 101"

Yes ☐ No ☐
Page # ☐**ATTACHMENT #4 ANGLE BROOM**

Hydraulic motor with hydraulic angle control

Yes ☒ No ☐
Page # 12

Weight 900 lbs

Yes ☒ No ☐
Page # 12

Straight Path 84"

Yes ☒ No ☐
Page # 12

Angled Path 75"

Yes ☒ No ☐
Page # 12

Angle 30 degrees

Yes ☒ No ☐
Page # 12

Brush Diameter 32"

Yes ☒ No ☐
Page # 12

Brush Material 50 poly/50 wire

Yes ☒ No ☐
Page # 12

ATTACHMENT #5 COLD PLANER

In cab electric control box to control unit

Yes ☒ No ☐
Page # 174

Depth gauge

Yes ☒ No ☐
Page # ~~174~~ 2

Access door for access to drum

Yes ☒ No ☐
Page # 174

Working Width 40"

Yes ☒ No ☐
Page # 174

Weight 3100 lbs

Yes ☒ No ☐
Page # 174

Hydraulic Requirements 40 gpm

Yes ☒ No ☐
Page # 174

Max. Milling Depth 5"

Yes ☒ No ☐
Page # 174

Side shift -3" to 22"

Yes ☒ No ☐
Page # ~~174~~ 2

Tilt +/- 8 degrees

Yes ☒ No ☐
Page # 2

ATTACHMENT #6: ROAD WIDENER-SINGLE DISCHARGE

Hydraulic-driven conveyor

10" Head and Tail Pulleys

Right or left side discharge

Hydraulic width/height adjustment

Adjustable shouldering angle

Width 10'2"

Length 7'6"

Height 4'3"

Working Width 1 – 3.5'

Weight (Empty) 2600 lbs.

Yes ___ No ___
Page # ___

Yes ___ No ___
Page # ___

Yes ___ No ___
Page # ___

Yes ___ No ___
Page # ___

Yes ___ No ___
Page # ___

Yes ___ No ___
Page # ___

Yes ___ No ___
Page # ___

Yes ___ No ___
Page # ___

Yes ___ No ___
Page # ___

Yes ___ No ___
Page # ___

No Bid

ATTACHMENT #7: ROAD WIDNER DUAL DISCHARGE

Hydraulic-driven conveyor

Yes ☐ No ☐
Page # ☐

No Bid

10" Head and Tail Pulleys

Yes ☐ No ☐
Page # ☐

Right and left side discharge

Yes ☐ No ☐
Page # ☐

Hydraulic width/height adjustment

Yes ☐ No ☐
Page # ☐

Adjustable shouldering angle

Yes ☐ No ☐
Page # ☐

Width 10'2"

Yes ☐ No ☐
Page # ☐

Length 7'6"

Yes ☐ No ☐
Page # ☐

Height 4'3"

Yes ☐ No ☐
Page # ☐

Working Width 1 – 3.5'

Yes ☐ No ☐
Page # ☐

Weight (Empty) 2600 lbs.

Yes ☐ No ☐
Page # ☐

ATTACHMENT #8: MULCHING ATTACHMENT

MINIMUM SPECIFICATIONS FOR MULCHING ATTACHMENT

Weight 2,250 lbs.

Yes ☐ No ☐
Page # ☐

No Bid

Horsepower rating 125

Yes ☐ No ☐
Page # ☐

RPM speed of spindle shaft 1,900

Yes ☐ No ☐
Page # ☐

Cutting width 58"

Yes ☐ No ☐
Page # ☐

Overall width	72"	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Page # <u> </u>
Fixed replaceable carbide cutting hammers (qty)	28	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Page # <u> </u>
Rated hydraulic flow	30 – 40 gal	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Page # <u> </u>
Hydraulic deflector door		Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Page # <u> </u>
4" diameter hydraulic pressure sight gauge which reads UP TO 6000 psi.		Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Page # <u> </u>
Rotor diameter including hammers	17.5"	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Page # <u> </u>
Rotor tube wall thickness	$\frac{3}{4}$ "	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Page # <u> </u>
Rotor shaft diameter	$\frac{3}{8}$ "	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Page # <u> </u>
Rotor shaft attached inside of tube with (4) sweat collars		Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Page # <u> </u>
Lower bearing boxes equipped with dual spherical bearings with tapered lock system		Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Page # <u> </u>
Upper bearing box assembly for hydraulic motor equipped with dual tapered bearings		Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Page # <u> </u>
PD drive belt and matching drive pulley system		Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Page # <u> </u>
2 – Position adjustable lower skid plates		Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Page # <u> </u>
3 – Position adjustable push bar		Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Page # <u> </u>