BID SUBMITTAL FORM Alabama County Joint Bidding Program Heavy Equipment – BID ITEM: RIDE ON INDUSTRIAL BOOM MOWER

Company Name: CoblENTZ EQUIPMENT & PARTS CO., INC.	
Address: 10400 HIGHWAY 80E	
MONTHOMERY, AL 36117	
Bid Submitted by: MATTHEW CORVENTZ (Name of company representative)	
Title: <u>VP</u> E-mail address: <u>matthew@coblentz</u>	**
Phone: 334-215-8600 Fax: 334-215-8532	
By submitting this bid, we agree:	Initials
The equipment model number identified below meets the bid specs for this bid item.	DMC
That the bid price will be honored for all counties for the period from Jan. 1, 2021 to Dec. 31, 2021.	DMC
The equipment will be delivered at the bid price to all counties participating in the joint bid program.	DMC
The company acknowledges the freight preparation and delivery price is to be included in the total bid price for the standard machine.	PMC
The company representative listed above will be the contact person for purchasing this bid item under the joint bid program.	DAC
The bid is accompanied by a current catalog or model specification document for the model number identified below.	DMC
The bid is accompanied by a copy of the manufacturer's standard warranty as required in the bid specifications.	DMC
The bid includes the e-verify documentation required by Alabama law.	DMC
If awarded the bid, a performance bond will be provided upon request.	Pac
The bid documents include the Manufacturer's Suggested Retail Price Sheet (MSRP) for the Standard Machine.	DMC

22 Foot Boom Model including 1,400 lb. counterweight
Total Bid Price for Standard Machine: \$ <u>「んり,ハコ」。゜</u> (Total Bid Price for Standard Machine Includes Freight Preparation, Delivery and Standard Warranty Costs) *
Freight Preparation and Delivery: \$\750. °(Included in Standard Machine Bid Price)
Manufacturer's Suggested Retail Price for Standard Machine: \$ 158,900.
Equipment Model #:
Description: RIDE-ON BOOM MOVER W/ 22' LONG ARM, AddITIONAL 1400 lbs COUNTERWEIGHT
* Mower Max OFFERS A ONE PRICE STRATEGY. THEY DO NOT OFFER AN INFLATED
SUGGESTED RETAIL PRICE,
24 Foot Boom Model including 1,400 lb. counterweight
Total Bid Price for Standard Machine: \$\(Total Bid Price for Standard Machine Includes Freight Preparation, Delivery and Standard Warranty Costs) *
Freight Preparation and Delivery: \$\(\sigma^2\) (Included in Standard Machine Bid Price)
Manufacturer's Suggested Retail Price for Standard Machine: \$ 158,900.00
Equipment Model #: Mover Max Boom
Description: RIDE-ON BOOM MOWER W/ 24' LONG ARM, ADDITIONAL 1,400 ILS COUNTERWEIGHT NO FRONT HITCH OR BOOM ARM HEADS.
* MONERMAX OFFERS A ONE PRICE STRATEGY. THOY DO NOT OFFER AN INFLATED SIGGESTED RETAIL 26 Foot Boom Model which including 1,400 lb. counterweight
Total Bid Price for Standard Machine: \$\(\odolor 5,000\). (Total Bid Price for Standard Machine Includes Freight Preparation, Delivery and Standard Warranty Costs) *
Freight Preparation and Delivery: \$150. ** (Included in Standard Machine Bid Price)
Manufacturer's Suggested Retail Price for Standard Machine: \$_\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
Equipment Model #: Mower Max Boom
Description: RIDE-ON BOOM MOWER W/ 26 LONG ARM, ASTRONAL 1,400 165 COUNTERWEGHT
No FRONT HIRUT OR BOOM ARMHEADS
* MOWERMAX OFFERS A ONE PAICE STRATEGY. THEY DO NOT OFFER AN INFLATED SUGGESTED

Total Bid Price for Standard Machine: \$\\(\frac{169}{400}, \frac{400}{50}\) (Total Bid Price for Standard Machine Includes Freight Preparation, Delivery and Standard Warranty Costs) *
Freight Preparation and Delivery: \$(Included in Standard Machine Bid Price)
Manufacturer's Suggested Retail Price for Standard Machine: \$1\(\sigma_1, 9\infty\).**
Equipment Model #: Mower Max Boom
Description: RIDE-DN BOOM MOWER W/ 30' TELESCOPING LONG ARM, INCLUDES 2 ADDITIONAL 1,400 lbs CWs, No FRONT HITCH OR BOOM ARM HEADS
* Mower Max Offers A ONE PRICE STRATEGY. TITEY DO NOT OFFER AN INFLATED SUGGESTED RETAIL Signature of company representative submitting bid:
Title: Vict PRESIDENT

30 Foot Boom Model including 3.450 lb. counterweight with integrated steps

^{*} NOTE: Award will be made based on the total cost of the **Standard Machine**. The total cost of the standard machine is to include the freight preparation, delivery and standard warranty cost. Freight preparation, delivery will be excluded from the total bid price of the standard machine in determining the percentage discount for any available options.

BID SUBMITTAL FORM: OPTION COST SHEET

By submitting this bid, we agree:

To offer any available options at the percent difference between the Manufacturer's Suggested Retail Price Sheet and the actual bid price on the Standard Machine*
* Mower Max Offers A One Price Strategy, They B Not Offer AN Inflated Suggested The bid documents include the Manufacturer's Suggested Retail Price Sheet (MSRP) RETAIL PRICE for the Standard Machine
Equipment Model #: MONERMAX BOOM Description: RIDE-ON BOOM MONER
Signature of company representative submitting bid:
Title: Vice President

*Note: The percent difference between the Manufacturer's Suggested Retail Price Sheet (MSRP) for the standard machine as specified by these Bid Specifications and the actual price bid by the vendor will be calculated to determine the percentage discount to be applied to any available options. The bid price of the freight preparation, delivery cost shall be excluded in determining the percentage discount to be applied to available options. Any individual county may choose to add any available option to the standard machine at the percentage discount at the time of purchase.

BID ITEM: RIDE-ON INDUSTRIAL BOOM MOWER WITH UNIVERSAL ATTACHMENT PLATE

GENERAL

These specifications shall be construed as the minimum acceptable standards for a ride-on industrial boom mower with universal attachment plate and mowing arm. Should the manufacturer's current published data or specifications exceed these standards, the manufacturer's standards shall be considered minimum and shall be furnished. All integral parts not specifically mentioned in the scope of these specifications that are necessary to provide a complete working unit shall be furnished. Additionally, the machine offered for bid shall include all standard manufacturer's equipment. The machine must be a new current production model and shall meet all EPA and other applicable standards at the time of manufacture.

The use of specific names and numbers in the specifications is not intended to restrict the bidder or any seller or manufacturer, but is intended solely for the purpose of indicating the type, size and quality of equipment considered best adapted to the uses of counties participating in this joint bid.

BID SUBMITTAL FORM

Each bidder must submit his or her bid on the Bid Submittal Form included in the invitation to bid package. All written warranties to be submitted shall be attached to the Bid Submittal Form.

BID PRICE

The price bid shall include all destination charges, delivery charges, title fees, rebates, and all other applicable costs and refunds.

MANUALS

Each unit shall be provided with one (1) copy of the operator's manual, (1) copy of the repair manual and one (1) copy of the current parts manual. Units will not be accepted for delivery until the manuals as outlined above are received by the purchaser.

REPLACEMENT PARTS AVAILABILITY

Parts must be available for 5 years or 7,500 hours of use for the piece of equipment bid. If replacement parts are not delivered within three (3) working days of an order being place d, the bidder will deliver an equivalent machine for the county to use at no cost to the county until such time as the parts are delivered to the county so it can affect repairs to its machine.

WARRANTY

Bidders shall submit a copy of the manufacturer's standard warranty.	Warranty shall include service
response time of maximum of 36 hours within notification by county.	

Yes_	No
Page#	
or	
Attachr	nent 🗹

BID ITEM: RIDE-ON INDUSTRIAL BOOM MOWER WITH UNIVERSAL ATTACHMENT PLATE

ALL ITEMS FACTORY INSTALLED UNLESS OTHERWISE INDICATED. THIS UNIT IS NOT INTENDED TO BE A MODIFIED AGRICULTURAL TRACTOR.

TO BE A MODIFIED AGRICULTURAL TRACTOR.	

The Engine shall meet the following requirements:

Minimum 130 HP Turbo Diesel Tier IV, with heavy duty radiator with high flow fan and canister style air cleaner with pre-cleaner. Electric start with engine pre-heat, and minimum 30-gallon fuel tank and full engine gauge package to include tachometer, water temperature, oil pressure, volt meter, fuel gauge and hour meter.

Yes ____ No ___ Page #____ of Attachment ____

POWER TRAIN:

ENGINE

Minimum power train requirements shall consist of permanent 4 Wheel Drive, four-wheel steer and three steering modes. Dana/Conner axles or equivalent.

Hydrostatic drive with two-speed heavy duty drive motor. Hydrostatic, variable displacement piston transmission pumps in closed loop system. Standard electric over hydraulic parking brake with standard service brake.

Joystick or pedal control transmission for speed and directional control, with 0-6 mph work mode and a travel mode of 0-20 MPH. 25 MPH capability is optional.

Yes ____ No ____ Page #____

BOOM: Equal to or Exceeds MowerMax

2 section steel construction. 22 Ft., 24 Ft., 26Ft., and 30Ft. Boom lengths includes counter weight with integrated steps & 175-degree rotation with HELAC actuator. Main Boom is to be 8"x6"x1/4" wall structural tubing conforming to ASTM A-500 Gr. B (58,000 psi minimum tensile).

Yes ____ No ____ Page #__****___

MOWER ATTACHMENTS: Equal to or Exceeds MowerMax

No Boom attachment is considered standard. All attachments shall be optional	Yes / No	
	Yes No Page # 2	
MUEEL C.		
WHEELS: Shall be equipped with, Four (4) Heavy Duty, Industrial flotation tires with either 22 Ply 550/45-22.5 flotation tires with Chevron Pattern or 460/70R24 with Multiuse		
tread	Yes No Page # \	
CAB, COMFORT, CONVENIENCE & SAFETY:	1 ago #	
Custom designed cab will be mounted in front of the engine and hydraulics for optim Cab must be certified for both ROPS – ISO 3471 and FOPS – ISO 3449.	um operator visibility.	
Low profile Grammer or equivalent full suspension seat with lumbar support and integrated operator-presence safety switch, ROPS enclosed cab with Red Dot A/C, heat and AM/FM Stereo with 7-inch Touch Screen with Blue Tooth,		
Minimum of Two (2) LED Safety Strobe lights and 2 mini strobe lights mounted below the head lights. 1- 35 inch LED Directional Control Bar. DOT reflector tape, clear view steering column with adjustable tilt steering, back up alarm.		
Seat belt with safety switch. 6 section Valve Bank with Electro-Hydraulic Joystick Confidence of Confidence of Seat with lumbar, tilt, arm rest and 2 safety switches. ½ inch thick Lesupports on Right side window.		
Y F	esNo Page # 2	
CONDITIONS:		
Boom Mower shall be equipped with all standard equipment specified by the manufactomply with EPA emission standards and all motor vehicle standards established by of Transportation regarding the manufacture of motor vehicles. This unit shall have year manufactured warranty.	the U.S. Department	
\ F	es No Page #	
The successful bidder shall be responsible for delivering the unit properly ser	viced, clean and in	

first class operating condition. Pre-delivery service at a minimum shall include the following:

Complete lubrication, check all fluid levels, adjustment of engine to proper operating condition, inflate tires to proper operating pressure, check proper operation of all accessories.



MowerMax Boom Standard Units include:

- Cummins 3.8L, 130HP Tier IV Turbo Diesel 2-Speed Hydrostatic Transmission
- 6 Section Valve Bank with Electro-Hydraulic Joystick Controls

- O Section Vaive Bain wint Electro-Hydraunic JoyStick Controls
 Red Dot AC/Heat Cab with AM/FM/DVD 6.2in Touchscreen with Blue Tooth & iPod Control
 Heavy Duty, Remote, Horizontally Mounted Radiator/Hyd. Oil Cooler/CAC with High Flow Fan
 Heavy-Duty, Industrial Flotation Tires with either 20 Ply Hockey Stick or 22 Ply Chevron Pattern
 Full time 4WD, 4 Wheel Steering with 3 Steering Modes, 45% Limit-slip Front Diff. Lock & 100% Operator Controlled Rear Diff. Loc
- Service Brake and Parking Brake
- Front Headlights with Turn Lights and Rear Brakelights with Turn Lights
 4- LED Flasher/Strobes and 1 36in LED Directional Control Bar
- 12v Air-ride, Grammer cloth seat with lumbar, tilt, arm rest & 2 safety switches
- 1/2 in Thick Lexan on Right Side Window
- Fire Extinguisher

Item	Product Description		ACCA Price
A	MowerMax Boom Standard unit with 3450lbs CW and 180Deg Rotray Actuator	\$	145,400.00
	Boom Arm Options:		
1	22ft or 24ft Long Arm without Head Attachment	\$	10,500.00
2	26ft Long Arm with 1 additional 1400lbs CW and without Head Attachment	\$	15,350.00
3	30ft Telescoping Long Arm, includes 2 additional 1400lbs CWs and without Attachment	\$	22,500.00
	Boom Arm Head Attachment Options:		
1	60in Rotary Deck with hydraulic controlled deck door	\$	11,125.00
2	62in Flail Head	\$	12,900.00
3	48in Saw Blade	\$	11,750.00
4	69in Triple Saw Blade	\$	15,900.00
5	90in Triple Saw Blade	\$	17,900.00
6	50in Mulching Head	\$	19,900.00
	Other Options:		
1	90 Degree Swivel/Rotating Deck (Rotary & Flail)	\$	2,650.00
2	180 Degree Swivel/Rotation	\$	2,950.00
3	Additional 1400lbs Counterweight (for 22ft, 24ft and 26ft Booms)	\$	3,000.00
4	Hydraulic Quick Disconnect (QD) system on boom arm and includes one attachment	\$	2,500.00
5	Additional Valve Bank Section	\$	875.00
6	Back Up Camera	\$	900.00
7	Back Up Alarm	\$	650.00
8	Reversing Radiator Fan	\$	975.00
9	Window Tinting	Ś	700.00
	Front Attachment Options:		, 00100
1	Front lift arms with universal attachment mount & Hydraulic QDs (N/A on 30ft)	\$	9,500.00
2	96in Front Rotary Mower	\$	13,900.00
3	84in Front Sweeper/broom with hydraulic angling	\$	8,150.00
5	48in Front pallet forks	\$	1,350.00
6	24in Front cold planer	\$	19,500.00
7	96in Snow Plow with hydraulic angling	\$	4,795.00

^{**} FOB Tampa, FL

ATMAX Equipment Co. LIMITED WARRANTY

ATMAX Equipment Co. (hereinafter "ATMAX") makes every effort to assure that its products meet high quality and durability standards. ATMAX warrants that its products shall be free from defects in parts, materials and workmanship (hereinafter "Defective Item(s)"), subject to the following conditions (hereinafter the "Warranty"):

- 1. It applies only to the original retail purchaser or original purchaser acting as a lessor (hereinafter the "Purchaser") and is not transferable;
- 2. To be eligible for the benefits of this Warranty, Purchaser must submit its warranty registration information in writing to ATMAX within ten (10) days of delivery of the product.
- 3. It is limited to Defective Items discovered within the earlier of the time periods listed below following the date of delivery to Purchaser of the product;

Engine: Cummins QSF3.8 130HP

2 years/2,000 hours

1 year/2,000 hours

2 years/2,000 hours

1 year/2,000 hours

3 years/10,000 hours

1 year/2,000 hours

1 year/2,000 hours

- 4. It is limited to the cost of the repair or the replacement by ATMAX or its authorized service representative of Defective Items. It does not include labor or transportation unless agreed upon by ATMAX in writing. It does, however, include reasonable shipping charges for Defective Items (as determined by ATMAX) to and from ATMAX or its authorized service representative which result from Defective Items;
- It is conditioned upon Purchaser's making its warranty claim regarding a possible Defective Item to ATMAX or its authorized service representative within ten (10) days of the discovery of the Defective Item;
- 6. It is conditioned upon the return of the Defective Item to ATMAX or its authorized service representative within ten (10) days of the purchaser's warranty claim;
- It does not apply to the product's parts and components which are manufactured by parties other that ATMAX, except for the extent that such other manufacturer provides a warranty that is transferable to the Purchaser and which warranty ATMAX hereby transfers to the Purchaser;

- 8. It does not apply to defects resulting from:
 - a. Neglect or improper and inadequate maintenance, repairs or replacements;
 - b. misuse, accident, theft, fire or the like;
 - c. use of improper, or inadequate use of, fuel, fluids or lubricants;
 - d. use of parts or components other than ones from ATMAX or ones authorized in writing by ATMAX;
 - e. modifications or alterations not authorized in writing by ATMAX;
 - f. continued use after a problem has been identified that requires, or one should reasonably expect to require, immediate attention.
- 9. The product must be operated and maintained only by trained and qualified personnel and in accordance with the instructions and recommendations furnished by ATMAX;
- 10. It does not apply if the product's serial number has been altered, defaced or removed, or if Purchaser is in default in any payment due ATMAX or any of its dealers or other agents.
- 11. ATMAX shall not be responsible for any injury, loss, or damage, either direct, indirect, incidental or consequential resulting from any Defective Item:
- 12. No warranty, expressed or implied, as to the merchantability, fitness for a particular purpose, quality or other matter is included herein;

THIS IS THE SOLE WARRANTY PROVIDED BY ATMAX AND NO PERSON IS AUTHORIZED TO MAKE ON BEHALF OF ATMAX ANY WARRANTIES OR REPRESENTATIONS OTHER THAN THOSE EXPRESSED HEREIN.



2020 Tier IV – Boom Mower Specifications

1.0	INTENT		
1.01	The intent of this specification is to provide for the purchase of a self-contained, purpose-built boom mower with a primary focus on operator safety.		
2.0	POWERTRAIN AND ENGINE		
2.01	Minimum Horsepower of 130HP Turbo Diesel Engine. Preference given to Tier IV Cummins Diesel		
2.02	The engine coolant and hydraulic oil will be cooled by a remote, horizontally mounted, heavy duty side by side radiator/CAC/oil cooler		
2.03	The radiator will have a custom, 21" diameter fan driven by a heavy-duty gear motor with case drain and pressure relief/anti-cavitation valve with an optional operator controlled reversing valve to cleanout radiator		
2.04	Two(2) heavy duty Dana/Comer axles with full time 4 wheel drive and 4 wheel steering with 3 steering modes: Four Wheel, Front, and Crab.		
2.05	Engine Battery will be located conveniently in the front of the machine for easy access with a locking door.		
2.06	Front axle will have automatic, 45% limited slip differential and rear axle will have 100% operator controlled locking differential		
2.07	Unit will have a 2-speed transmission with 0-6 MPH work mode, 0-20 MPH travel mode. 25mph optional		
2.08	Drive Axle Pump is to be heavy duty hydrostatic, closed loop piston pump with charge pump filter.		
2.09	Braking will be accomplished via hydrostatic braking as well as a secondary foot-controlled service brake. Parking brake will be electric over hydraulic with an integrated seat belt safety switch.		
2.10	Standard tires will be 22 ply, 550/45-22.5 floatation tires with Chevron tread or 460/70R24 with Multiuse tread		
3.0	BOOM FEATURES & MOWING		
3.01	Main boom is to be 8" X 6" X 1/4" wall structural tubing conforming to ASTM A-500 Gr. B (58,000 PSI minimum tensile).		
3.02	Main boom will be lifted by a 6 inch bore cylinder with a 2.5 inch diameter rod.		
3.03	Outer boom is to be 6 inch X 4 inch X ¼ inch wall structural tubing conforming to ASTM A-500 Gr. B (58,000 PSI minimum tensile).		
3.04	Outer Boom will be lifted by a 5 inch bore cylinder with a 2.0 inch diameter rod.		
3.05	Main pivot pins shall be constructed of 1.5 inch AISI 4140 steel.		
3.06	Each pin is to be supported by a pair of 2 inch wide hardened steel, greaseable Connex® bushings.		
3.07	Standard boom functions will include horizontal swing, vertical lift, dipper reach, mower head tilt and mower head door open/close.		
3.08	All boom functions as well as axle stabilizer system must be controlled by the operator's right hand and the joystick.		
3.09	Boom must swing hydraulically a minimum of 175 degrees with a rotary actuator with dual cross port reliefs and an accumulator for system protection.		
3.10	Boom mower deck tilt will be lifted by a 3 inch bore cylinder with a 1.75 inch diameter rod. The cylinder will also have an integrated counter-balance holding valve.		
3.11	The mower blades will be powered by a closed-loop, hydrostatic piston pump with charge pump filter and a bent axis piston motor with maximum pressures capable of 4900psi. This system should have approximately 87% hydraulic efficiency.		
3.12	The standard 60in rotary deck frame will be made of a minimum of 9ga. steel plate and have a 1in thick blade bar with 5/8in dual double-sided sling blades.		
3.13	The rotary deck will also have an optional 90 degree swivel option.		
3.14	The boom arm travel cradle must come with a 2in ratchet strap to secure boom in the cradle to prevent accidental movement when in travel mode.		
3.15	The main boom Helac mount weldment will be made of $\frac{3}{4}$ inch and 5/8 inch A-36 steel and attached by a minimum of ten (10) grade 8 flange bolts with lock washers.		

	Primary counterweight will be custom, cast iron with a minimum of 3,400 pounds with integrated operator steps for easy access and be attached to the main frame with a minimum of nine (9), 1 inch grade 8 bolts.
3.17	Additional cast iron counterweights (Maximum of 2) are available of a minimum of 1,400 pounds each and be attached to the main frame with a minimum of four (4), 1 inch grade 8 bolts.
4.0	CAB AND OTHER FEATURES
4.01	Custom designed cab will be mounted in front of the engine and hydraulics for optimum operator visibility.
4.02	Cab will be certified for both ROPS - ISO 3471 and FOPS - ISO3449.
4.03	The right side of the cab, or the boom arm side, will feature a minimum of ½ inch Lexan with no vertical supports to hinder the visibility of the operator while operating the boom.
4.04	The steering wheel and column will have a full column tilt and telescoping features and must include a horn and steering knob.
4.05	The operator's seat will be a Grammer, cloth seat with 12-volt adjustable air ride, two armrests, tilt, lumbar support, an operator presence switch limiting joystick and transmission functions and a seatbelt with switch limiting the disengagement of the parking brake and mower PTO.
4.06	Must include Red Dot Air Conditioning, heat and front windshield wiper with washer as standard equipment.
4.07	Unit must include a minimum of three rear view mirrors: one mounted inside the cab, two additional mirrors mounted on the left and right outside the cab.
4.08	The engine gauge display will be at least a 7in diagonal, color monitor mounted on a double ball RAM mount for easy operator adjustment.
4.09	The A/C condenser must be mounted on the upper front of the cab for minimum clogging from dust and debris.
4.10	Unit must have (2) Class 1 LED Safety Strobe Lights and a 35in LED Directional Light Bar as well as 2 mini strobes mounted below front headlights. (Front Main Frame, aft Cab mount and Cab A/C Housing for light bar)
4.11	Unit must be equipment with a backup alarm, Slow Moving Vehicle diamond, head lights with LED daytime running lights, high & low beam, front and rear turn signals, brake and reverse lights.
4.12	Cab must come equipment with an audible and visible alarm for low hydraulic oil to alert operator of a hydraulic oil leak as well as high coolant temperature and low oil pressure.
4.13	Cab must come equipment with an AM/FM stereo with Bluetooth. And have as options a backup camera.
4.14	Unit will come equipped with two locking tools boxes mounted on the side of the machine.
5.0	OPTIONS
5.01	Back up alarm & camera
5.02	Radiator reversing fan
5.03	Quick Disconnect System for boom attachments
5.04	50in mulching head for boom
	60in flail head for boom
5.06	48in saw blade for boom
5.07	Front Lift Arms with universal skid steer plate and high flow hydraulics
5.08	84in angle broom for front lift arms
5.09	96in rotary deck for front lift arms





Company ID Number: 503975

THE E-VERIFY PROGRAM FOR EMPLOYMENT VERIFICATION MEMORANDUM OF UNDERSTANDING

ARTICLE I

PURPOSE AND AUTHORITY

This Memorandum of Understanding (MOU) sets forth the points of agreement between the Department of Homeland Security (DHS) and Equipment & Parts Specialty Co., Inc. (Employer) regarding the Employer's participation in the Employment Eligibility Verification Program (E-Verify). This MOU explains certain features of the E-Verify program and enumerates specific responsibilities of DHS, the Social Security Administration (SSA), and the Employer. E-Verify is a program that electronically confirms an employee's eligibility to work in the United States after completion of the Employment Eligibility Verification Form (Form 1-9). For covered government contractors, E-Verify is used to verify the employment eligibility of all newly hired employees and all existing employees assigned to Federal contracts or to verify the entire workforce if the contractor so chooses.

Authority for the E-Verify program is found in Title IV, Subtitle A, of the Illegal Immigration Reform and Immigrant Responsibility Act of 1996 (IIRIRA), Pub. L. 104-208, 110 Stat. 3009, as amended (8 U.S.C. § 1324a note). Authority for use of the E-Verify program by Federal contractors and subcontractors covered by the terms of Subpart 22.18, "Employment Eligibility Verification", of the Federal Acquisition Regulation (FAR) (hereinafter referred to in this MOU as a "Federal contractor with the FAR E-Verify clause") to verify the employment eligibility of certain employees working on Federal contracts is also found in Subpart 22.18 and in Executive Order 12989, as amended.

ARTICLE II

FUNCTIONS TO BE PERFORMED

A. RESPONSIBILITIES OF SSA

- 1. SSA agrees to provide the Employer with available information that allows the Employer to confirm the accuracy of Social Security Numbers provided by all employees verified under this MOU and the employment authorization of U.S. citizens.
- 2. SSA agrees to provide to the Employer appropriate assistance with operational problems that may arise during the Employer's participation in the E-Verify program. SSA agrees to provide the Employer with names, titles, addresses, and telephone numbers of SSA representatives to be contacted during the E-Verify process.
- 3. SSA agrees to safeguard the information provided by the Employer through the E-Verify program procedures, and to limit access to such information, as is appropriate by law, to individuals responsible for the verification of Social Security Numbers and for evaluation of the E-Verify program or such other persons or entities who may be authorized by SSA as governed





Company ID Number: 503975

To be accepted as a participant in E-Verify, you should only sign the Employer's Section of the signature page. If you have any questions, contact E-Verify at 888-464-4218.

Employer Equipment & Part	ts Specialty Co., In	е.	
David Coblentz			aport came in another came in an other c
Name (Please Type or Print)		Title	
		2011010010	-
Electronically Signed Signature		02/13/2012 Date	Commence of the commence of th
Cignature			1
Department of Homeland Secu	rity – Verification Di	vision	
USCIS Verification Division		Program version 1991 1991 1991 1991 1991 1991 1991 19	
Name (Please Type or Print)		Title	
Electronically Signed		02/13/2012	
Signature		Date	
And the second s			
Infor	mation Required t	or the E-Verify Program	
Information relating to yo	ur Company.		
illiorillation relating to yo	di Company.		Name of the Indian Control of the Indian Con
Carrage Maria	e:Equipment & Parts \$	Specially Co. Inc.	
Company Name	e. Equipment & Farts C	specially co., mo.	er den trees for eight en fan de
	3523 Mobile Highwa		
Company Facility Addres	S. 3323 WODITE I TIGITWA	A CONTRACTOR OF THE CONTRACTOR	
	Montgomery, AL 36	108	
	Note that the second se		
Company Alternate			
Address:	Post Office Box 250	44/	
Montgomery, AL 36125			
*			
County or Parish:	MONTGOMERY		NUMBER OF THE STREET OF A PROPERTY OF
Employer Identification			
Number:	630926850		and the state of t





View / Edit



Welcome David Coblentz User ID DCOB0375 Last Login 02.23 PM - 02/15/2013

Click any 🚱 for help

Home

My Cases

New Case

View Cases

Search Cases My Profile

Edit Profile

Change Password

Change Security Questions

My Company

Edit Company Profile

Add New User

View Existing Users

Close Company Account

My Reports View Reports

My Resources

View Essential Resources

Take Tulorial

View User Manual

Contact Us

Company Information

Company ID Number:

Doing Business As (DBA)

Name:

DUNS Number:

Physical Location:

Address 1:

Address 2:

City: State:

Zip Code:

County:

Company Name:

Coblentz Equipment & Parts Co., Inc.

503975

153590609

10400 Highway 80 East

Montgomery

36117

MONTGOMERY

Additional Information:

Employer Identification Number: 630926850 Total Number of Employees: 10 to 19

Parent Organization:

Administrator:

Organization Designation:

Employer Category:

State Government

Mailing Address:

Address 1: Post Office Box 242608

Address 2:

City: Montgomery

State: AL

Zip Code: 36124

NAICS Code:

111 - CROP PRODUCTION

View / Edit

Total Hiring Sites:

View / Edit

Total Points of Contact:

3

View / Edit

U.S. Department of Homeland Security - www dhs gov U.S. Citizenship and Immigration Services - www uscis gov

Accessibility Download Viewers

INVITATION TO BID HEAVY EQUIPMENT

NOTICE OF BID OPENING

NOTICE IS HEREBY GIVEN that the Association of County Commissions of Alabama, which administers the Alabama County Joint Bid Program on behalf of Alabama's county governing bodies, shall receive and open bids for the purchase of zero (0) or more items of heavy road equipment at its office located at 2 North Jackson Street, Montgomery, Alabama, at 10:00 a.m. on Friday, September 4, 2020. Bid specifications are available at http://www.alabamacounties.org/heavy-equipment/ for each of the following items:

Light Duty Backhoe Medium Duty Backhoe Heavy Duty Backhoe Option A

Heavy Duty Backhoe Option C

85 PTO Tractor Option A

85 PTO Tractor Option B 95 PTO Tractor Option A

95 PTO Tractor Option B

Track Mount Excavator Option A-1

Track Mount Excavator Option A-2

Track Mount Excavator Option A-3

Track Mount Excavator Option B-1

Track Mount Excavator Option B-2

Track Mount Excavator Option B-3

Track Mount Excavator Option C-1

Track Mount Excavator Option C-2

19 Ton Wheeled Excavator

21 Ton Wheeled Excavator

Compact Track Mount Excavator Option D-1

Compact Track Mount Excavator Option D-2

Light Duty Motorgrader – Option A Light Duty Motorgrader – Option B

Heavy Duty Motorgrader – Option A

Heavy Duty Motorgrader - Option B

Medium Duty Motorgrader – Option A

Medium Duty Motorgrader - Option B

Medium Duty Motorgrader - AWD

Light Duty Motorgrader - Option B

100 HP Heavy Duty Hydrostatic Bulldozer - Option B

100 HP Heavy Duty Hydrostatic Bulldozer - Option C

100 HP Heavy Duty Hydrostatic Bulldozer - Option D

125 HP Heavy Duty Hydrostatic Bulldozer - Option A

125 HP Heavy Duty Hydrostatic Bulldozer - Option B

Mulching Dozer

3 CY Wheel Loader Option A

3 CY Wheel Loader Option B

3 CY Wheel Loader Option C

3.65 CY Wheel Loader Option A

3.65 CY Wheel Loader Option B

Heavy Duty Dump Chassis - Option B

Heavy Duty Dump Chassis - Option C

Heavy Duty Dump Chassis - Option E

Lowboy Tractor Option – B

Lowboy Tractor Option - C

Lowboy Tractor Option - D

Skid Steer Attachments

Ride-on Industrial Boom Mower

Telescopic Boom Cutter 75 FT. Reach

Telescopic Boom Cutter 55 FT. Reach

Asphalt Distributor Truck

Chip Spreader

Rubber Tire Roller

One-man Pothole Patcher Option A

2WD Highway Speed Truck Excavator

4WD Highway Speed Truck Excavator

Time is of the essence in submitting bids and only bids received in the Association office by 10:00 a.m. Central Time on Friday, September 4, 2020 will be opened and considered. Bidders and any other interested individuals are invited to attend the bid opening.

THE INVITATION PACKAGE

The invitation package for each item to be bid includes: this invitation to bid, the written bid specifications for the particular item of heavy road equipment, and a Bid Submittal Form to be used in submitting a bid for that particular item. Bidders should verify that they have received all pages of the invitation package. If there are any omissions, the bidder should contact Kenya Howard in the Association office by mail, fax, or e-mail (jointbid@alabamacounties.org) to request missing pages. It is the responsibility of the bidder to make this request in sufficient time to prepare and submit the bid in time for the bid opening. Bidders should carefully read and comply with all parts of the invitation package, including all attachments and/or any addendum.

PREPARING AND SUBMITTING BIDS

All bids must be typed or hand written in ink on the attached Bid Submittal Form. The completed Bid Submittal Form shall be placed in front of and separated from all other documents included in the bid packet, such that it will be the first document viewed upon opening the bid packet.

Bids submitted in pencil and bids not submitted on the Bid Submittal Form will **not** be considered. All bids shall include a current catalog or model specification document for the equipment model number being offered for consideration. Bids submitted without such documentation will **not** be considered. Only information contained on the attached Bid Submittal Form and in the model specification document will be considered in evaluating bids.

Each separate requirement in the bid specification includes a block for indicating whether or not the item bid meets the specification. The bidder shall indicate compliance with each requirement by checking "Yes" or "No" in the block to the right of each bid specification. In addition, the bidder shall indicate the page number in the supplied manufacturer's equipment literature on which compliance with the specification can be verified. Failure to complete this portion of the bid form may result in the subject bid not being considered.

Each bid for one of the heavy equipment items included in the bid package must be submitted on the Bid Submittal Form for that item and forwarded in a separate envelope with the bid item and item number clearly identified on the outside of the envelope. Envelopes containing a "no bid" shall also include the words "NO BID" on the outside of the envelope. Facsimiles and e-mails will not be accepted. Bids submitted by "Express/Overnight" services must be in a separate inner envelope or package sealed and identified as stated above. All bids must be received in the Association office prior to the bid opening. Bids received after the deadline will be returned unopened.

The County Joint Bid Program reserves the right to require a performance bond from successful bidders as permitted under Alabama law. However, no bid bond is required for this bid offering.

All bids should be mailed or hand-delivered to:

Association of County Commissions of Alabama Attention: JOINT BID PROGRAM Attention: JOINT BID PROGRAM 2 North Jackson Street Montgomery, Alabama 36104

OR P.O. Box 5040 Montgomery, Alabama 36103

BID SPECIFICATIONS

Please note that each piece of heavy equipment available for bid may include several different sizes and categories of machines. You should read each set of specifications very carefully as the differences vary depending upon the piece and size of equipment.

The award will be based on the total cost of the **Standard Machine** bid by the lowest responsible bidder. Each Bid shall include a **Manufacturer's Suggested Retail Price Sheet (MSRP)** for each machine bid. The percent difference between the Manufacturer's Suggested Retail Price (MSRP) for the standard machine as specified by these bid specifications and the actual price bid by the vendor will be calculated and that percentage discount shall be applied to any options an individual county may choose to add to the machine.

Once the bids have been awarded, any county participant purchasing under this program may, at its discretion, add any of the vendor's available options at the same discount off the Manufacturer's Suggested Retail Price Sheet as was applied to the Standard Machine Price Bid.

Any use of specific names and/or model numbers in the attached specifications is not intended to restrict the bidder or any seller or manufacturer, but is included solely for the purpose of indicating the type, size, and quality of materials, product services, or equipment considered best adapted to the use of the counties participating in the joint bid program.

ACQUISITION AND FINANCING OPTIONS

The awarded Vendor will provide the equipment, including any options required by the purchaser, at the awarded price as contracted through the Joint Bid Program. The purchaser may secure its own financing to acquire the equipment or execute any financial options available under Alabama law with the awarded Vendor in order to acquire the equipment.

BIDDER QUALIFICATIONS

All bidders and all program participants must be in compliance with any applicable federal, state, county and municipal laws, regulations, resolutions and ordinances, including but not limited to, licensing, permitting, and taxation requirements. All bidders should be prepared to submit evidence or documentation as proof that they are properly licensed and permitted under any applicable laws upon request. Such evidence or documentation may be submitted with the bid. Additionally, all bidders shall provide proof that they are in compliance with the e-verify requirements of Alabama's Immigration Law (Ala. Code § 31-13-1 et seq., as amended by Act No. 2012-491).

BID AWARD

The Houston County Commission will serve as the awarding authority for all bids and will award all contracts at a regular meeting of the Houston County Commission. Any and all bids submitted in compliance with this invitation to bid shall be considered, and award will be made to the lowest responsible bidder meeting bid specifications as determined by the awarding authority in compliance with Alabama law. All bids will be reviewed and evaluated by a committee created for that purpose, which committee will make comments and recommendations to the awarding authority regarding the award. All factors contained in each invitation package will be evaluated in determining the successful bidder, and any omissions of the stated requirements may be cause for rejection of the bid submitted. The awarding authority reserves the

right to reject any and all bids, to waive any informality in bids, and to accept in whole or in part such bid or bids solely at its discretion.

The contract period will be one year with an option to renew for a second and third year under identical price, terms, and conditions upon the mutual consent of the vendor and the awarding authority. Any renewal contract shall be approved in writing by the vendor and the awarding authority no later than 90 days prior to the expiration of the existing contract.

CONTACT REGARDING BIDS AND INVITATION

Contact initiated by a potential bidder with any county official, county employee, or member of the Association staff shall only be as specifically set out in this Invitation to Bid. Any questions related to the bid or the County Joint Bid Program shall be directed to Association staff in writing under the procedures set out in this Invitation to Bid. Additionally, a bidder may contact the Association in writing to request an appointment to review bid specifications following the bid opening. However, there shall be no communication with any county official or county employee regarding this bid between the date of this invitation and the date of bid award. Any contact other than as set out here shall be deemed as an attempt to unduly influence the bid award, and shall be grounds for rejection of the bid submitted by the bidder initiating such other contact.

Any questions or problems related to downloading or obtaining copies of this Invitation to Bid should be directed to Kenya Howard at jointbid@alabamacounties.org or 334-263-7594.

Any other questions or requests for additional information regarding this invitation or the bid specifications shall be submitted **in writing** no later than five (5) days prior to bid opening to:

ATTN: Chase Cobb
Association of County Commissions of Alabama
P.O. Box 5040
Montgomery, Alabama 36103
E-mail: ccobb@alabamacounties.or



(334) 215-8600 • 1-800-239-3353 • Fax: (334) 215-8532 10400 Highway 80 E. • Montgomery, Alabama 36117 • matthew@coblentzep.com PO. Box 242608 • Montgomery, Alabama 36124 • www.coblentzequipment.com



ENGINEERED FOR PERFORMANCE

The revolutionary MowerMax Boom Mower is designed and purpose built from the ground up to have the best **Stability, Visibility, Maneuverability and Versatility** of any boom mower on the market. The MowerMax is a heavy-duty boom mower that is also very safe, easy to operate and maintain.





















OPTIMUM STABILITY

The MowerMax is designed to have a low center of gravity. The counterweights are mounted directly opposite the boom for maximum benefit and it's easy to add additional counterweights. These features combined with the rear axle stabilizer system, make the MowerMax an extraordinarily stable machine.









INCOMPARABLE VISIBILITY

The MowerMax cab forward design greatly enhances the operator's visibility making for a much more productive and safer cutting experience. Plus the right









EXTREMELY SIMPLE & COMFORTABLE

The MowerMax is extremely simple to operate and very comfortable for the operator! The MowerMax is easy to get into and out of with non slip coated steps integrated into the main counter-weight. The cab has a plush, Grammer air-ride suspension seat with tilt and lumbar, a tilt & telescoping steering wheel with steeing knob, 6.2in color AM/FM/CD stereo with Bluetooth & optional Backup Camera, and a 7in Control Display.





OUTSTANDING MANEUVERABILITY

The MowerMax has hydrostatic, 2 speed transmission which is operated by two foot pedals and comes with permanent 4 wheel drive with 45% limited slip front axle and 100% operator controlled rear differential lock. The MowerMax Boom also has 4 wheel steering with 3 different steering modes:

1) 4 Wheel Steer 2) Front Wheel Steer or 3) Crab Steer. These three steering modes allows the MowerMax to be extremely maneuverable and productive. Lastly all of MowerMax booms come with 180 degree rotation with a helical actuator for maximum operating flexibility.











SERIOUS VERSATILITY

The MowerMax Boom is extremely versatile with 4 different boom head attachments as well as the optional front lift arms with universal quick attach mounts that allows you to use over 30 common skid steer attachments.















EXCEPTIONALLY SAFE

ATMAX Equipment knows that boom mowing often happens on busy roads under rough conditions, so safety of the operator and the machine are of utmost importance! 1/2in Lexan Glass on boom side. ROPS & FOPS - Most tractors and other purpose built boom mowers only have ROPS even though all trim trees with them! Bright Yellow Powder Coated Paint with 2 front LED daytime running lights, 2 reflective SMV diamonds, 2 - SAE Class 1 strobes, 1 - 35in LED directional control bar, 12 amber/white mini LED flashers, and over 30ft of reflective decals and DOT tape.













MOWER SPECIFICATIONS MOWERMAX BOOM

Power Unit Specs

Ground Speed

Engine Cummins Tier 4F 3.8QSF 130 HP Turbo Diesel

Horizontally-mounted Radiator/CAC/Oil Cooler with High Flow Fan & Reversing Cleanout System Cooling System (Engine & Hydraulic)

Transmission Two Speed Closed Loop Hydrostatic with Double Foot Pedal Controls

Permanent 4-Wheel Drive with 4-Wheel Steering and 3 Steering Modes **Drive Train & Steering**

Differential Lock 45% Limited Slip on Front Axle and 100% Operator-controlled Rear Locking Rear Axle

Parking Brake Standard SAHR Electric over Hydraulic Standard Foot Pedal Controlled Service Brake

460/70-R24 Radial with Multiuse Tread or 550/45-22.5 22 Ply Flotation with Lug Tread **Tires**

> 0-8 MPH Work Mode 0-25 MPH Travel Mode

Boom Arm Specifications

Boom Controls Multifunction, Electric Over Hydraulic Joystick

Approximately 22 ft, 24 ft, 26 ft & Telescoping 27 ft to 30 ft **Boom Lengths** 180 Degrees with Helical Actuator with Cross Port Relief **Boom Rotation**

Closed Loop Hydrostatic Pumpwith 30GPM @ 5000 psi **High Flow Hydraulics to Boom Attachments**

Available Attachments:

50 in & 60 in with Hydraulic Door & Optional 90 Degree Swivel **Rotary Decks**

50in Fixed Tooth Mulching mfg for MowerMax by Fecon with optional 180 Degree Swivel **Mulching Head** Saw Heads 48 in Single Blade Direct Drive, 69 in Triple Blade Belt Drive & 90 in Quad Blade Belt Drive

50 in Brush Flail & 60 in Grass Flail with optional 180 Degree Swivel Flail Heads

Front Lift Arm Specs (Optional)

High Flow Hydraulics to Attachments

Most Universal Skid Steer Mount Attachments **Attachment Types**

2500 lbs Lift Capacity

Closed Loop Hydrostatic Pump with 30GPM @ 5000 psi

General Specs

Width with Boom in Stow 100 in Length with Boom in Stow (no boom attachments) 236 in

Height 112 in Weight (with 24ft boom & no attachments)

19,500 lbs approximately **Diesel Fuel Tank Capacity** 38 gallons **DEF Tank Capacity** 5 gallons

Cab & Safety Features

Grammer Air Ride Suspension Seat with Back Rest, Lumbar, Tilt with Operator Presence Switch & Seatbelt with Switch

Tilt Steering Column with Telescoping Steering Wheel with Knob

Easy to View, Adjustable 7in Color Display with All Gauges and Warning Signals

6.2in Color AM/FM/CD Stereo with Bluetooth and Optional Backup Camera

Front Hedlights with LED Daytime Running Lights and Rear LED Brake Turn and Backup Lights

12 Amber/White LED Mini Flashers on all 4 Sides

2 - SAE Class 1 LED Stobes and 1 - LED Directional Control Bar on Rear on Cab

Backup Alarm

2 Reflective SMV Diamonds and over 28ft of Reflective DOT tape

Certified ROPS - ISO 3471 & FOPS - ISO 3449

STEERING MODES













WWW.MOWERMAX.COM







Call 813-781-0100 or 423-595-4897 to schedule a demonstration or go to www.MowerMax.com