

INVITATION TO BID HEAVY EQUIPMENT

NOTICE OF BID OPENING

NOTICE IS HEREBY GIVEN that the Association of County Commissions of Alabama, which administers the Alabama County Joint Bid Program on behalf of Alabama's county governing bodies, shall receive and open bids for the purchase of zero (0) or more items of heavy road equipment at its office located at 2 North Jackson Street, Montgomery, Alabama, at **10:00 a.m. on Tuesday, November 18, 2025**. Bid specifications are available at <http://www.alabamacounties.org/heavy-equipment/> for each of the following items:

Track Mount Excavators
Compact Excavators
Mini Track Excavators
Wheeled Excavators
Highway Speed Truck Excavators
Motor Graders
Wheel Loaders
Heavy Duty Dump Chassis
Lowboy Tractors
Lowboy Trailers
Half Round End Dump
Skid Steer Loader and Attachments
Ride-on Industrial Boom Mowers
Rubber Tire Roller
Vibratory Roller

One-man Pothole Patchers
Trailer Mount Mastic Patcher/Crack Sealer
Trailer Mounted Patcher – Diesel
Trailer Mounted Patcher – Air Compressor/Tools
Chip Spreader
Asphalt Distributor
Asphalt Milling Attachments
Asphalt Storage Tanks
Backhoes
Bulldozers
Dump Bodies
Road Wideners
Ride On Industrial Boom Mowers

Time is of the essence in submitting bids and only bids received in the Association office by 10:00 a.m. Central Time on Tuesday, November 18, 2025 will be opened and considered. Bidders and any other interested individuals are invited to attend the bid opening.

NOTICE OF BID OPENING PROCEDURES

All bids for Heavy Equipment will be opened and the name(s) of the bidders read aloud on the morning of the bid opening on Tuesday, November 18, 2025 at 10:00 a.m. at 2 North Jackson Street, Montgomery, AL. The specifics of each bid submitted will be compiled by the Association staff thereafter and will be available, upon written or emailed request, one week after the bid opening. Requests should be emailed to jointbid@alabamacounties.org.

THE INVITATION PACKAGE

The invitation package for each item to be bid includes: this invitation to bid, the written bid specifications for the particular item of heavy road equipment, and a Bid Submittal Form to be used in submitting a bid for that particular item. Bidders should verify that they have received all pages of the invitation package. If there are any omissions, the bidder should contact Kenya Howard in the Association office by mail, fax, or e-mail (jointbid@alabamacounties.org) to request missing pages. It is the responsibility of the bidder to make this request in sufficient time to prepare and submit the bid in time for the bid opening. Bidders should carefully read and comply with all parts of the invitation package, including all attachments and/or any addendum.

PREPARING AND SUBMITTING BIDS

All bids must be typed or handwritten in ink on the attached Bid Submittal Form. **The completed Bid Submittal Form shall be placed in front of and separated from all other documents included in the bid packet, such that it will be the first document viewed upon opening the bid packet.**

Bids submitted in pencil and bids not submitted on the Bid Submittal Form **will not** be considered. All bids shall include a current catalog or model specification document for the equipment model number being offered for consideration. Bids submitted without such documentation **will not** be considered. Only information contained on the attached Bid Submittal Form and in the model specification document will be considered in evaluating bids.

Each separate requirement in the bid specification includes a block for indicating whether or not the item bid meets the specification. The bidder shall indicate compliance with each requirement by checking "Yes" or "No" in the block to the right of each bid specification. In addition, the bidder shall indicate the page number in the supplied manufacturer's equipment literature on which compliance with the specification can be verified. Failure to complete this portion of the bid form may result in the subject bid not being considered.

Each bid for one of the heavy equipment items included in the bid package must be submitted on the Bid Submittal Form for that item and forwarded in a separate envelope with the bid item and item number clearly identified on the outside of the envelope. Envelopes containing a "no bid" shall also include the words "NO BID" on the outside of the envelope. Facsimiles and e-mails will not be accepted. Bids submitted by "Express/Overnight" services must be in a separate inner envelope or package sealed and identified as stated above. All bids must be received in the Association office prior to the bid opening. Bids received after the deadline will be returned unopened.

The County Joint Bid Program reserves the right to require a performance bond from successful bidders as permitted under Alabama law. However, **no bid bond is required for this bid offering.**

All bids should be mailed or hand-delivered to:

**ATTN: Alabama County Joint Bid Program
Association of County Commissions of Alabama or ACCA
2 North Jackson Street, FL 7, Montgomery, Alabama 36104 (Physical Address)
P.O. Box 5040, Montgomery, Alabama 36103 (Mailing Address)**

BID SPECIFICATIONS

Please note that each piece of heavy equipment available for bid may include several different sizes and categories of machines. You should read each set of specifications very carefully as the differences vary depending upon the piece and size of equipment.

The award will be based on the total cost of the **Standard Machine** bid by the lowest responsible bidder. Each Bid shall include a **Manufacturer's Suggested Retail Price Sheet (MSRP)** for each machine bid. The percent difference between the Manufacturer's Suggested Retail Price (MSRP) for the standard machine as specified by these bid specifications and the actual price bid by the vendor will be calculated and that percentage discount shall be applied to any options an individual county may choose to add to the machine.

Both parties agree that the Vendor SHALL extend to ALL counties purchasing this equipment any factory discounts, incentives or rebates that become available during the Contract Period; provided that there are no alterations from the bid specifications for this item required in order to receive the discount, incentive, or rebate. FURTHER, BOTH PARTIES AGREE THAT THE VENDOR SHALL EXTEND TO ALL COUNTIES PURCHASING THIS EQUIPMENT THE SAME PURCHASE PRICE AND DISCOUNTS AS THEY ARE AWARDED ON ANY OTHER NATIONAL PURCHASING COOPERATIVE APPROVED BY THE DEPARTMENT OF EXAMINERS OF PUBLIC ACCOUNTS FOR USE BY ALABAMA COUNTIES.

Once the bids have been awarded, any county participant purchasing under this program may, at its discretion, add any of the vendor's available options at the same discount off the Manufacturer's Suggested Retail Price Sheet as was applied to the Standard Machine Price Bid.

Any use of specific names and/or model numbers in the attached specifications is not intended to restrict the bidder or any seller or manufacturer but is included solely for the purpose of indicating the type, size, and quality of materials, product services, or equipment considered best adapted to the use of the counties participating in the joint bid program.

ACQUISITION AND FINANCING OPTIONS

The awarded Vendor will provide the equipment, including any options required by the purchaser, at the awarded price as contracted through the Joint Bid Program. The purchaser may secure its own financing to acquire the equipment or execute any financial options available under Alabama law with the awarded Vendor in order to acquire the equipment.

BIDDER QUALIFICATIONS

All bidders and all program participants must be in compliance with any applicable federal, state, county and municipal laws, regulations, resolutions and ordinances, including but not limited to, licensing, permitting, and taxation requirements. All bidders should be prepared to submit evidence or documentation as proof that they are properly licensed and permitted under any applicable laws upon request. Such evidence or documentation may be submitted with the bid. **Additionally, all bidders shall provide proof that they are in compliance with the E-Verify requirements of Alabama's Immigration Law (Ala. Code § 31-13-1 et seq.). All bidders shall also affirm that they are in compliance with, and will comply with, Alabama's anti-boycott law (Ala. Code § 41-16-5) and anti-economic boycott law (Ala. Code § 41-16-160 et seq.).**

BID AWARD

The Houston County Commission will serve as the awarding authority for all bids and will award all contracts at a regular meeting of the Houston County Commission. Any and all bids submitted in compliance with this invitation to bid shall be considered, and award will be made to the lowest responsible bidder meeting bid specifications as determined by the awarding authority in compliance with Alabama law. All bids will be reviewed and evaluated by a committee created for that purpose, which committee will make comments and recommendations to the awarding authority regarding the award. All factors contained in each invitation package will be evaluated in determining the successful bidder, and any omissions of the stated requirements may be cause for rejection of the bid submitted. The awarding authority reserves the right to reject any and all bids, to waive any informality in bids, and to accept in whole or in part such bid or bids solely at its discretion.

The contract period will be Six (6) months with an option to renew each Six (6) months not to exceed a period of Three (3) years under identical price, terms, and conditions upon the mutual consent of the vendor and the awarding authority. Any renewal contract shall be approved in writing by the vendor and the awarding authority no later than **60 days** prior to the expiration of the existing contract.

CONTACT REGARDING BIDS AND INVITATION

Contact initiated by a potential bidder with any county official, county employee, or member of the Association staff shall only be as specifically set out in this Invitation to Bid. Any questions related to the bid or the County Joint Bid Program shall be directed to Association staff in writing under the procedures set out in this Invitation to Bid. Additionally, a bidder may contact the Association in writing to request an appointment to review bid specifications following the bid opening. **However, there shall be no communication with any county official or county employee regarding this bid between the date of this invitation and the date of bid award.** Any contact other than as set out here shall be deemed as an attempt to unduly influence the bid award, and shall be grounds for rejection of the bid submitted by the bidder initiating such other contact.

Any questions or problems related to downloading or obtaining copies of this Invitation to Bid should be directed to Kenya Howard at jointbid@alabamacounties.org or 334-263-7594.

Any other questions or requests for additional information regarding this invitation or the bid specifications shall be submitted **in writing** no later than five (5) days prior to bid opening to:

**ATTN: Patrick McDougald
Association of County Commissions of Alabama
P.O. Box 5040
Montgomery, Alabama 36104**

OR

**Patrick McDougald
Email: pattymackdaddy@gmail.com**

BID SUBMITTAL FORM
Alabama County Joint Bid Program
BID ITEM – ASPHALT DISTRIBUTOR WITH CHASSIS

Company Name: _____

Address: _____

Bid Submitted by: _____
(Name of company representative)

Title: _____ E-mail address: _____

Phone: _____ Fax: _____

By submitting this bid, we agree:

Initials

The equipment model number identified below meets the bid specs for this bid item

That the bid price will be honored for all counties for the period from **January 1, 2026** to **June 30, 2026**.

The equipment will be delivered at the bid price to all counties participating in the joint bid program

The company representative listed above will be the contact person for purchasing this bid item under the joint bid program

The bid is accompanied by a current catalog or model specification document for the model number identified below

The bid is accompanied by a copy of the manufacturer's standard warranty as required in the bid specifications

The bid includes the E-Verify documentation required by Alabama law

We comply with, and if awarded the contract, we will comply with, the requirements of Section 41-16-50 and Sections 41-16-160 to -166, Code of Alabama 1975.

If awarded the bid, a performance bond will be provided upon request

The bid documents include the **Manufacturer's Suggested Retail Price Sheet (MSRP) for the Standard Machine**.

ASPHALT DISTRIBUTOR WITH CHASSIS

Total Bid Price for Standard Machine: \$ _____
(Total Bid Price for Standard Machine Includes Freight Preparation, Delivery and Standard Warranty Costs)*

Freight Preparation and Delivery: \$ _____
(Included in Standard Machine Bid Price)

Manufacturer's Suggested Retail Price for Standard Machine: \$ _____

Equipment Model #: _____

Description: _____

Signature of company representative submitting bid: _____

Title: _____

***NOTE:** Award will be made based on the total cost of the **standard machine**. The total cost of the standard machine is to include freight preparation, delivery and standard warranty cost. Freight preparation and delivery will be excluded from the total bid price of the standard machine in determining the percentage discount for any available options.

BID SUBMITTAL FORM: OPTION COST SHEET ASPHALT DISTRIBUTOR WITH CHASSIS

By submitting this bid, we agree:

To offer any available options at the percent difference between the Manufacturer's Suggested Retail Price Sheet and the actual bid price on the Standard Machine* _____

The bid documents include the Manufacturer's Suggested Retail Price Sheet (MSRP) with **any available options** for the Standard Machine _____

Equipment Model #: _____

Description: _____

Signature of company representative submitting bid: _____

Title: _____

***Note:** The percent difference between the **Manufacturer's Suggested Retail Price Sheet (MSRP)** for the standard machine as specified by these **Bid Specifications** and the actual price bid by the vendor will be calculated to determine the percentage discount to be applied to any available options. The bid price of the freight preparation and delivery cost shall be excluded in determining the percentage discount to be applied to available options. Any individual county may choose to add any available option to the standard machine at the percentage discount at the time of purchase.

BID SPECIFICATIONS FOR ASPHALT DISTRIBUTOR WITH CHASSIS

GENERAL

These specifications shall be construed as the minimum acceptable standards for an **Asphalt Distributor with Chassis**. Should the manufacturer's current published data or specifications exceed these standards, the manufacturer's standards shall be considered minimum and shall be furnished. All integral parts not specifically mentioned in the scope of these specifications that are necessary to provide a complete working unit shall be furnished. Additionally, the machine offered for bid shall include all standard manufacturers' equipment. The asphalt distributor with chassis must be a new current production model and shall meet all EPA and other applicable standards at the time of manufacturer.

The use of specific names and numbers in the specification is not intended to restrict the bidder or any seller or manufacturer but is intended solely for the purpose of indicating the type, size and quality of equipment considered best adapted to the uses of counties participating in this joint bid.

BID SUBMITTAL FORM

Each bidder must submit his or her bid on the Bid Submittal Form included in the Invitation to Bid package. All written warranties to be submitted shall be attached to the Bid Submittal Form.

BID PRICE

The bid price shall include all destination charges, delivery charges, title fees, rebates, and all other applicable costs and refunds.

MANUALS

Each unit shall be provided with one (1) copy of the operator's manual, one (1) copy of the repair manual and one (1) copy of the current parts manual. Units will not be accepted for delivery until the manuals as outlined above are received by the purchaser.

REPLACEMENT PARTS AVAILABILITY

Parts must be available for 5 years or 7,500 hours of use for the piece of equipment bid. If replacement parts are not delivered within three (3) working days of an order being placed, the bidder will deliver an equivalent machine for the county to use at no cost to the county until such time as the parts are delivered to the county so it can affect repairs on its machine.

WARRANTY

Bidders shall submit a copy of the manufacturer's standard warranty. Warranty shall include service response time of maximum of 36 hours within notification by county.

Yes ____ No ____

Page or Attachment No. ____

OPERATING CAPACITY

Unit shall have a tank capacity of 2000 gallons.

Yes ___ No ___
Page # _____

TANK DESIGN

It is important that the Distributor be capable of returning all material in the spray bar, hand spray and distributing lines to the Distributor tank by means of pump suction. This function is to be accomplished without reversing the asphalt pump. Tank shall be bolstered and straddle mounted to allow for flexing of tank when heated.

Yes ___ No ___
Page # _____

Unit shall use volumetric metering with no bypass when spraying to ensure accuracy of application. Provision shall be made for easily draining the circulating system independently of the tank and for flushing circulating system and pump with not more than three (3) quarts of fuel oil so as not to dilute tank contents. .

Yes ___ No ___
Page # _____

Material: Shell to be 10-gauge steel. Tanks to have 10-gauge steel heads, deep dished and flanged, welded to tank shell both inside and outside for strength and durability.

Yes ___ No ___
Page # _____

Surge Plate: Tank to be supported with full section surge plate, deep dished and flanged, constructed of 10-gauge steel. To be spaced to provide adequate tank strength and proper surge control. Openings shall be provided in the surge plates for the free flow of material to the pump and large enough for a man to crawl through.

Yes ___ No ___
Page # _____

Manhole: 20" inside diameter manhole with quick-opening cover.

Yes ___ No ___
Page # _____

Overflow: 3" diameter overflow, extending at least 6 inches above the liquid, and draining internally only through the bottom of the tank in such a location as to clear all chassis members. Tank overflow design that drains asphalt material into the spill collar around manhole is not acceptable.

Yes ___ No ___
Page # _____

Tank design and construction to meet all applicable Federal Cargo Tank Regulations 49 CFR 173.247 and including DOT-406, HM-183, HM-198A, with consideration for hot asphalt products. Must have ASME tank approval number to assure that federal cargo tank regulations can be met.

Yes____No____

Page # _____

POWER UNIT

Type: Hydrostatic transmission, consisting of Infinitely variable displacement pump with a minimum displacement of 3.1 cubic inches per revolution, axial piston type. Electronic stroker control.

Yes____No____

Page # _____

Controls: Electronic micro-control of hydrostatic transmission for setting asphalt pump discharge rate shall be located in truck cab. Control to permit stopping the variable pump discharge without disconnecting the drive and be equipped with an override of the micro- control which shall allow increases in asphalt pump output for filling, sucking back, etc., without affecting application rate setting. Override control shall be located at rear of unit.

Yes____No____

Page # _____

BITUMEN PUMP

Type: Positive displacement rotary gear type. 4 1/2" suction x 4" discharge.

Yes____No____

Page # _____

Location: To be located below the bottom level of the tank so that the material will flow vertically from the suction to the discharge ensuring complete drainage when tank contents valve is closed.

Yes____No____

Page # _____

Capacity: Minimum of 400 gallons per minute.

Yes____No____

Page # _____

Self-Flushing line from fuel tank or heating system to fill line. Includes minimum 20 gallon capacity fuel tank with float level gauge. Located away from burners for safe operation.

Yes____No____

Page # _____

HEATING SYSTEM

Flues: (2) with (LPG) liquid petroleum gas burner, with minimum of 1,000,000 BTU per hour per burner capacity. With pressure regulator, valves, piping, and 52-gallon frame mounted tank to be furnished.

Yes___No___
Page #___

SPRAY BAR

Full circulating 16 feet in length, hinged to permit folding for traveling. Length of bar in folded position not to exceed 8 feet.

Yes___No___
Page #___

Positive circulation from one end of the bar to the other end, regardless of bar length or asphalt pump rate.

Yes___No___
Page #___

To consist of 8' center section with (2) folding wing sections with electric-air on-off in 1' increments, cab controlled and an electric-hydraulic spray bar shifting, lifting and wing folding, cab controlled.

Yes___No___
Page #___

Nozzles to be spaced on 4" centers on spray bar and shall have an individual valve for each spray Nozzle and capable of .18 to .45 gallons per sq. yard application rates. Each nozzle valve to have flip lever control so spray width can be adjusted, and allows individual valves to be disconnected without the use of tools or pulling pins. Right and left side wings (bar extensions) to relieve fore and aft. Pin replacement required when bar relieves.

Yes___No___
Page #___

Bar to adjust for positive or negative crown and also adjustment for pitch of bar to aim nozzle valves rearward. Sections to be interchangeable, right or left side.

Yes___No___
Page #___

AIR CONTROLS

Distributor shall be equipped with air controls. Air for the controls shall be obtained from the air system on the truck chassis. The Distributor air system shall include its own air reservoir (using of truck chassis reservoir not acceptable) with check valve set at 80 pounds to prevent loss of air on truck chassis brakes in case lines are ruptured. System shall have its own airline oiling device and controls shall be electric, located in cab convenient to operator.

Yes___No___
Page #___

All air solenoid valves and hydraulic solenoid valves are to be mounted to be accessible and serviceable from the ground without climbing on the machine.

Yes___No___
Page # _____

CONTROLS / INSTRUMENTATION

Computer with in-cab operator controls which include a computer-controlled switches for ten (minimum) preset application rates. Distance/volume reset switch. Application rate adjustment switch. Display select switch. System control of 4-way asphalt valve. Radar type sensor to pick up ground speed. In-cab instrumentation will include the following information on self-illuminated display(s) to include:

Yes___No___
Page # _____

Truck travel speed feet/minute or meters/minute.

Yes___No___
Page # _____

Application rate in gallons/square yard or liters/square yard.

Yes___No___
Page # _____

Pump rate in gallons/minute or liters/minute.

Yes___No___
Page # _____

Resettable distance sprayed in feet or meters.

Yes___No___
Page # _____

Resettable volume sprayed in gallons or liters.

Yes___No___
Page # _____

Low tank level warning.

Yes___No___
Page # _____

Warnings that travel speed and/or applications rate are beyond system capability.

Yes___No___
Page # _____

MISC

Dial Thermometer, 2", power wash down system including electric fuel pump, 15' hose with gun, wet storage box with drain plug & hinged lid, additional display in rear control box, 12' x 3" steel fill hose. (450 Deg) or 12' x 3" rubber fill hose (350 Deg), L.E.D. Lights, Sealed system, 3" cam lock fittings, wet storage box with drain plug and hinged lid and strobe light mounted on each corner.

Yes___No___
Page #_____

CHASSIS

Chassis shall be 2020 or newer with a GVW of 33,000 lbs. with min. 21,000 lb. rear axle

Yes___No___
Page #_____

Engine Shall be at least 280 hp. with VGT exhaust brake

Yes___No___
Page #_____

Frame shall be at least 10-5/8 steel rails

Yes___No___
Page #_____

Fuel tank shall be at least 70 gallons

Yes___No___
Page #_____

Shall have power steering

Yes___No___
Page #_____

Tires shall be 11R22.5 14 ply rating

Yes___No___
Page #_____

Transmission shall be Allison 3500 RDS 6 speed automatic shift with a Fuller AT-1202 auxiliary transmission

Yes___No___
Page #_____

Air conditioning shall be
Standard

Yes___No___
Page #_____

Shall have the following:

Heated mirrors

Yes___No___
Page #_____

LED Marker lights

Yes___No___
Page #_____

Bendix air dryer

Yes___No___
Page #_____

Tilting and Telescoping steering

Yes___No___
Page #_____

Engine protection shut down

Yes___No___
Page #_____

Battery disconnect switch

Yes___No___
Page #_____

Power door locks and windows

Yes___No___
Page #_____