INVITATION TO BID HEAVY FOUIPMENT

NOTICE OF BID OPENING

NOTICE IS HEREBY GIVEN that the Association of County Commissions of Alabama, which administers the Alabama County Joint Bid Program on behalf of Alabama's county governing bodies, shall receive and open bids for the purchase of zero (0) or more items of heavy road equipment at its office located at 2 North Jackson Street, Montgomery, Alabama, at **10:00 a.m. on Tuesday, November 18, 2025.** Bid specifications are available at http://www.alabamacounties.org/heavy-equipment/ for each of the following items:

Track Mount Excavators Compact Excavators Mini Track Excavators Wheeled Excavators **Highway Speed Truck Excavators Motor Graders** Wheel Loaders **Heavy Duty Dump Chassis Lowboy Tractors Lowboy Trailers** Half Round End Dump **Skid Steer Loader and Attachments Ride-on Industrial Boom Mowers** Rubber Tire Roller Vibratory Roller **One-man Pothole Patchers**

Trailer Mount Mastic Patcher/Crack Sealer Trailer Mounted Patcher – Diesel Trailer Mounted Patcher – Air Compressor/Tools Chip Spreader Asphalt Distributor Asphalt Milling Attachments Asphalt Storage Tanks Backhoes Bulldozers Dump Bodies Road Wideners Ride On Industrial Boom Mowers

Time is of the essence in submitting bids and only bids received in the Association office by 10:00 a.m. Central Time on Tuesday, November 18, 2025 will be opened and considered. Bidders and any other interested individuals are invited to attend the bid opening.

NOTICE OF BID OPENING PROCEDURES

All bids for Heavy Equipment will be opened and the name(s) of the bidders read aloud on the morning of the bid opening on Tuesday, November 18, 2025 at 10:00 a.m. at 2 North Jackson Street, Montgomery, AL. The specifics of each bid submitted will be compiled by the Association staff thereafter and will be available, upon written or emailed request, one week after the bid opening. Requests should be emailed to jointbid@alabamacounties.org.

THE INVITATION PACKAGE

The invitation package for each item to be bid includes: this invitation to bid, the written bid specifications for the particular item of heavy road equipment, and a Bid Submittal Form to be used in submitting a bid for that particular item. Bidders should verify that they have received all pages of the invitation package. If there are any omissions, the bidder should contact Kenya Howard in the Association office by mail, fax, or e-mail (jointbid@alabamacounties.org) to request missing pages. It is the responsibility of the

bidder to make this request in sufficient time to prepare and submit the bid in time for the bid opening. Bidders should carefully read and comply with all parts of the invitation package, including all attachments and/or any addendum.

PREPARING AND SUBMITTING BIDS

All bids must be typed or handwritten in ink on the attached Bid Submittal Form. The completed Bid Submittal Form shall be placed in front of and separated from all other documents included in the bid packet, such that it will be the first document viewed upon opening the bid packet.

Bids submitted in pencil and bids not submitted on the Bid Submittal Form will **not** be considered. All bids shall include a current catalog or model specification document for the equipment model number being offered for consideration. Bids submitted without such documentation will **not** be considered. Only information contained on the attached Bid Submittal Form and in the model specification document will be considered in evaluating bids.

Each separate requirement in the bid specification includes a block for indicating whether or not the item bid meets the specification. The bidder shall indicate compliance with each requirement by checking "Yes" or "No" in the block to the right of each bid specification. In addition, the bidder shall indicate the page number in the supplied manufacturer's equipment literature on which compliance with the specification can be verified. Failure to complete this portion of the bid form may result in the subject bid not being considered. Additionally, all bidders are required to submit a factory build/order sheet showing all of the standard and option items for each piece of equipment bid in order to assist the bid review committee in assuring that each bid is in conformance with the required bid specifications.

Each bid for one of the heavy equipment items included in the bid package must be submitted on the Bid Submittal Form for that item and forwarded in a separate envelope with the bid item and item number clearly identified on the outside of the envelope. Envelopes containing a "no bid" shall also include the words "NO BID" on the outside of the envelope. Facsimiles and e-mails will not be accepted. Bids submitted by "Express/Overnight" services must be in a separate inner envelope or package sealed and identified as stated above. All bids must be received in the Association office prior to the bid opening. Bids received after the deadline will be returned unopened.

The County Joint Bid Program reserves the right to require a performance bond from successful bidders as permitted under Alabama law. However, **no bid bond is required for this bid offering**.

All bids should be mailed or hand-delivered to:

ATTN: Alabama County Joint Bid Program
Association of County Commissions of Alabama or ACCA
2 North Jackson Street, FL 7, Montgomery, Alabama 36104 (Physical Address)
P.O. Box 5040, Montgomery, Alabama 36103 (Mailing Address)

BID SPECIFICATIONS

Please note that each piece of heavy equipment available for bid may include several different sizes and categories of machines. You should read each set of specifications very carefully as the differences vary depending upon the piece and size of equipment.

Where applicable, each bid submission shall include the separate cost of each item listed in the "Options" section of the bid specifications. However, all bids will be awarded on the basis of the **total cost of the machine with all options included.** Therefore, the "Bid Price" stated on the Bid Submittal Form must be the total cost, including the cost of all options.

Both parties agree that the Vendor SHALL extend to ALL counties purchasing this equipment any factory discounts, incentives or rebates that become available during the Contract Period; provided that there are no alterations from the bid specifications for this item required in order to receive the discount, incentive, or rebate. FURTHER, BOTH PARTIES AGREE THAT THE VENDOR SHALL EXTEND TO ALL COUNTIES PURCHASING THIS EQUIPMENT THE SAME PURCHASE PRICE AND DISCOUNTS AS THEY ARE AWARDED ON ANY OTHER NATIONAL PURCHASING COOPERATIVE APPROVED BY THE DEPARTMENT OF EXAMINERS OF PUBLIC ACCOUNTS FOR USE BY ALABAMA COUNTIES.

Once the bids have been awarded, any county participant purchasing under this program may, at its discretion, deduct one or more of the options set out in the bid specifications, and in such event, the cost of the option as stated on the bid shall be deducted from the total cost of the machine. There shall be no other deductions and no additions made to the machine by the purchasing county or by the vendor.

Any use of specific names and/or model numbers in the attached specifications is not intended to restrict the bidder or any seller or manufacturer but is included solely for the purpose of indicating the type, size, and quality of materials, product services, or equipment considered best adapted to the use of the counties participating in the joint bid program.

BIDDER QUALIFICATIONS

All bidders and all program participants must be in compliance with any applicable federal, state, county and municipal laws, regulations, resolutions and ordinances, including but not limited to, licensing, permitting, and taxation requirements. All bidders should be prepared to submit evidence or documentation as proof that they are properly licensed and permitted under any applicable laws upon request. Such evidence or documentation may be submitted with the bid. Additionally, all bidders shall provide proof that they are in compliance with the E-Verify requirements of Alabama's Immigration Law (Ala. Code § 31-13-1 et seq.). All bidders shall also affirm that they are in compliance with, and will comply with, Alabama's anti-boycott law (Ala. Code § 41-16-5) and anti-economic boycott law (Ala. Code § 41-16-160 et seq.).

BID AWARD

The Houston County Commission will serve as the awarding authority for all bids and will award all contracts at a regular meeting of the Houston County Commission. Any and all bids submitted in compliance with this invitation to bid shall be considered, and award will be made to the lowest responsible bidder meeting bid specifications as determined by the awarding authority in compliance with Alabama law. All bids will be reviewed and evaluated by a committee created for that purpose, which committee will make comments and recommendations to the awarding authority regarding the award. All factors contained in each invitation package will be evaluated in determining the successful bidder, and any omissions of the stated requirements may be cause for rejection of the bid submitted. The awarding authority reserves the right to reject any and all bids, to waive any informality in bids, and to accept in whole or in part such bid or bids solely at its discretion.

The contract period will be six (6) months with an option to renew each six (6) months not to exceed a period of three (3) years under identical price, terms, and conditions upon the mutual consent of the vendor and the awarding authority. Any renewal contract shall be approved in writing by the vendor and the awarding authority no later than **60 days** prior to the expiration of the existing contract.

CONTACT REGARDING BIDS AND INVITATION

Contact initiated by a potential bidder with any county official, county employee, or member of the Association staff shall only be as specifically set out in this Invitation to Bid. Any questions related to the bid or the County Joint Bid Program shall be directed to Association staff in writing under the procedures set out in this Invitation to Bid. Additionally, a bidder may contact the Association in writing to request an appointment to review bid specifications following the bid opening. However, there shall be no communication with any county official or county employee regarding this bid between the date of this invitation and the date of bid award. Any contact other than as set out here shall be deemed as an attempt to unduly influence the bid award and shall be grounds for rejection of the bid submitted by the bidder initiating such other contact.

Any questions or problems related to downloading or obtaining copies of this Invitation to Bid should be directed to **Kenya Howard** at <u>jointbid@alabamacounties.org</u> or **334-263-7594**.

Any other questions or requests for additional information regarding this invitation or the bid specifications shall be submitted **in writing** no later than five (5) days prior to bid opening to:

ATTN: Patrick McDougald Association of County Commissions of Alabama P.O. Box 5040 Montgomery, Alabama 36104

OR

Patrick McDougald
Email: pattymackdaddy@gmail.com

BID SUBMITTAL FORM Alabama County Joint Bidding Program BID ITEM – LOWBOY TRACTOR - OPTION B

| Company Name: | |
|--|----------|
| Address: | |
| Bid Submitted by:(Name of company representative) | |
| Title: E-mail address: | |
| Phone: Fax: | |
| By submitting this bid, we agree: | Initials |
| That the equipment model number identified below meets the bid specs for this bid item | |
| That the bid price will be honored for all counties for the period from January 1, 2026 to June 30, 2026. | |
| That the equipment will be delivered at the bid price to all counties participating in the joint bid program | |
| That the company representative listed above will be the contact person for purchasing this bid item under the joint bid program | |
| That the bid is accompanied by a current catalog or model specification document for the model number identified below | |
| That the bid is accompanied by a copy of the manufacturer's standard warranty as required in the bid specifications | |
| That the bid includes the E-Verify documentation required by Alabama law | |
| We comply with, and if awarded the contract, we will comply with, the requirements of Section 41-16-50 and Sections 41-16-160 to -166, Code of Alabama 1975. | |
| That, if awarded the bid, a performance bond will be provided upon request | |
| That an option sheet with individual pricing is attached | |

| Total Bid Price including options: \$ | |
|---|---|
| Equipment Model #: | _ |
| Description: | |
| Signature of company representative submitting bid: | |
| Title | |

OPTION COST SHEET FOR LOW BOY TRACTOR OPTION B

| <u>Options</u> | Option Price | |
|--|--------------|--|
| Dual purpose wet line kit | \$ | |
| Aluminum cab guard | \$ | |
| 60" Long Light bar | \$ | |
| 15L engine in place of 13L engine (18) Speed Automated Manual Transmission with torque input capacity of 1850 Ft LBs in place of standard 18 Speed Manual Transmission. | \$ \$ | |
| NOTE: Award will be made on the basis of the total cost of the Low Boy Tractor with the option included. However, a county may, at its discretion, deduct the above-referenced option from the Low Boy Tractor, and in such event, the cost of the option as stated on the bid shall be deducted from the total cost of the Low Boy Tractor. There shall be no other deductions and no additions made to the Low Boy Tractor by the purchasing county or by the vendor. | | |
| Equipment Model #: | | |
| Description: | | |
| Signature of company representative submitting bid: | | |
| Title: | | |

BID SPECIFICATIONS FOR HEAVY DUTY LOW BOY TRACTOR-OPTION B

GENERAL

These specifications shall be construed as the minimum acceptable standards for a heavy duty Low Boy tractor. Should the manufacturer's current published data or specifications exceed these standards, the manufacturer's standards shall be considered minimum and shall be furnished. All integral parts not specifically mentioned in the scope of these specifications that are necessary to provide a complete working unit shall be furnished. Additionally, the machine offered for bid shall include all standard manufacturers' equipment.

The use of specific names or numbers in the specifications is not intended to restrict the bidder or any seller or manufacturer, but is intended solely for the purpose of indicating the type, size, and quality of equipment considered best adapted to the uses of counties participating in this joint bid.

Note all units offered for bid must be of manufacturer's current production model and must be fully compliant with 2021 EPA standards without the use of EPA engine credits. Chassis should be equipped with the appropriate diesel particulate filter and SCR after treatment system.

BID SUBMITTAL FORM

Each bidder must submit his or her bid on the Bid Submittal Form included in the invitation to bid package. All written warranties to be submitted shall be attached to the Bid Submittal Form.

BID PRICE

The price bid shall include all destination charges, delivery charges, title fees, rebates and all other applicable costs and refunds.

REPLACEMENT PARTS AVAILABILITY

Parts must be available for 5 years or 500,000 miles of use for the piece of equipment bid.

ASSEMBLY AND DELIVERY

The selling Low Boy Tractor dealer shall be responsible for delivery of the completed unit to the purchasing county with all requested options.

DOT INSPECTION AND SAFETY EQUIPMENT

Prior to delivery each unit shall be DOT inspected and include the appropriate documentation and decal. In addition, each unit shall be equipped with the required fire extinguisher and reflective triangle kit.

WARRANTY

Bidders shall submit a copy of the manufacturer's standard warranty along with a complete explanation of the warranty with their bid. Warranty must be transferable. Warranty must include the following minimum coverage:

Basic Vehicle: 1 Year or 100,000 miles

Diesel Engine: 2 year or 250,000 miles. However, counties will have the option to purchase additional coverage (an extended warranty) if negotiated between the purchasing county and successful bidder within the first 9 months of truck purchase.

Transmission: 3 Year or 300,000 miles Rear Carriers: 3 Year or 300,000 miles Yes___ No ___ Page #_____ or Attachment **ENGINE AND RELATED COMPONENTS** Shall be an in line 6 design 13 liter minimum, turbo charged diesel engine capable of Yes No developing 500HP minimum with a governed engine speed of 1800RPM or more. Page # Torque rating to be a minimum of 1,850FT Lbs. Engine shall have full wet replaceable cylinder liners. Fuel injection system to be Yes ___ No ___ Page #_____ equipped with a unit pump or unit injector style with CARB idle reduction. Yes ___ No ___ Air intake system shall have a minimum of 1 filter elements in with a restriction indicator. Air cleaner element/elements mounted either under or outside of the hood. Page #_____ Engine cooling system to have a minimum 1,240 square inches of frontal area, aluminum Yes ____ No ____ core radiator with silicone hoses throughout and coolant protection to -34 degrees F. Page #_____ Yes ___ No ___ Fan drive to be Horton two speed type Page #_____ Yes ___ No ___ Exhaust to be DUAL vertical with turnouts. Heat shields and stacks to be bright Page #_____ finish. Yes ___ No ___ Diesel Particulate Filter and SCR catalyst to be mounted under passenger door Page #_____ with aluminum cover. Factory installed integral Engine Brake. Yes ___ No ___ Page #_____ STARTING AND ELECTRICAL SYSTEM Yes ___ No ___ 12-Volt system fuse/circuit breaker protected Page #_____ Yes ___ No ___ 12V gear reduction starter, 12V 160 amp alternator Page #_____

| Unit should be equipped with a backup alarm | Yes No Page # |
|---|-------------------------|
| (3) 12V maintenance free group 31 batteries with 700 cold cranking amps each. Batteries to be mounted in a single steel box with polished aluminum cover LH side under cab. | Yes No Page # |
| TRANSMISSION AND DRIVELINE | |
| A manual eighteen (18) speed overdrive design, with over all gear ratio coverage of 19.73 and a minimum first gear reduction of 14.4 to 1 and a torque input capacity of 1850 FT#. | Yes No Page # |
| Transmission should have oil cooler with dash mounted temperature gauge, left and right-side PTO access gears with appropriate clearance. | Yes No Page # |
| Main drivelines Spicer 1810HD or Equivalent with coated splines/ inter axle 1810 with coated splines. | Yes No Page # |
| CAB EXTERIOR Cab to be Class 8 design for construction and vocational applications. Aluminum and composite construction for corrosion resistance. Huck bolted or Hen rob fastened construction. Minimum width 1.9 meters. | Yes No Page # |
| Drop style side windows for improved driver's downward visibility. | Yes No Page # |
| Stainless steel piano type door hinges. No automotive type hinges allowed. | Yes No Page # |
| Rear of engine may not extend into cab. No doghouse in firewall is allowed. | Yes No Page # |
| Both doors should have power windows and power mirrors. | Yes No Page # |
| One piece curved windshield. No bonded in windshield allowed. | Yes No Page # |
| Cab mounting should be air suspended at rear on at least 1 air bags. | Yes No Page # |
| Cab should feature: Dual air horns in addition to the standard electric signal horn | Yes No Page # |

| LED marker lights | Yes No Page # |
|---|------------------|
| Cab mounted heated mirrors with convex mirrors mounted directly below heated mirrors Stainless Steel exterior sun visor | Yes No Page # |
| Hood is to be a full tilting composite design. Includes bright finished grill and grill surround. | Yes No Page # |
| Cab and hood paint color to be selected from manufacturer's standard non-metallic paint chart. | Yes No Page # |
| CAB INTERIOR Cab interior to include the following: | |
| Cab interior is to be Midgrade level fully groomed with with headliner, back wall and door panels. | Yes No Page # |
| AM/FM/WB and Bluetooth radio with clock and six gauges for engine oil temperature, transmission oil temperature, turbo boost pressure, air suspension pressure, & dual rear axle oil temperature. | Yes No Page # |
| Cab should have interior sun visors on both sides of cab. | Yes No Page # |
| Black appearance with chrome gauge surrounds | Yes No Page # |
| Center mount console with cup holders | Yes No Page # |
| Full adjusting tilt and telescopic steering column | Yes No Page # |
| Multifunction Driver Display to include the following: Average and real time fuel economy RPM display Ignition timer Trip information Truck information Onboard diagnostics Gear display (automated manual only) | Yes No Page # |

| Cab seats should be: | | |
|---|----------------|------|
| Driver High Back air ride design with dual arm rests | Yes | |
| | Page #_ | |
| Passenger High Back air ride design with dual arm rests | Yes | |
| | Page #_ | |
| Both seats to have fabric and/or vinyl covering with required lap and shoulder | | |
| belts. | Yes | No |
| | Page #_ | |
| Factory installed integral heater/air conditioning (HVAC) with R134A refrigerant | Voc | No |
| and rotary type air conditioner compressor. HVAC unit to be | Yes Page # | |
| firewall mounted to allow for easier access to components. | · ago ». | |
| Two way radio newer leads with mounting plate installed in averband console | Voc | Mo |
| Two- way radio power leads with mounting plate installed in overhead console with dual mirror mounted antennas. | Yes Page #_ | |
| The saar minor mounted antormas. | · ago "_ | |
| One additional deals mounted power outlet to be furnished | Voo | Ma |
| One additional dash mounted power outlet to be furnished. | Yes Page #_ | |
| | · aga "_ | |
| Windshield wipers to be two (2) speed electric with washer and intermittent | Yes | |
| feature. Wiper motor and linkage to be mounted external of the cab on firewall for easier access. | Page #_ | |
| Power door locks. | Yes | No |
| | Page #_ | |
| AIR BRAKES | | |
| | Yes | No |
| ABS/ATC/ESP with YAW control. | Page #_ | |
| Air compressor should have a minimum 18.7CFM capacity and Bendix heated air dryer wit | ·h | |
| All compressor should have a minimum 10.7 of M capacity and behalf heated all dryer wit | Yes | _ No |
| extended purge. | Page #_ | |
| FRAME/BUMPER/FUEL TANKS | | |
| Steel 120,000 PSI steel frame rails 10.6875" x 3.50" x 0.50" with a section modulus | Yes | _ No |
| of 22.35 and a RBM per rail of 2,683,000. | Page #_ | |
| Minimum 205" wheelbase with a 134" cab to axle. | Yes | No |
| William 200 Wildelbuse Will a 101 Gab to axio. | Page #_ | |
| Harring disks 2 minute annual manuals and Harring to the Harring to the second | V | Ma |
| Heavy-duty 3 piece cross members. Huck bolt fasteners Throughout where possible. | Yes Page # | |

| Front bumper Bright Finish steel tapered with two removable tow pins. | | _ No |
|--|-----|------|
| Dual fuel tank(s) to be aluminum with a minimum of 100-gallon capacity on RH side and 75-gallon capacity on LH side. 7" wide heavy duty fuel tank straps. | | _ No |
| Minimum 20.7-gallon capacity DEF tank mounted on LH side with polished cover | | _ No |
| Chassis to be equipped with frame mounted bright finish quarter fenders mounted ahead of front pull axle and rear mud flaps mounted at end of frame on heavy duty spring loaded brackets. | | _ No |
| FIFTH WHEEL Tractor to be equipped with a Holland 24" air slide fifth wheel. Fifth wheel should have pinning feature for dump trailer use. Pins should be removable type for Multi-purpose use. | | _ No |
| FRONT AXLE Dana Spicer E-1462W or Equivalent 14.6K axle with 16,000# multi leaf suspension and shock absorbers. Threaded spring hanger pins and bushings replacing rubber bushings. Wide track front axle for improved wheel cut. | | _ No |
| 13,200# integral power steering. | | _ No |
| Minimum of 24.5" spring centers. | | _ No |
| Unitized sealed (maintenance free) front wheel hubs. | | _ No |
| Sealed tapered kingpins and bearings. | | _ No |
| Meritor "S" cam design (or equivalent) Federal Reduced Stopping Distance Compliant Brakes. | Yes | _ No |
| Front wheels to be polished aluminum ten (10) hole bud style, hub piloted 24.5" x 8.25". | | _ No |
| Front tires to be 16 ply 11R24.5 radials Bridgestone, Goodyear, Yokohama, Michelin. | Yes | _ No |

REAR AXLE

Dual Meritor RT46-164PEH or Equivalent 46K tandem rear axle with heavy wall housing and integral lube pump (4.10 ratio). 46,000# air ride suspension with shock absorbers, torque and tracking rods, and dump valve. Yes ___ No ___ In cab Power divider lock out valve with warning light and buzzer. Page #_____ Yes ____No ___ Driver controlled inter wheel differential locks for both rear axles with Page #_____ manual valve and warning light. Meritor "S" cam design (or equivalent) Federal Reduced Stopping Yes ___ No ___ Distance Compliant Brakes. Page #_____ Yes ___ No ___ Brake chambers shall be (4) 30/30 Long Stroke for Federal Reduced Page #_____ Stopping Distance Compliant style chambers Polished aluminum ten- (10) hole bud style, hub piloted 24.5 x 8.25 rear wheels. Yes ___ No ___ Page #_____ Rear tires to be 14 ply 11R 24.5 traction radials Bridgestone, Goodyear, Yokohama, or Michelin. Yes No Page #_____

OPTIONS

In addition the bid must also include the cost for each of the following options, itemized separately on the bid:

| Dual-pu low boy | rpose wet line system for use with a dump trailer or a detachable neck trailer. | Yes Page #_ | _ No |
|--------------------|---|----------------|------|
| Aluminu | um Cab Guard with window | Yes Page #_ | |
| 60-Inch | Long Light bar with Two Power Supplies and Eight Strobes (4 Front/4 Rear) -Shall include built-in, rear facing stop/tail/turn signals and Rear Facing work Lights | Yes Page #_ | _ No |
| | -Light bar shall be mounted on the Aluminum Cab Guard with controls mounted inside the cab. | Yes Page # | No |
| , , , | eed Automated Manual Transmission with torque input capacity Ft LBs in place of standard 18 Speed Manual. | Yesl Page#_ | |
| 15L eng | gine in place of 13L engine | Yes Page#_ | No |

NOTE: Award will be made on the basis of the total cost of the Low Boy Tractor with all options included. However, a county may, at its discretion, deduct the above-referenced option from the Low Boy Tractor, and in such event, the cost of the option as stated on the bid shall be deducted from the total cost of the Low Boy Tractor. There shall be no other deductions and no additions made to the Low Boy Tractor by the purchasing county or by the vendor.