INVITATION TO BID HEAVY EQUIPMENT

NOTICE OF BID OPENING

NOTICE IS HEREBY GIVEN that the Association of County Commissions of Alabama, which administers the Alabama County Joint Bid Program on behalf of Alabama's county governing bodies, shall receive and open bids for the purchase of zero (0) or more items of heavy road equipment at its office located at 2 North Jackson Street, Montgomery, Alabama, at **10:00 a.m. on Tuesday, November 18, 2025**. Bid specifications are available at http://www.alabamacounties.org/heavy-equipment/ for each of the following items:

Track Mount Excavators
Compact Excavators
Mini Track Excavators
Wheeled Excavators
Highway Speed Truck Excavators
Motor Graders
Wheel Loaders
Heavy Duty Dump Chassis
Lowboy Tractors
Lowboy Tractors
Lowboy Trailers
Half Round End Dump
Skid Steer Loader and Attachments
Ride-on Industrial Boom Mowers
Rubber Tire Roller
Vibratory Roller

One-man Pothole Patchers
Trailer Mount Mastic Patcher/Crack Sealer
Trailer Mounted Patcher – Diesel
Trailer Mounted Patcher – Air Compressor/Tools
Chip Spreader
Asphalt Distributor
Asphalt Milling Attachments
Asphalt Storage Tanks
Backhoes
Bulldozers
Dump Bodies
Road Wideners

Ride On Industrial Boom Mowers

Time is of the essence in submitting bids and only bids received in the Association office by 10:00 a.m. Central Time on Tuesday, November 18, 2025 will be opened and considered. Bidders and any other interested individuals are invited to attend the bid opening.

NOTICE OF BID OPENING PROCEDURES

All bids for Heavy Equipment will be opened and the name(s) of the bidders read aloud on the morning of the bid opening on Tuesday, November 18, 2025 at 10:00 a.m. at 2 North Jackson Street, Montgomery, AL. The specifics of each bid submitted will be compiled by the Association staff thereafter and will be available, upon written or emailed request, one week after the bid opening. Requests should be emailed to jointbid@alabamacounties.org.

THE INVITATION PACKAGE

The invitation package for each item to be bid includes: this invitation to bid, the written bid specifications for the particular item of heavy road equipment, and a Bid Submittal Form to be used in submitting a bid for that particular item. Bidders should verify that they have received all pages of the invitation package. If there are any omissions, the bidder should contact Kenya Howard in the Association office by mail, fax, or e-mail (jointbid@alabamacounties.org) to request missing pages. It is the responsibility of the bidder to make this request in sufficient time to prepare and submit the bid in time for the bid opening. Bidders should carefully read and comply with all parts of the invitation package, including all attachments and/or any addendum.

PREPARING AND SUBMITTING BIDS

All bids must be typed or handwritten in ink on the attached Bid Submittal Form. The completed Bid Submittal Form shall be placed in front of and separated from all other documents included in the bid packet, such that it will be the first document viewed upon opening the bid packet.

Bids submitted in pencil and bids not submitted on the Bid Submittal Form *will not* be considered. All bids shall include a current catalog or model specification document for the equipment model number being offered for consideration. Bids submitted without such documentation *will not* be considered. Only information contained on the attached Bid Submittal Form and in the model specification document will be considered in evaluating bids.

Each separate requirement in the bid specification includes a block for indicating whether or not the item bid meets the specification. The bidder shall indicate compliance with each requirement by checking "Yes" or "No" in the block to the right of each bid specification. In addition, the bidder shall indicate the page number in the supplied manufacturer's equipment literature on which compliance with the specification can be verified. Failure to complete this portion of the bid form may result in the subject bid not being considered.

Each bid for one of the heavy equipment items included in the bid package must be submitted on the Bid Submittal Form for that item and forwarded in a separate envelope with the bid item and item number clearly identified on the outside of the envelope. Envelopes containing a "no bid" shall also include the words "NO BID" on the outside of the envelope. Facsimiles and e-mails will not be accepted. Bids submitted by "Express/Overnight" services must be in a separate inner envelope or package sealed and identified as stated above. All bids must be received in the Association office prior to the bid opening. Bids received after the deadline will be returned unopened.

The County Joint Bid Program reserves the right to require a performance bond from successful bidders as permitted under Alabama law. However, **no bid bond is required for this bid offering**.

All bids should be mailed or hand-delivered to:

ATTN: Alabama County Joint Bid Program
Association of County Commissions of Alabama or ACCA
2 North Jackson Street, FL 7, Montgomery, Alabama 36104 (Physical Address)
P.O. Box 5040, Montgomery, Alabama 36103 (Mailing Address)

BID SPECIFICATIONS

Please note that each piece of heavy equipment available for bid may include several different sizes and categories of machines. You should read each set of specifications very carefully as the differences vary depending upon the piece and size of equipment.

The award will be based on the total cost of the **Standard Machine** bid by the lowest responsible bidder. Each Bid shall include a **Manufacturer's Suggested Retail Price Sheet (MSRP)** for each machine bid. The percent difference between the Manufacturer's Suggested Retail Price (MSRP) for the standard machine as specified by these bid specifications and the actual price bid by the vendor will be calculated and that percentage discount shall be applied to any options an individual county may choose to add to the machine.

Both parties agree that the Vendor SHALL extend to ALL counties purchasing this equipment any factory discounts, incentives or rebates that become available during the Contract Period; provided that there are no alterations from the bid specifications for this item required in order to receive the discount, incentive, or rebate. FURTHER, BOTH PARTIES AGREE THAT THE VENDOR SHALL EXTEND TO ALL COUNTIES PURCHASING THIS EQUIPMENT THE SAME PURCHASE PRICE AND DISCOUNTS AS THEY ARE AWARDED ON ANY OTHER NATIONAL PURCHASING COOPERATIVE APPROVED BY THE DEPARTMENT OF EXAMINERS OF PUBLIC ACCOUNTS FOR USE BY ALABAMA COUNTIES.

Once the bids have been awarded, any county participant purchasing under this program may, at its discretion, add any of the vendor's available options at the same discount off the Manufacturer's Suggested Retail Price Sheet as was applied to the Standard Machine Price Bid.

Any use of specific names and/or model numbers in the attached specifications is not intended to restrict the bidder or any seller or manufacturer but is included solely for the purpose of indicating the type, size, and quality of materials, product services, or equipment considered best adapted to the use of the counties participating in the joint bid program.

ACQUISITION AND FINANCING OPTIONS

The awarded Vendor will provide the equipment, including any options required by the purchaser, at the awarded price as contracted through the Joint Bid Program. The purchaser may secure its own financing to acquire the equipment or execute any financial options available under Alabama law with the awarded Vendor in order to acquire the equipment.

BIDDER QUALIFICATIONS

All bidders and all program participants must be in compliance with any applicable federal, state, county and municipal laws, regulations, resolutions and ordinances, including but not limited to, licensing, permitting, and taxation requirements. All bidders should be prepared to submit evidence or documentation as proof that they are properly licensed and permitted under any applicable laws upon request. Such evidence or documentation may be submitted with the bid. Additionally, all bidders shall provide proof that they are in compliance with the E-Verify requirements of Alabama's Immigration Law (Ala. Code § 31-13-1 et seq.). All bidders shall also affirm that they are in compliance with, and will comply with, Alabama's anti-boycott law (Ala. Code § 41-16-5) and anti-economic boycott law (Ala. Code § 41-16-160 et seq.).

BID AWARD

The Houston County Commission will serve as the awarding authority for all bids and will award all contracts at a regular meeting of the Houston County Commission. Any and all bids submitted in compliance with this invitation to bid shall be considered, and award will be made to the lowest responsible bidder meeting bid specifications as determined by the awarding authority in compliance with Alabama law. All bids will be reviewed and evaluated by a committee created for that purpose, which committee will make comments and recommendations to the awarding authority regarding the award. All factors contained in each invitation package will be evaluated in determining the successful bidder, and any omissions of the stated requirements may be cause for rejection of the bid submitted. The awarding authority reserves the right to reject any and all bids, to waive any informality in bids, and to accept in whole or in part such bid or bids solely at its discretion.

The contract period will be six (6) months with an option to renew each six (6) months not to exceed a period of three (3) years under identical price, terms, and conditions upon the mutual consent of the vendor and the awarding authority. Any renewal contract shall be approved in writing by the vendor and the awarding authority no later than 60 days prior to the expiration of the existing contract.

CONTACT REGARDING BIDS AND INVITATION

Contact initiated by a potential bidder with any county official, county employee, or member of the Association staff shall only be as specifically set out in this Invitation to Bid. Any questions related to the bid or the County Joint Bid Program shall be directed to Association staff in writing under the procedures set out in this Invitation to Bid. Additionally, a bidder may contact the Association in writing to request an appointment to review bid specifications following the bid opening. However, there shall be no communication with any county official or county employee regarding this bid between the date of this invitation and the date of bid award. Any contact other than as set out here shall be deemed as an attempt to unduly influence the bid award and shall be grounds for rejection of the bid submitted by the bidder initiating such other contact.

Any questions or problems related to downloading or obtaining copies of this Invitation to Bid should be directed to Kenya Howard at jointbid@alabamacounties.org or 334-263-7594.

Any other questions or requests for additional information regarding this invitation or the bid specifications shall be submitted **in writing** no later than five (5) days prior to bid opening to:

ATTN: Patrick McDougald Association of County Commissions of Alabama P.O. Box 5040 Montgomery, Alabama 36104

OR

Patrick McDougald

Email: pattymackdaddy@gmail.com

BID SUBMITTAL FORM Alabama County Joint Bid Program BID ITEM – HIGHWAY SPEED TRUCK MOUNTED EXCAVATOR - 2WD

Company Name:		
Address:		
Bid Submitted by:(Name of compa		
Title: E-I	mail address:	
Phone:	Fax:	
By submitting this bid, we agree:	Initia	ıls
The equipment model number identified below meets the	he bid specs for this bid item	
That the bid price will be honored for all counties for the June 30, 2026.	e period from January 1 , 2026 to	
The equipment will be delivered at the bid price to all conjoint bid program	ounties participating in the	
The company representative listed above will be the co this bid item under the joint bid program	ontact person for purchasing	
The bid is accompanied by a current catalog or model model number identified below	specification document for the	
The bid is accompanied by a copy of the manufacturer in the bid specifications	's standard warranty as required	
The bid includes the E-Verify documentation required by	oy Alabama law	
We comply with, and if awarded the contract, we we Section 41-16-50 and Sections 41-16-160 to -166,		
If awarded the bid, a performance bond will be provided	d upon request	
The bid documents include the Manufacturer's Sugger for the Standard Machine	gested Retail Price Sheet (MSRP)	

Total Bid Price for Standard Machine: \$
(Total Bid Price for Standard Machine Includes Freight Preparation, Delivery and Standard Warranty Costs)*
Freight Preparation and Delivery: \$(Included in Standard Machine Bid Price)
Manufacturer's Suggested Retail Price for Standard Machine: \$
Equipment Model #:
Description:
Signature of company representative submitting bid:
Title:

* NOTE: Award will be made based on the total cost of the **Standard Machine**. The total cost of the standard machine is to include freight preparation, delivery and standard warranty cost. Freight preparation and delivery will be excluded from the total bid price of the standard machine in determining the percentage discount for any available options.

BID SUBMITTAL FORM: OPTION COST SHEET

By submitting this bid, we agree:	
To offer any available options at the percent difference between the Manufacturer's Suggested Retail Price Sheet and the actual bid price on the Standard Machine*	
The bid documents include the Manufacturer's Suggested Retail Price Sheet (MSRP) with any available Options for the Standard Machine	
Equipment Model #:	
Description:	
Signature of company representative submitting bid:	_
Title:	

*Note: The percent difference between the Manufacturer's Suggested Retail Price Sheet (MSRP) for the standard machine as specified by these Bid Specifications and the actual price bid by the vendor will be calculated to determine the percentage discount to be applied to any available options. The bid price of the freight preparation and delivery cost shall be excluded in determining the percentage discount to be applied to available options. Any individual county may choose to add any available option to the standard machine at the percentage discount at the time of purchase.

HIGHWAY SPEED TRUCK MOUNTED EXCAVATOR - 2WD

GENERAL:

It is the intent of this specification to describe a carrier mounted, single engine, full hydraulic telescoping boom excavator capable of excavating, grading, sloping, backfilling, etc., equivalent to a **Gradall model D172**. The unit shall be current production and the manufacturer's printed literature shall be submitted with the bid.

The excavator shall consist of a revolving upper-structure mounted on a rubber-tired highway speed carrier complete with remote control as follows:

Rotating Structure

The Upper-structure shall be supported on the carrier by an internal swing bearing and shall be capable of continuous swing at not less than 8 RPM. The counterweight shall weigh not more than 4,500 pounds and the tail swing shall not exceed 6' 7". The swing system shall incorporate a spring set, hydraulic release swing parking brake. Anti-slip paint is required on all walking surfaces.

Yes	_No	
Page #		

Boom

The boom shall be triangular in cross section and shall consist of a main section and a telescoping section. Adjustable boom rollers shall be furnished on both boom sections. The telescope section shall be equipped with pin-on buckets and shall telescope hydraulically through a distance of not less than 10′ 3″. The boom assembly shall be supported by a cradle that provides for the tilt of the entire boom assembly and attachment through an arc of not less than 220° about its longitudinal axis. The boom shall rise through an arc of not less than 30° and lower not less than 60°. The attachment shall open and close through an arc of not less than 165°.

Yes	No	
Page #_		

Hydraulic System

Power for the hydraulic system shall be supplied by the carrier engine. There shall be one-piston pump providing not less than **58 GPM @ 3800 PSI**. The pump shall be engaged with a PTO to the transmission. The system shall provide for simultaneous boom, swing and remote functions, quick disconnect type pressure check ports, minimum **51 HP** swing motor, minimum **21 HP** tilt motor and appropriate relief valves, oil cooler and filter with service indicator. The pressurized reservoir shall be of minimum **62-gallon** capacity and shall be equipped with sight level gauges. System operating pressure shall not exceed **3,800 PSI**.

Yes	No
Page #_	

Cab & Controls

The operator's cab shall be all weather with safety glass windows and skylight. The cab shall be complete with front window that rolls overhead for storage, wiper washer, AC, AM/FM radio, four-way adjustable

seat, acoustical treatment, signal horn, filtered heater and defroster. The controls shall be dead-man type consisting of 2 electronic joysticks mounted on the armrests. Engine controls	self-cen ols shall	itering include
key type ignition switch with neutral start and throttle. There shall be warning lights for low engine maintenance, hydraulic filter condition and level. There shall be an automatic engi low oil pressure or high coolant temperature. Remote carrier propel, steering and automa	ne shutd tic diggin	own for ng brake
shall be controlled by two-foot pedals and two joystick mounted switches. The hydraulic resystem shall be complete with an emergency brake control and travel alarm.		
		_ No
<u>Carrier</u>	3	
The carrier shall be a 4x2 rubber-tired type, 8' 6" wide with a 37,320-lb . gross vehicle a The frame shall be the manufacture's standard, reinforced with Steel frame insert (1/4" ful beyond the front spring hanger in the front and extending throughout the total length of the There shall be a separate sub-frame for Upper-structure mounting. The wheelbase of t minimum of 15' 10" and the frame width a minimum of 34" . There shall be a minimum 8 and a minimum 13-gallon DEF tank . The carrier shall be equipped with transmission control.	I C-chan frame to he unit s 0-gallon	inel) from the rear shall be a fuel tanl
	Yes	_ No
<u>Engine</u>	r age "	
The carrier shall be powered by the current emissions certified "clean idle" liquid cooled tu after cooled diesel engine with a minimum of 300 hp @ 2600 RPM . The engine shall be electric grid warmer, two stage dry type air cleaner, spin on fuel filter, and oil filter. The electric shall be 12-volt and incorporate a 160-amp alternator.	equipped	with an
	Yes	_ No
Transmission	Page #	
The carrier shall be equipped with a 5-speed Automatic transmission, Allison 3500RDS , speeds and 1 reverse speed. Max road speed shall be 55 mph .	having 5	forward
	Yes	_ No
Axles and Suspension	Page #	
The front axle shall be rated at 14,320-lb. minimum. The front suspension shall be leaf	type and	d shall be

complete with automatic lockout cylinders.

Yes	No
Page #	

The rear axle shall be rated at 23,000 lb. minimum with a 6.43 ratio and single reduction. equipped with a cab controlled differential lock.	. The axle	shall be
equipped with a cab controlled differential lock.	Yes Page #_	_ No
<u>Brakes</u>	J -	
The carrier shall be equipped with anti-lock braking system to include four-wheel cam ty automatic slack adjusters. The system shall include spring set brakes incorporating emerg brakes on the rear axle. The system shall include a minimum 18.7 C.F.M. air compressor a air dryer with automatic purge valve and thermostatically controlled heater. Wheels and Tires	gency and	d parking cant type No
The wheels shall be 10-stud hub piloted disc. The front tires shall be single 275/80R2 traction tread. The four rear tires shall be M/S11R22.5 14 ply with mud and snow traction		No
Steering	-	
Carrier steering shall be integral hydraulic power steering.	Yes Page #_	No
<u>Cab</u>		
The carrier cab shall be a two-man, isolation mounted cab. The cab shall include a driv suspension seat, a basic high back non-suspension passenger seat, 3-point high visibility passenger seat belts, adjustable tilt and telescoping steering column, tinted safety glass wi lining, and heater/defroster and Air Conditioner. Both side windows must open for vadjustable.	orange di indows, a	river and coustical and be
	Page #_	
The cab instrument panel shall include the following equipment: Gauges for oil patemperature, dual air tank pressures, fuel level, indicator for DEF level, low DEF level was voltmeter, hour meter, speedometer and odometer and intake air restriction indicator. The complete with electronic cruise control, AM/FM radio, headlights, tail lights, stoplights identification light clusters, turn indicators, hazard warning, electric windshield wiper and alarm and plain and convex mirrors on both sides.	arning light ne carrier s, back-u d washer, Yes	ht/alarm, shall be ip lights, back-up No
	Page #_	

Operating Weight

Working weight.	includina 60"	excavating bucket	and half-full fuel	tanks shall meet o	r exceed 32,200 pounds.

	Yes	No
	Page	#
Discription Constitutions with 7011 Europetius Discript		
Digging Specifications with 60" Excavating Bucket	10///	
Maximum Digging Depth:		"
Maximum Surface Reach:		
Boom Tilt (Total Arc/CW Arc/CCW Arc):		10-/110-
Minimum Reach (Cleanup - Bucket level, ground level boom retracted):		
Maximum Digging Depth (165 º Pivot):		/ Oo Le I
Minimum Boom Arc:		-60º ievei
Tail Swing:		
Maximum Height with Bucket Below ground level:		
Maximum Loading Height		
Bucket Pivot	165°	
		No
	Page	#
Lifting Capacity without bucket, at ground level		
Over-End	Over-	
15' 0" Radius4,760 lbs4		
20' 0" Radius3,365 lbs		
22' 9" Max Radius2,950 lbs	2,950	lbs.
		No
	Page	#
Travel Dimensions with 60" Excavating Bucket		
Width		
Height with bucket		
Length	27′ 1"	
		No
	Page	#
The equipment shall be capable of performing all functions without the use of outriggers.		
		No
	Page	#