

BID SUBMITTAL FORM
Alabama County Joint Bid Program
BID ITEM – ASPHALT MILLING ATTACHMENT- OPTION C – 48/72 INCH

Company Name: Asphalt Zipper Inc

Address: 310 West 700 South
Pleasant Grove, UT 84062

Bid Submitted by: David Fokken
(Name of company representative)

Title: Municipal Sales Manager E-mail address: daveF@asphaltzipper.com

Phone: 801-847-3220 Fax: 801-847-3250

By submitting this bid, we agree:

Initials

The equipment model number identified below meets the bid specs for this bid item

df

That the bid price will be honored for all counties for the period from **January 1, 2026** to **June 30, 2026**.

df

The equipment will be delivered at the bid price to all counties participating in the joint bid program

df

The company representative listed above will be the contact person for purchasing this bid item under the joint bid program

df

The bid is accompanied by a current catalog or model specification document for the model number identified below

df

The bid is accompanied by a copy of the manufacturer's standard warranty as required in the bid specifications

df

The bid includes the E-Verify documentation required by Alabama law

df

We comply with, and if awarded the contract, we will comply with, the requirements of Section 41-16-50 and Sections 41-16-160 to -166, Code of Alabama 1975.

df

If awarded the bid, a performance bond will be provided upon request

df

The bid documents include the **Manufacturer's Suggested Retail Price Sheet (MSRP) for the Standard Machine**

df

BID SUBMITTAL FORM: OPTION COST SHEET
ASPHALT MILLING ATTACHMENT- OPTION C – 48/72 INCH

By submitting this bid, we agree:

To offer any available options at the percent difference between the Manufacturer's Suggested Retail Price Sheet and the actual bid price on the Standard Machine*

def

The bid documents include the Manufacturer's Suggested Retail Price Sheet (MSRP) with **any available Options** for the Standard Machine

def

Equipment Model #: 480Xi (48"), 720Xi (72")

Description: 48"/72" Asphalt Milling Attachment with trailer

Signature of company representative submitting bid: David Fell

Title: Municipal Sales Manager

***Note:** The percent difference between the **Manufacturer's Suggested Retail Price Sheet (MSRP)** for the standard machine as specified by these **Bid Specifications** and the actual price bid by the vendor will be calculated to determine the percentage discount to be applied to any available options. The bid price of freight preparation and delivery cost shall be excluded in determining the percentage discount to be applied to available options. Any individual county may choose to add any available option to the standard machine at the percentage discount at the time of purchase.

ASPHALT MILLING ATTACHMENT- OPTION C – 48/72 INCH

Total Bid Price for Standard Machine: \$ 249,480.75 (Tier 4) 48 Inches
(Total Bid Price for Standard Machine Includes Freight Preparation, Delivery and Standard Warranty Costs) *

Freight Preparation and Delivery: \$ 6,210.75
(Included in Standard Machine Bid Price)

Manufacturer's Suggested Retail Price for Standard Machine: \$ 260,181.82

Equipment Model #: 480Xi

Description: 48" Asphalt Milling Attachment with trailer

Signature of company representative submitting bid: Daniel Falk

Title: Municipal Sales Manager

Total Bid Price for Standard Machine: \$ 303,320.75 (Tier 4) 72 Inches
(Total Bid Price for Standard Machine Includes Freight Preparation, Delivery and Standard Warranty Costs) *

Freight Preparation and Delivery: \$ 6,210.75
(Included in Standard Machine Bid Price)

Manufacturer's Suggested Retail Price for Standard Machine: \$ 317,764.71

Equipment Model #: 720Xi

Description: 72" Asphalt Milling Attachment with trailer

Signature of company representative submitting bid: Daniel Falk

Title: Municipal Sales Manager

***NOTE:** Award will be made based on the total cost of the **Standard Machine**. The total cost of the standard machine is to include freight preparation, delivery and standard warranty cost. Freight preparation and delivery will be excluded from the total bid price of the standard machine in determining the percentage discount for any available options.

BID SPECIFICATIONS FOR ASPHALT MILLING ATTACHMENT- OPTION C – 48/72 INCH

GENERAL

These specifications shall be construed as the minimum acceptable standards for a diesel-powered portable asphalt milling-recycling attachment, which attaches to the front of a loader by way of the bucket, and shall be complete with a trailer specifically designed to transport the unit from one job to the next. Should the manufacturer's current published data or specifications exceed these standards, the manufacturer's standards shall be considered minimum and shall be furnished. All integral parts not specifically mentioned in the scope of these specifications that are necessary to provide a complete working unit shall be furnished. Additionally, the machine offered for bid shall include all standard manufacturer's equipment. The portable asphalt milling-recycling attachment must be a new current production model and shall meet all EPA and other applicable standards at the time of manufacture.

The use of specific names and numbers in the specifications is not intended to restrict the bidder or any seller or manufacturer, but is intended solely for the purpose of indicating the type, size and quality of equipment considered best adapted to the uses of counties participating in this joint bid.

BID SUBMITTAL FORM

Each bidder must submit his or her bid on the Bid Submittal Form included in the invitation to bid package. All written warranties to be submitted shall be attached to the Bid Submittal Form.

BID PRICE

The price bid shall include all destination charges, delivery charges, title fees, rebates, and all other applicable costs and refunds.

MANUALS

Each unit shall be provided with one (1) copy of the operator's / owner's manual. Units will not be accepted for delivery until the manual as outlined above is received by the purchaser.

WARRANTY

Units purchased under this specification shall be warranted against defects in materials and workmanship for a period of not less than one (1) year and unlimited hours, whichever occurs first, from date of delivery to customer. Items thought to be defective will be returned to factory prepaid to be repaired or replaced.

YES ☒ NO
PG # <u>1,2,3</u>
Attachment <u>spec</u>

ENGINE

Engine: Water-cooled, six-cylinder Tier 4 EPA compliant, to a water-cooled, 6.7liter diesel developing no less than 215 hp at rated RPM and generating 670 ft./lbs. of torque (48 inch), 260 hp and 730 ft./lbs. (72 inch). Shall be equipped with 24-volt electric system including starter, battery, and an alternator. Battery shall be maintenance free with side mounted, threaded posts. Alternator shall produce 27 volts and 70 amps.

YES ☒	NO
PG #	1, 3

Shall be equipped with 24-volt electrical system including starter, battery, wiring harness, and alternator.

YES ☒	NO
PG #	1

The engine shall have manufacturer approved fuel and oil filters, approved type air cleaner that consists to a two-element filter system, and an adequate exhaust system. Fuel tank shall have a capacity of no less than 40 US Gallons (48 inch) and 50 U.S. Gallons (72 inch). Cooling system shall be protected to -20° F with ethylene glycol type antifreeze in compliance with engine manufacturer's specifications. Tachometer and a digitally controlled multifunction display panel that can selectively indicate, at a minimum; fuel level, engine hours, percent engine load, engine oil pressure, system voltage, and engine temperature.

YES ☒	NO
PG #	1, 3

CONTROL AND INSTRUMENT PANEL

Shall be equipped with an operator control panel located on the belt cage side of the machine. This allows machine operator to control depth of cut and throttle function on curb side of machine away from traffic. A key switch to control engine start, run and shut off, clutch on/off, and water on/off will also be mounted on this panel as well as a maintenance hatch open/close control and an emergency stop switch.

YES ☒	NO
PG #	1

Wireless Remote Control: The unit shall have a wireless remote control consisting of a receiver and hand-held transmitter that will be able to control engine speed, depth of cut, clutch on/off, and water on/off and will also be able to shut off the engine from a distance of fifty feet.

YES ☒	NO
PG #	2

CUTTER HEAD ASSEMBLY

Heavy Duty Cutter Head: Shall be equipped with HD (Standard Heavy Duty) Cutter head and shall be securely attached to the machine's frame and enclosed by heavy-duty cowling. Maximum cutting depth shall be approximately 12" (Twelve Inches). Shall have a maximum cutting width of 48" or 72". Shall have a minimum of 142 snap-in bits that insert into blocks that shall be welded securely to the skin of the cutter head. The cutter head and housing shall be designed so that only pulverized materials leave the drum assembly.

YES ☒	NO
PG #	1, 3

Cutter Head Service Access Hatch: Unit shall be equipped with a powered hydraulic system that will lift an access hatch to expose the cutter head for service. This system will be independent of the active hydraulic system and will operate without the diesel engine running.

YES ☒	NO
PG #	2

CUTTER HEAD DRIVE

The power from the engine shall be transmitted to the cutter head through a power take-off system and V-belts to a planetary reduction gearbox at the cutter head drum. Drive belt tension shall be regulated by the use of an idler wheel and air bag. Air bag pressure shall be monitored by a gauge mounted on the machine frame and visible to the operator on the ground.

YES ☒	NO
PG #	1

MOUNTING SYSTEM

Unit shall be designed and recommended by the manufacturer to attach to the front bucket of loader with a gross operating weight of at least 35,000 lbs. (48 inch) and 39,000 lbs. (72 inch).

YES ☒	NO
PG #	2, 3

Unit shall be equipped with a hydraulic bucket clamping system to secure the unit to the bucket of the host vehicle. This bucket clamping system will be actuated by the active hydraulic system. System will maintain a pressure of 1500 psi. The system will have pressure relief valve to safeguard against over pressurizing the system.

YES ☒	NO
PG #	2

Attachment system shall allow the loader to load and unload the reclaiming / trenching machine from its transport trailer. Mounting of the machine shall not require the removal of the bucket nor shall it require the use of a quick connect or attachment pins.

YES ☒	NO
PG #	2

ACTIVE HYDRAULIC SYSTEM

The machine shall be equipped with a hydraulic system consisting of a hydraulic gear pump that is engine powered by an auxiliary drive adapter, reservoir, pressure side filter, hydraulic manifold with tandem center valves, lines and two cylinders to actuate and control depth of cut.

YES ☒	NO
PG #	1, 2

All hydraulic fittings shall be leak free and O-ring face seal or O-ring boss design. Hydraulic fluid shall be dyed red to distinguish it from other engine fluids. The reservoir shall hold at least four U.S. gallons of hydraulic fluid.

YES ☒	NO
PG #	1, 2

OUTER FRAME

The frame shall allow continuous actuated control in cutting depth from 0 to 12 inches. This frame shall rest on ski wear plates that provide distributed support for the machine during operation. The frame shall have improved side shielding that provides for better material containment, reducing the amount of debris that could be ejected from the dome. The frame shall also allow for new material such as crushed gravel or emulsions to be mixed with the pulverized asphalt.

YES ☒	NO
PG #	2

INTEGRATED ENHANCED PULVERIZING SYSTEM

The machine shall be equipped with a fully integrated enhanced containment system that fully encloses the cutting chamber at all cutting depths, allows baffle position to be hydraulically adjusted to control material size on the fly, allows grade adjustment of up to 1.5 inches across the cutting width, and allows depth control to be fully independent of loader bucket height.

YES ☒	NO
PG #	2

WEIGHT

Milling/trenching/recycling machine (without trailer) shall have an approximate dry weight of 11,500 lbs. (48 inch), 13,375 lbs. (72 inch).
12,200

YES ☒	NO
PG #	2, 3

ADDITIONAL EQUIPMENT

Tools for changing cutter bits and an extra twenty-five carbide bits and five extra blocks shall be provided. Two bucket retention chains equipped with grab hooks and slip locks shall be included.

YES ☒	NO
PG #	2

COLOR

Units shall be powder coated with factory standard colors. Shall include manufacturer's standard warning, safety, and instructional decals. Shall have identification and serial number decals.

YES ☒	NO
PG #	2

TRAINING

The successful bidder shall furnish qualified personnel to instruct operators and service technicians on operation and maintenance of units purchased under this specification. Up to four hours of training in the correct use and maintenance of the machine will be given at time of delivery.

YES	☒	NO
PG #	3	

Specifications

720Xi (72") Portable Asphalt Reclaiming / Trenching Machine with Integrated Enhanced Pulverizing System with Custom Transport / Storage Trailer and Option for 480Xi (48") Version

1. **General:** This specification shall cover a diesel powered portable asphalt reclaiming / trenching machine that attaches to the bucket of a wheel loader.
2. **Engine:** Water-cooled, six-cylinder Tier IV Final EPA compliant, electronically controlled 6.7 liter turbo diesel engine developing 260 hp at rated RPM and generating 730 foot pounds of peak torque. Engine shall be equipped with a remote throttle and an exhaust system with muffler. Shall be equipped with 24-volt electrical system including starter, batteries, wiring harness, and alternator. Shall be equipped with an engine management system that includes low oil pressure shutdown, high coolant temperature shutdown, hour meter, and starter protection lockout. Batteries shall be maintenance free with top mounted, threaded posts and shall provide no less than 1,000 cold cranking amps at 0 degrees F. Alternator shall produce 27 volts and 70 amps. Shall be equipped with engine manufacturer's approved 2-element air cleaner, oil and fuel filters. Fuel tank shall have a capacity of no less than 50 U.S. Gallons. Radiator cooling system shall be protected to -20° F with ethylene glycol type antifreeze in compliance with engine manufacturer's specifications.
3. **Engine Instrument Panel:** Shall be a wireless remote type, which is placed in the cab of the loader to allow the loader operator to monitor engine functions without leaving the cab. Shall include engine emergency stop (E-Stop) control, clutch disengage & engine idle down, and a digitally controlled multifunction display panel that can selectively indicate, at a minimum: fuel level, engine hours, percent engine load, engine oil pressure, system voltage, engine speed, and engine coolant temperature.
4. **Control Panel:** Shall be equipped with an operator control panel located on the belt cage side of machine which allows machine operator to control depth of cut, engine speed, hydraulic clutch engage & disengage, baffle position, water pump on/off, maintenance hatch open/close control, and bucket clamping as well as indicators for belt tension and clutch pressure on curb side of machine away from traffic. A key switch to control engine start, run and shutoff will also be mounted on this panel as well as an emergency stop switch.
5. **Z-Pro Cutter Head Assembly:** Shall be securely attached to the machine's main-frame, enclosed by a heavy-duty cowling. Maximum cutting depth shall be approximately 12" (twelve inches). Shall have a standard cutting width of 72" (seventy-two inches). Shall have a minimum of 174 carbide tipped, 19mm shank, snap-in bits with spring-steel full sleeve retainers and washers. The bit holders or blocks shall have locating pins that insert into a base that is welded to the cutter head. The cutter head and housing shall be designed so that only pulverized materials leave the drum assembly.
6. **Cutter Head Drive:** Power shall be transmitted from the engine to the cutter head through a power take-off and V-belts to a planetary reduction gearbox at the cutter head. Drive belt tension shall be regulated by the use of an idler wheel and hydraulic cylinder. The proper belt tension shall be monitored by a gauge mounted on the machine frame and visible to the operator on the ground.
7. **Active Hydraulic System:** Unit shall be equipped with a hydraulic system consisting of a hydraulic gear pump that is engine powered by an auxiliary drive adapter, reservoir, pressure side filter, hydraulic manifold with poppet valves, lines and two cylinders with electronic position feedback to actuate and

control depth and angle of cut. All hydraulic fittings shall be leak free and o-ring face seal or o-ring boss design. Hydraulic fluid shall be dyed red to distinguish it from other engine fluids. The reservoir shall hold at least five U.S. gallons of hydraulic fluid.

8. **Hydraulic Clutch:** The machine shall be equipped with a hydraulically activated clutch that will engage and disengage the cutter head by a button on the control panel or by a button on the handheld wireless remote control.
9. **Mounting:** Unit shall be designed and recommended by the manufacturer to mount to the bucket of a wheel loader with a gross operating weight of at least 39,000 lbs. Mounting system shall allow the loader to load and unload the reclaiming / trenching machine from its transport trailer. Mounting of the machine shall not require the removal of the bucket nor shall it require the use of a quick connect, quick connect hooks or direct attachment pins. No other mounting systems will be considered.
10. **Hydraulic Bucket Clamps:** Unit shall be equipped with a hydraulic bucket clamping system to secure the unit to the bucket of the host vehicle. System will maintain a pressure of 1500 psi. The system shall have pressure relief valve to safeguard against over pressurizing the system.
11. **Cutter Head Service Access Hatch:** Unit shall be equipped with a powered hydraulic system that will lift the access hatch to expose the cutter head for service and clamp down during operation. This system will operate without the diesel engine running. Hatch shall have an electrical safety interlock that will prevent the engine from running or starting while the hatch is in the open position.
12. **Integrated Enhanced Pulverizing System:** Unit shall be equipped with a fully integrated enhanced containment system that fully encloses the cutting chamber at all cutting depths, allows baffle position to be hydraulically adjusted to control material size on the fly, allows grade adjustment of up to 1.5 inches across the cutting width, and allows depth control to be fully independent of loader bucket height.
13. **"X" Frame Design:** The frame shall allow continuous actuated control in cutting depth from 0 to 12 inches. This frame shall rest on ski wear plates that provide distributed support for the machine during operation. The frame shall have improved side shielding that provides for better material containment, reducing the amount of debris that could be ejected from the dome. The frame shall also allow for new material such as crushed gravel or emulsions to be mixed with the pulverized asphalt.
14. **Weight:** Reclaiming / trenching machine (without optional trailer) shall have an approximate dry weight of 13,375 pounds.
15. **Additional Equipment:** Tools for changing cutter bits and a supply of 25 extra bits and 5 extra blocks shall be provided. Two bucket retention chains for holding the machine in the loader bucket shall be included.
16. **Wireless Remote Control:** The unit shall have a wireless remote control consisting of a receiver and hand held transmitter that will be able to control engine speed, clutch, depth & angle of cut, baffle position, and engine stop. It will function up to a distance of 50 feet.
17. **Color:** Unit shall be powder coated with factory standard colors. Shall include manufacturer's standard warning, safety, and instructional decals. Shall have identification and serial number decals.

- 18. Warranty:** Units purchased under this specification shall be warranted against defects in materials and workmanship for a period of one year from date of delivery to customer with unlimited hours of use. Customer shall have direct and immediate access to factory technical experts for items thought to be defective. Defective items shall then be either repaired, replaced or referred to an in-state local service center under direction of factory technicians.
- 19. Training:** Manufacturer shall furnish qualified personnel to instruct operators and service technicians on the operation and maintenance of units purchased under this specification. Up to four hours of training in the correct use and maintenance of the unit shall be given at time of delivery. Manufacturer shall furnish one (1) copy of the owner's / operator's manual at time of delivery.
- 20. Custom Transport / Storage Trailer:** The Unit shall include its own custom transport trailer. Custom trailer shall allow the machine to transport inset into trailer with a lower center of gravity. Shall include a secured tool box and serve as a safe working platform for field maintenance. Shall be a heavy-duty (18,000 LBS GVW) tandem axle trailer specifically designed by the manufacturer for transporting the asphalt reclaiming / trenching machine. The frame shall be constructed of steel channel; rectangular steel tubing or I beam with all welded construction. Shall have steel wheels. Hubs shall run on tapered roller bearings. Tires shall be the size and load bearing capacity to handle the machine at highway speeds. The trailer shall be equipped with electric brakes and automatic breakaway system in compliance with current ICC requirements. Trailer coupler shall use a standard pintle hitch. The trailer shall come with four independent attachments that secure unit to trailer with grade 70 transport chains and ratchet style load binders. The trailer shall have a lockable toolbox, tongue jack, machine supports, and all necessary lights and reflectors to meet U.S. Federal DOT and ICC requirements. Shall come complete with trailer wiring connectors.

Option for 48" Version:

- 21. Optional Downsize to 4' (forty-eight inch) Version:** As an option, the same piece of equipment shall be available in a 48" wide model. The specifications shall be the same as those listed above with the following exceptions:
- a. Engine: shall be a 6.7 liter diesel engine developing 215 hp at rated RPM and generating 670 foot-pounds of peak torque. . . Fuel tank shall have a capacity of no less than 40 U.S. Gallons.
 - b. Z-Pro Cutter Head Assembly: shall have a standard cutting width of 48" (forty-eight inches). Shall have a minimum of 142 carbide tipped, 19mm shank, snap-in bits.
 - c. Mounting: the Unit shall be designed and recommended to mount to the front bucket of a wheel loader with a gross operating weight of at least 35,000 lbs.
 - d. Weight: shall have an approximate dry weight of 12,200 pounds.
 - e. Custom Transport / Storage Trailer: shall be a heavy-duty (16,000 LBS GVW) tandem axle trailer.

ASPHALT ZIPPER, INC. LIMITED WARRANTY

All new Asphalt Zipper machines used in locations in the United States and Canada include the following warranties from the date of training in the U.S. and the date of delivery in Canada.

- **Engine - 24 months or 2,000 hours, whichever comes first (Engine Manufacturer)**
- **Engine Emission Warranty. 5 years from the date the machine is placed in service (Engine Manufacturer).**
- **Planetary Gear Box – 12 months, unlimited hours (Planetary Manufacturer)**
- **PTO (Power Take Off) - 12 months, unlimited hours (PTO Manufacturer)**
- **Materials and Workmanship – 12 months, unlimited hours (Asphalt Zipper, Inc.)**

Warrantable issues will be handled either directly with Asphalt Zipper, Inc. or the nearest Asphalt Zipper authorized service partner at the sole discretion of Asphalt Zipper, Inc.

All warranty issues and repairs must be pre-approved and coordinated through the Asphalt Zipper, Inc. service department. Most warranty and service issues can usually be resolved over the telephone or through email communications. Asphalt Zipper will generally request that photos and a written statement be submitted via email of issues and the circumstances surrounding those issues. Defective items will likely be requested to be returned to Asphalt Zipper, Inc.'s facility or to an assigned authorized Asphalt Zipper repair facility closer to you. Upon inspection, defective items will either be repaired or replaced at Asphalt Zipper, Inc.'s sole discretion.

All pre-approved repairs must have a written email authorization by an Asphalt Zipper Customer Service representative prior to starting any warranty work. Asphalt Zipper, Inc. has a flat rate labor allowance for pre-approved work completed by the Customer in the field.

Asphalt Zipper, Inc. warrants all of its Asphalt Zipper Models for the pulverizing or milling of asphalt, chip seal or bitumen surfaces, gravel roads with 3" minus and smaller materials or asphalt over concrete and very limited amounts of use in unreinforced concrete. **A prolonged use of the Asphalt Zipper machine in concrete or rock laden materials will void all warranties. Failure to perform periodic maintenance and adjustments or any unauthorized modifications will also void all warranties.**

The following are considered "Normal Wear Items" and are not included under this limited warranty:

- | | | |
|--------------------------|------------------------|---------------------------|
| • Primary Air filter | • Hydraulic filter | • All Belts |
| • Secondary Air filter | • Planetary fluid | • Skid feet and Skid skis |
| • Engine oil filter | • Engine oil | • Grind box skids |
| • Fuel / Water Separator | • Bits / Cutting Tools | • Batteries |
| • Fuel filter | • Blocks | |

Asphalt Zipper, Inc. shall not be liable for any damages to the Asphalt Zipper machine or other equipment or injuries to operating personnel or others when the machine or parts / components are operated in an unsafe manner or contrary to any written instructions to include but not limited to the training instruction checklist and the operator's safety and operating manuals. Customer assumes full responsibility to bear the financial burden of all expenses associated with any environmental or structural damage, no matter what the nature, or irrespective of how the damage occurred, at the site of operations. Customer agrees that the equipment shall not be used in violation of any government regulations. Customer is responsible for correct operation and maintenance of the Asphalt Zipper machine and all of its wear parts. Asphalt Zipper, Inc. shall not be financially liable for any down time or loss of production or for any other cost due to equipment failure, misuse, abuse, or applications outside the scope of this warranty.

The above limited warranty comprises Asphalt Zipper, Inc.'s sole and entire International Limited Warranty obligation. All other warranties expressed or implied, including without limitation warranties on merchantability and fitness for a particular purpose or application are expressly excluded.

Manufacturer's Suggested Retail Price Sheet (MSRP)

11/13/2025

Option C

<u>Machine and Trailer</u>	<u>MSRP</u>
480Xi	260,181.82
720Xi	317,764.71

Options

300 Gallon Hitch Mount Water System	8,352.94
300 Gallon Heavy Hitch Mount Water System	9,941.18
150 Gallon Wheel Assist Mount Water System	6,502.67
300 Gallon Wheel Assist Mount Water System	9,208.56
48" Wheel Assist System	31,951.87
72" Wheel Assist System	32,663.10
48" Wheel Assist Custom Trailer Upgrade	18,171.12
72" Wheel Assist Custom Trailer Upgrade	16,679.14
Trailer Upgrade to 5th Wheel or Gooseneck Compatible	4,508.02
260 HP Tier 4 Final Performance Engine	15,566.85
280 HP Tier 4 Final Performance Engine	TBD
Accu-Flow Liquid Delivery System	16,037.43
Emulsion Injection System	TBD
Retractable Breaker Bar System (48")	9,085.56
Retractable Breaker Bar System (72")	9,620.32
Enhanced Pulverizing / Material Control System	TBD
48" Quick Coupler System	TBD
72" Quick Coupler System	TBD
48" Side Shift Tilt System	TBD
72" Side Shift Tilt System	TBD
48" QC / SST Custom Trailer Upgrade	TBD
72" QC / SST Custom Trailer Upgrade	TBD
SST / Wheel Assist Custom Trailer Upgrade	TBD
Starter Kit	TBD
Extra 1 Year Warranty	TBD



Asphalt Zipper

The Most Economical Way to Open Utility Trench in Asphalt

November 12, 2025

Association of County Commissions of Alabama
P.O. Box 5040
Montgomery, AL 36103

RE: E-verification for bids

This letter is to confirm that Asphalt Zipper, Inc. is in compliance with the e-verify requirements for Alabama. At this time, Asphalt Zipper does not employ any individuals in the state of Alabama. If Asphalt Zipper were to employ persons in the state of Alabama in the future, the company would comply with the verification process Alabama has set forth.

Currently, Asphalt Zipper uses a PPO (Helpside Inc.) to handle employment, payroll and benefits administration. The PPO requires that all Asphalt Zipper employees working in the United States complete the federal I9 form and provide the required documents, which have been verified, to prove eligibility to work in the United States. This process meets all applicable federal rules and regulations as well as all state regulations for the states where these employees reside.

Please let us know if you have any questions.

Regards,

Patrick Duke
Asphalt Zipper / Asst. Controller