

**BID SUBMITTAL FORM**  
**Alabama County Joint Bid Program**  
**Heavy Equipment – Bid Item: Road Widener Attachment - Option A**

Company Name: Pittman Tractor Company Inc.

Address: 9652 Milton Jones Rd.  
Daphne, AL 36526

Bid Submitted by: Lee Pittman

(Name of company representative)

Title: Business Development Manager E-mail address: Lee@PittmanTractor.com

Phone: 251-621-3555 Fax: 251-621-5626

By submitting this bid, we agree:

Initials

The equipment model number identified below meets the bid specs for this bid item

LP

That the bid price will be honored for all counties for the period from **January 1, 2026** to **June 30, 2026**.

LP

The equipment will be delivered at the bid price to all counties participating in the joint bid program.

LP

The company acknowledges the freight preparation and delivery price is to be included in the total bid price for the standard machine.

LP

The company representative listed above will be the contact person for purchasing this bid item under the joint bid program.

LP

The bid is accompanied by a current catalog or model specification document for the model number identified below.

LP

The bid is accompanied by a copy of the manufacturer's standard warranty as required in the bid specifications.

LP

The bid includes the E-Verify documentation required by Alabama law.

LP

We comply with, and if awarded the contract, we will comply with, the requirements of Section 41-16-50 and Sections 41-16-160 to -166, Code of Alabama 1975.

LP

If awarded the bid, a performance bond will be provided upon request.

LP

The bid documents include the **Manufacturer's Suggested Retail Price Sheet (MSRP) for the Standard Machine.**

LP

Total Bid Price for Standard Machine: \$ 160,701.40

(Total Bid Price for Standard Machine Includes Freight Preparation, Delivery and Standard Warranty Costs) \*

Freight Preparation and Delivery: \$ 5,500.00  
(Included in Standard Machine Bid Price)

Manufacturer's Suggested Retail Price for Standard Machine: \$ 172,446.00

Equipment Model #: Midlund WA

Description: WA Road Widener Attachment option A.

Signature of company representative submitting bid: 

Title: Business Development Manager

\* **NOTE:** Award will be made based on the total cost of the **Standard Machine**. The total cost of the standard machine is to include freight preparation, delivery and standard warranty cost. Freight preparation and delivery will be excluded from the total bid price of the standard machine in determining the percentage discount for any available options.

## BID SUBMITTAL FORM: OPTION COST SHEET

By submitting this bid, we agree:

To offer any available options at the percent difference between the Manufacturer's Suggested Retail Price Sheet and the actual bid price on the Standard Machine\* ✓

The bid documents include the **Manufacturer's Suggested Retail Price Sheet (MSRP)** for the Standard Machine ✓

Equipment Model #: Midland WA

Description: WA Road Widener Attachment

Signature of company representative submitting bid: [Signature]

Title: Business Development Manager

**\*Note:** The percent difference between the **Manufacturer's Suggested Retail Price Sheet (MSRP)** for the standard machine as specified by these **Bid Specifications** and the actual price bid by the vendor will be calculated to determine the percentage discount to be applied to any available options. The bid price of the freight preparation and delivery cost shall be excluded in determining the percentage discount to be applied to available options. Any individual county may choose to add any available option to the standard machine at the percentage discount at the time of purchase.

# **BID SPECIFICATIONS FOR BID ITEM – Road Widener Attachment - Option A**

## **GENERAL**

These specifications shall be construed as the minimum acceptable standards for a **Road Widener Attachment**. Should the manufacturer's current published data or specifications exceed these standards, the manufacturer's standards shall be considered minimum and shall be furnished. All integral parts not specifically mentioned in the scope of these specifications that are necessary to provide a complete working unit shall be furnished. Additionally, the machine offered for bid shall include all standard manufacturer's equipment. The roller must be a new current production model. The roller must be a new current production model and shall meet all EPA and other applicable standards at the time of manufacture.

The use of specific names and numbers in the specifications is not intended to restrict the bidder or any seller or manufacturer but is intended solely for the purpose of indicating the type, size, and quality of equipment considered best adapted to the uses of counties participating in this joint bid.

## **BID SUBMITTAL FORM**

Each bidder must submit his or her bid on the Bid Submittal Form included in the invitation to bid package. All written warranties to be submitted shall be attached to the Bid Submittal Form.

## **BID PRICE**

The price bid shall include all destination charges, delivery charges, title fees, rebates, and all other applicable costs and refunds.

## **MANUALS**

Each unit shall be provided with one (1) copy of the operator's manual, (1) copy of the repair manual and one (1) copy of the current parts manual. Units will not be accepted for delivery until the manuals as outlined above are received by the purchaser.

## **REPLACEMENT PARTS AVAILABILITY**

Parts must be available for 5 years or 7,500 hours of use for the piece of equipment bid. If replacement parts are not delivered within three (3) working days of an order being placed, the bidder will deliver an equivalent machine for the county to use at no cost to the county until such time as the parts are delivered to the county so it can affect repairs to its machine.

## **WARRANTY**

Bidders shall submit a copy of the manufacturer's standard warranty. Warranty shall include service response time of maximum of 36 hours within notification by county.

Yes  No   
Page# 1  
or  
Attachment

**BID SPECIFICATIONS  
FOR  
BID ITEM – Road Widener Attachment - Option A**

**ATTACHES TO**

Most makes of loaders, graders and pavers. USED WITH All types of aggregates and hot asphalt.

Yes  No   
Page No. 2-3

**CAPACITY**

Variable to 600 tons per hour.

Yes  No   
Page No. 2-3

**WIDTH OF SPREAD**

Standard 1' to 8'; optional 10'.

Yes  No   
Page No. 2-3

**DEPTH OF SPREAD**

12" below to 12" above pavement. WEIGHT Not to exceed 8400 pounds.

Yes  No   
Page No. 2-3

**OVERALL WIDTH**

Not to exceed 11 '6".

Yes  No   
Page No. 3

**HOPPER**

Width-inside 9' 8" minimum.

Apron Full Width of hopper,  $\frac{3}{4}$ " thick rubber type.

Yes  No   
Page No. 4

**PUSH ROLLERS**

Rollers must be self-cleaning and oscillating type to maintain proper truck alignment.

Rigid rollers acceptable. **Frame** Push roller frame must be extendable (14" travel) to match with various types of trucks

Yes  No   
Page No. 3

**CONVEYOR**

Drive High torque hydraulic motor mounted on drive pulley shaft. Motor shall be movable to opposite end with minimal effort. Motor shall be reversible by interchanging 2 hydraulic hoses. Belt Conveyor belt must be 24" wide positive drive type to eliminate slippage and wandering under load. Belt shall consist of two (2) drive chains bolted to each edge of the heat and oil resistant two (2) ply. Belt splice shall be bolted hinged type stainless steel.

Yes  No   
Page No. 2-4

### **PULLEYS DRIVE**

Pulleys shall be identical at each end of the conveyor so that belt can be driven from either end without changing the pulleys. Each pulley shall have two (2) drive sprockets for driving the positive drive conveyor.

**Idlers** Conveyor idlers shall be ball bearing type. Conveyor must be supported by a minimum of 30 rollers to reduce belt deflection and stress on the belt when starting under load. Idlers shall be spaced on minimum 4" centers to properly support belt and minimize material leakage beneath sideboard.

Yes  No \_\_\_\_\_  
Page No. 2+4

### **SIDBOARDS**

Shall be adjustable and replaceable rubber type. Mounting must be in a retainer for easy access and adjustment with removable steel plate covers for protection from hopper load.

Yes  No \_\_\_\_\_  
Page No. 4

### **STRIKE-OFF BLADE**

Curved type, 24" high, reversible, with torque tubes for rigidity

Yes  No \_\_\_\_\_  
Page No. 4

### **COLUMN**

Column tube shall be large diameter (5") for stability at wide widths. Push bar slope shall be telescoping type with quick pins for fast set-up and changes.

Yes  No \_\_\_\_\_  
Page No. 4

### **HYDRAULIC CONTROL**

Strike-off height (grade) and angle (slope) shall be hydraulically adjustable from operator panel. Hydraulic valves shall have automatic lock feature to maintain grade and slope once set by operator.

Yes  No \_\_\_\_\_  
Page No. 5+4

### **INSIDE EDGE PLATE**

Inside edge plate shall be provided to keep paving material in front of the strike-off and away from the main road surface.

Yes  No \_\_\_\_\_  
Page No. 4

### **OUTER EDGE PLATE**

Shall be provided to retain shoulder paving material within the desired width. Edger shall have adjustment to hold plate at desired height.

Yes  No \_\_\_\_\_  
Page No. 5

### **HYDRAULIC VARIABLE WIDTH BLADE**

A 35" blade section shall be provided which can extend up to an additional 24" by remote control from operator panel. Extending blade shall be able to lay a mat as well as the main blade sections.

Yes  No \_\_\_\_\_  
Page No. 5

## **CATER WHEELS**

Wheels Eight (8) wheels minimum shall be provided for maximum rotation and control. Wheels are to be 16" diameter by 5" wide hard rubber type (pneumatic tires not acceptable) with full width roller bearing axle. Frames Four (4) caster frames shall be installed on the unit. Each frame shall have two wheels (one wheel per frame not acceptable). Caster pivot shaft shall be heat treated, high strength steel 3" diameter minimum. Each pivot shall have dual roller bearings and one thrust bearing. Mounting Casters shall be mounted beneath the attachment for safety. Wheels mounted in front of attachment are not acceptable.

Yes  No   
Page No. 5

## **OPERATOR CONTROLS**

Operator panel will be movable, mounted on a 6' cord. Panel shall be attached to machine by quick disconnect. Operator panel controls shall include: throttle, conveyor on/off, conveyor speed and all strike-off functions (grade, slope, extension option). Panel shall be constructed so that operator can easily carry it on mount near operator of loader, grader or paver.

Yes  No   
Page No. 5

## **PLATFORM**

An operator platform shall be provided which mounts at the base of the strike-off blade. It shall be easily moveable and protect the operator from trucks and drive unit. Front mounted operator platform is not acceptable.

Yes  No   
Page No. 5

## **POWER**

Diesel engine shall be air cooled type 40 HP.

Fuel system to have 15 gal. Tank with filter. Controls to include: keys with, throttle, shutdown, low oil switch, maintenance-free battery an hour meter.

*\* engine water cooled*

Yes  No   
Page No. 5

## **HYDRAULICS**

A high pressure, closed loop, variable displacement hydraulic pump shall be provided to run belt up to 350'/min. Variable speed belt will be controlled by solenoid/relief valve. Hydraulic cylinders shall be double acting through individual manual actuated relief valves, Hydraulic Replaceable filters shall be spin-on type.

Yes  No   
Page No. 6

## **PLATE**

Shall be provided to retain shoulder paving material within the desired width. Edger shall have adjustment to hold plate at desired height.

Yes  No   
Page No. 4&5

## **HYDRAULIC VARIABLE WIDTH BLADE**

A 35" blade section shall be provided which can extend up to an additional 24" by remote control from

operator panel. Extending blade shall be able to lay a mat as well as the main blade sections.

Yes  No   
Page No. 5

#### **GRADER LIFT GROUP**

Arms- Lift group shall bolt to existing holes in grader front plate. All arms shall be heavy duty with bushing on all lifting pins for protection. Tube type arms are required.

Lift- Lift shall be provided by 5" diameter hydraulic cylinder all lifting power must be provided by widener attachment lifting the attachment via grader scarifier is unacceptable Controls for lifting shall all be located at the attachment operator panel.

Yes  No   
Page No. 6

#### **LOADER ADAPTER**

Adapter A specially designed bracket shall be supplied to fit the specified loader

Yes  No   
Page No. 6

#### **PAVER ADAPTER**

Adapter A specially designed bracket shall be supplied to fit the specified paver

Yes  No   
Page No. 6

#### **PAINT**

Paint shall be high visibility orange with reflective striping for maximum nighttime and roadside visibility. One coat of rust inhibitive primer and two coats of high-quality enamel must be professionally applied to all parts of the attachment (excluding engine).

Yes  No   
Page No. 6

#### **HYDRAULIC CONTROL**

Strike-off height (grade) and angle (slope) shall be hydraulically adjustable from operator panel. Hydraulic valves shall have automatic lock feature to maintain grade and slope once set by operator.

Yes  No   
Page No. 6

#### **INSIDE EDGE PLATE**

Inside edge plate shall be provided to keep paving material in front of the strike-off and away from the main road surface.

Yes  No   
Page No. 4

#### **OUTER EDGE PLATE**

Shall be provided to retain shoulder paving material within the desired width. Edger shall have adjustment to hold plate at desired height.

Yes  No   
Page No. 5

#### **HYDRAULIC VARIABLE WIDTH BLADE**

A 35" blade section shall be provided which can extend up to an additional 24" by remote control from operator panel. Extending blade shall be able to lay a mat as well as the main blade sections.

Yes  No   
Page No. 6

P.O.

## WARRANTY AND DISCLAIMER



101 Cranbrook Ext.,  
Tonawanda, NY 14150  
(716) 692-1200

Midland warrants to the original purchaser only, that each part of the Road Building Machine, or components or other manufactured items, sold herein under normal use and service, shall be free from defects in workmanship and material for 365 days (1 year) and 1000 working hours, from initial start-up, whichever occurs first, except that this warranty shall not apply to tires, engines, batteries, manufactured hydraulic components, which items shall be subject to the original manufacturers' warranty. No adjustment shall be made for defective items unless notice is given in writing within ten days after the defect is noted and the equipment is immediately taken out of service. Use of equipment thereafter shall constitute acceptance and waiver of the alleged defects.

This warranty shall be fulfilled by Midland repairing or replacing at its authorized location, products or parts that have been returned to it with transportation charges prepaid and that appear to its satisfaction to have been defective in workmanship or material.

The foregoing specific warranty is in lieu of any other expressed or implied warranties including any implied warranty of merchantability or fitness for a particular use, and any other obligation on part of Midland. Midland shall not be responsible under this warranty for any loss of use of the equipment, loss of time, inconvenience, commercial loss or consequential damage.

No agent, employee or representative of Midland has any authority to bind Midland to any affirmation, representation or warranty concerning the machine sold under this contract not stated within, and unless an affirmation, representation or warranty made by an agent, employee or representative is specifically included within this written agreement, it shall not be enforceable against Midland.

## IMPORTANT



### WARRANTY CARD

NOTE: NO CLAIMS ARE HONORED UNLESS WARRANTY IS ESTABLISHED

MODEL: \_\_\_\_\_ SERIAL NO.: \_\_\_\_\_

TYPE OF ENGINE: \_\_\_\_\_ SERIAL NO. OF ENGINE: \_\_\_\_\_

MACHINE HAS BEEN: SOLD: \_\_\_\_\_ RENTED: \_\_\_\_\_ DATE: \_\_\_\_\_

DEALER: \_\_\_\_\_

PURCHASED BY/RENTED TO: \_\_\_\_\_

ADDRESS OF ABOVE: \_\_\_\_\_

SIGNED BY: \_\_\_\_\_ TITLE: \_\_\_\_\_

# WA Model

Rugged, Highway Class, High Production

P2



- ▶ Highway Class Machine
- ▶ High Production at Half the Cost
- ▶ Quick Change Dual Discharge R&L Pkg. Available
- ▶ Extendable Push Roller for best truck fit
- ▶ Spread Width: 1ft up to 10 ft Wide
- ▶ Utilize your Fleet: Wheel Loader or Grader
- ▶ 49HP Diesel Power Package
- ▶ 600 Tons Per Hour

## SPECIFICATIONS

<b>Standard Spread Width</b>	One (1) to Eight (8) Feet
<b>Maximum Optional Spread Width</b>	Ten (10) Feet
<b>Spread Depth Range</b>	12" Above to 12" Below Grade
<b>Production Rate Capacity</b>	600 Tons Per Hour
<b>Strike Off</b>	Strike-off Blade spreads material to a controlled width, depth and slope
<b>Controls</b>	Hydraulic Grade, Slope and Extend
<b>Engine</b>	49 HP Water Cooled Diesel Tier 4f
<b>Fuel Tank</b>	24 Gal. with Filter
<b>Hydraulic Reservoir</b>	10 Gal. Suction Strainer & Return Filter
<b>Conveyor</b>	
Width	24 Inches
Live Area	22 Inches
Speed	0-400 F.P.M.
Type	Variable Speed Positive Drive Hydraulic
Material	Hot Asphalt Belt 350 (degree) Capacity
<b>Weight (standard unit)</b>	8000#
<b>Push Roller</b>	Oscillating and Extendable
<b>Hydraulic Pump</b>	Variable Displacement with Cooler
<b>Caster Wheels</b>	
Caster	Heavy Duty 10,000# Capacity
Wheel	16" Dia. x 5" wide, (2) Wheels per Caster
Standard Arrangement	4 Casters



The WA model offers increased versatility and widening performance when a self-propelled widener is not an option. By utilizing existing equipment as the drive unit (e.g. wheel loader, grader, etc.) the user can still successfully meet, and exceed, high job demands. Lower equipment costs and a higher utilization rate leads to lower overhead and higher profitability for the user.

## POSITIVE DRIVE CONVEYOR:

Midland's innovative heavy-duty Positive Drive Conveyor System is chain driven, resulting in the elimination of belt wandering and spillage. Positive drive means less maintenance and adjustments, leading to a cleaner and more reliable system for moving all types of hot asphalt and dense aggregates.

We Save You Time and Money!

**MIDLAND MACHINERY CO., INC.**  
**101 CRANBROOK EXT.**  
**TONAWANDA, NY 14150**  
**Ph: 716-692-1200**  
**Fax: 716-692-1206**

D.3

**MODEL WA ATTACHMENT - ROAD WIDENER/SHOULDER MACHINE**  
**Diesel Powered 49 HP Tier IV final**

**DETAILED SPECIFICATIONS**

**ATTACHES TO:**

Most makes of front end loaders and motorgraders.

Can place all types of crushed or graded aggregate and various types of hot asphalt mixes.

**CAPACITY/PRODUCTION**

Variable to 600 tons per hour

**WIDTH OF SPREAD**

Standard 1 ft. to 8 ft. – optional to 10 ft. with Hydraulic Variable Strike off blade.

**DEPTH OF SPREAD**

12 in. below grade to 12 in. above pavement

**WEIGHT**

Not to exceed 8500 lbs. in standard configuration

**OVERALL WIDTH FOR TRANSPORT**

Not to exceed 11 ft. – 6 in. or

7 ft- 11 in. when turned length wise and disconnected from push unit.

**PUSH ROLLERS**

Push rollers to contact and push on dump truck rear tires must be self-cleaning and mounted to oscillating type beam to maintain proper truck alignment.

Push Roller frame must be manually extendable 14 in. and manually lock into various positions to match dump trucks and position dump truck in hopper.

(Option) Push Rollers shall extend/retract hydraulically by hydraulic valve.

## **HOPPER**

Hopper frame shall be welded type with integrated hydraulically driven conveyor. Opening for dump truck between hopper end panels shall be a minimum width of 9 ft -8 in. with a  $\frac{3}{4}$  in. thick hopper bib rubber bolted to a 1/2 in. thick steel bumper plate to prevent material spillage and retain material above conveyor. Capacity of the hopper shall be 3.5 cu. yds.

## **CONVEYOR**

To eliminate conveyor slippage and wandering under load, a 24 in. wide belt conveyor with drive chains bolted to each side of a 2 ply heat and oil resistant conveyor belt and equipped with a positive drive, high torque hydraulic motor mounted to drive pulleys with integrated sprockets shall be provided (motor shall be movable to opposite ends and reversible). Belt splice shall be bolted hinged type made of stainless steel. Conveyor must be supported by a minimum of 30 idler rollers to reduce belt deflection and stress from heavy load. Idlers shall be spaced on 4 in. minimum centers to properly support conveyor belt and minimize material leakage under conveyor sideboards.

## **PULLY DRIVE**

Conveyor pulley at each end of the conveyor shall be identical and have two identical sprockets in proper alignment to pull conveyor under heavy load. Pulley shall accept high torque, hydraulic motors at both ends of the conveyor to allow right or left hand material discharge from the conveyor.

## **SIDEBOARDS**

Sideboards shall be adjustable and replaceable rubber type.

Mounting must be in a retainer for easy access and adjustment with removable steel plate covers for protection from hopper load.

## **STRIKE-OFF BLADE**

Curved type – 24 in. high, reversible with torque tubes for rigidity.

## **COLUMN**

Support column for strike-off blade shall be heavy duty type 5" Diameter for stability at widest spreading widths. Push bar for the strike-off blade shall be telescoping type with quick release pins for fast set up and width changes. Control for strike-off blade height (grade) shall be hydraulically adjustable from the operator panel. Hydraulic valves shall have locking feature to maintain proper grade once set by operator. Control of strike-off blade slope shall be hydraulically adjustable from operator panel and be able to position the strike-off blade slope into a positive or negative slope. Support column shall be provided on both right and left side of machine.

## **INSIDE EDGE PLATE**

Inside edge (roadway edge) plate shall be provided to retain paving materials in front of the strike-off blade and keep materials off the main road surface. Plate(s) shall be provided on both right side and left side.

D. S

### **OUTER EDGE PLATE**

Outer edge plate shall be provided to retain shoulder paving materials within the desired spread width.

### **HYDRAULIC VARIABLE WIDTH STRIKE-OFF BLADE**

A 35 in. strike-off blade section shall be provided that can extend up to an additional 24 in. by hydraulic control through a lever at the operators control panel. It shall be installed on the right side strike off assembly.

### **CASTER WHEELS**

A minimum of Eight (8) wheels shall be provided for maximum floatation and steering control. Wheels shall be hard rubber type (16 in. diameter by 5 in. wide) –pneumatic tires are not acceptable. Four (4) caster frames shall be installed on the road widener unit frame and shall have two (2) hard rubber tire and wheels on each frame to form the four (4) supporting caster units (one wheel per caster frame is not acceptable). Caster frame pivot shaft shall be 3 in. diameter and constructed of heat treated, high strength steel mounted in dual roller bearings inside a high strength mounting block positioned beneath the frame for stability.

### **OPERATORS CONTROLS**

A single control box shall be mounted on a 6 ft cord. Electric Controls in the box shall include strike-off blade grade and slope operation, strike- off blade extension operation, conveyor on/off and conveyor speed along with kill switch. Control panel shall be quickly moveable between right and left side operation.

### **OPERATORS PLATFORM**

An operators platform shall be provided mounting on the strike-off blade column tube. It shall be moveable from RH side to LH side and protect the operator from both haul trucks and drive unit.

### **POWER**

Diesel engine shall be Kubota 49 HP Tier IV. Fuel system to have 25 gal. tank with filter. Controls to include: keyswitch, throttle, shutdown, low oil switch, maintenance-free battery, hourmeter.

## HYDRAULICS

A high pressure, closed loop, variable displacement hydraulic pump shall be provided to run belt up to 400' /min. Variable speed belt on/off will be controlled by solenoid/relief valve. Strike-off blade hydraulic cylinders shall be double acting through individual manual actuated relief valves. Selector valves shall direct power to strike off blade cylinders on discharge end of machine. Hydraulic tank shall have suction and return line filtration. Replaceable filters shall be spin-on type.

## PAINT

Paint shall be high visibility orange with reflective striping for maximum nighttime and roadside visibility. One coat of rust inhibiting primer and a finish coat of high quality epoxy shall be professionally applied to all areas of the attachment – excluding the engine or hydraulic components.

## **One of the following will be needed to fit and adapt to a user supplied Prime Mover.**

### WHEEL LOADER ADAPTER

A specially designed Mating Adapter shall be supplied to fit specified loader, either pin-on style or quick attach style. Arms- lift group shall bolt to existing holes in grader plate, all arms shall be heavy duty with bushing. Lift cylinder shall be 5" diameter, controls shall be located at operator panel. Please provide Quick attach model and size or Loader model.

### GRADER ADAPTER

**A specially designed Mating Adapter shall be supplied to fit Grader front lift arms either pin-on style or quick attach style. Please provide Quick attach model and size.**



101 Cranbrook Ext.

Tonawanda NY 14150-4110

Ph. (716) 692-1200 Fax: (716) 692-1206

[www.midlandmachinery.com](http://www.midlandmachinery.com)

e-mail: sales@midlandmachinery.com

WA Model Price List

Effective-01/01/2026

Supersedes 03/03/2025

10% Discount

ITEM	DESCRIPTION	PRICE	COST TO COUNTY	OPTIONS
1	WA-954-001 D <b>WA MODEL - DIESEL ENGINE POWERED</b>	\$ 139,748.00	\$ 125,773.20	INCLUDED IN STANDARD PRICE
	Spreads Right & Left	\$	\$	-
	Electric/Hydraulic Control Valves w/control box cord	\$	\$	-
	Movable Operator Control Panel	\$	\$	-
	49 HP Kubota Diesel Engine -Tier IV	\$	\$	-
	Hydraulic Grade Control & Slope Control	\$	\$	-
	Oscillating Push Roller in Extendible Frame	\$	\$	-
	Caster Wheels, Front Mounted, Set of four (4) (2 Wheels per Caster)	\$	\$	-
	Vari. Speed, Heat & Oil Resistant, Positive Drive Conveyor Belt, 24 in. Wide	\$	\$	-
	Strike-Off Blade 1- 6 ft. w/ Adjustable Outside Edger Plate (Optional to 10' w/item 5 below)	\$	\$	-
	<b>OPTIONAL EQUIPMENT</b>	\$	\$	-
2	Various PIN TYPE HITCH ADAPTER, replaces loader bucket*	\$ 4,978.00	\$ 4,480.20	
3	Various QUICK COUPLER HITCH SYSTEM, female section only (JRB, ACS, Balderson, etc.)	\$ 5,852.00	\$ 5,266.80	INCLUDED IN STANDARD PRICE
4	SW-893 MANUALLY ADJUSTABLE CONVEYOR DISCHARGE GATE	\$ 3,209.00	\$ 2,888.10	
5	SW-1738 2 ft. HYDRAULIC VARIABLE WIDTH STRIKE-OFF (24 in. Stroke-expands to 48 in.)	\$ 9,878.00	\$ 8,890.20	INCLUDED IN STANDARD PRICE
6	SW-2092 OPERATOR PLATFORM	\$ 3,265.00	\$ 2,938.50	INCLUDED IN STANDARD PRICE
7	MA-1231,1232, MA-1248,1249 GRADER PARALLEL LIFT GROUP-BOLTS TO GRADER FRONT PLATE	\$ 13,703.00	\$ 12,332.70	INCLUDED IN STANDARD PRICE
	For Graders which do not have front scarified or plow arms	\$	\$	-
	Allows Widener to be raised for transport or float for operation	\$	\$	-
8	WA-1813-001 DEDUCT TO REMOVE ENGINE	\$ (9,750.00)	\$ (8,775.00)	
	Drive Unit must supply all hydraulic power for Widener	\$	\$	-
	Valve package (Item #10 below) may be required	\$	\$	-
9	WA-1813-001 LOADER HYDRAULIC VALVE PACKAGE (Deduct Item #8)	\$ 3,338.00	\$ 3,004.20	
	Receives hydraulic power from loader 3rd valve	\$	\$	-
	Regulates pressure and flow and divides hydraulic power to all Widener functions	\$	\$	-
10	SA-1513 TRENCH FILL STRIKE-OFF BOX	\$ 14,106.00	\$ 12,695.40	
	For filling narrow edge drain trenches adjacent to pavement	\$	\$	-
	Box mounts on end of conveyor to direct aggregate in trench	\$	\$	-
	Strike-off levels material in trench up to 34" below pavement level	\$	\$	-
11	SW-944 SCREW JACKS w/HAND CRANKS FOR ADJ. OUTER (End of Blade) EDGER PLATE	\$ 2,200.00	\$ 1,980.00	
12	SW-864 Rev-B HYDRAULIC PUSH ROLLER ASSEMBLY	\$ 7,599.00	\$ 6,839.10	
13	TBD REPAIR KIT; Included: Conveyor belt w/drive chain, Conveyor belt splice, sideboard rubber w/clamp, 6 conveyor rollers, 1 return idler roller, 3 electric solenoids, 2 electric actuator, 6 (2 ea.) electric switches, 1 hydraulic grade blade lift cylinder, 1 hydraulic blade slope cylinder, 1 hydraulic blade extension cylinder, 4 caster wheel bearings & 6 pivot arms (Edger plate)	\$ 16,660.00	\$ 14,994.00	
14	WAD-1791-003 WA Model - Quick Full Left Hand Reversing Capable including Blade/ Column support and up/down/slope controls, Adj. Discharge gates	\$ 27,020.00	\$ 24,318.00	
15	WAD-1791-004 WA Model Conveyor Reversing only with RH/LH Adj. Discharge Gates	\$ 13,748.00	\$ 12,373.20	

All Prices FOB Tonawanda, NY USA

	PRICE TO COUNTY
	\$ 155,201.40
FREIGHT & PDI	5500
TOTAL	\$ 160,701.40

WA Model Price List

# E-Verify



Company ID Number: 579304

To be accepted as a participant in E-Verify, you should only sign the Employer's Section of the signature page. If you have any questions, contact E-Verify at 888-464-4218.

**Employer Pittman Tractor Co, Inc**

**Lynn Pittman**

Name (Please Type or Print)

Title

**Electronically Signed**  
Signature

07/09/2012  
Date

**Department of Homeland Security – Verification Division**

**USCIS Verification Division**

Name (Please Type or Print)

Title

**Electronically Signed**  
Signature

07/09/2012  
Date

## Information Required for the E-Verify Program

### Information relating to your Company:

Company Name: **Pittman Tractor Co, Inc**

Company Facility Address: **9652 Milton Jones Road**

**Daphne, AL 36526**

Company Alternate  
Address: **P.O. Box 26**

**Montrose, AL 36559**

County or Parish: **BALDWIN**

Employer Identification  
Number: **630991112**

WA Widener Attachment  
Option A

# INVITATION TO BID HEAVY EQUIPMENT

## NOTICE OF BID OPENING

**NOTICE IS HEREBY GIVEN** that the Association of County Commissions of Alabama, which administers the Alabama County Joint Bid Program on behalf of Alabama's county governing bodies, shall receive and open bids for the purchase of zero (0) or more items of heavy road equipment at its office located at 2 North Jackson Street, Montgomery, Alabama, at **10:00 a.m. on Tuesday, November 18, 2025**. Bid specifications are available at <http://www.alabamacounties.org/heavy-equipment/> for each of the following items:

Track Mount Excavators  
Compact Excavators  
Mini Track Excavators  
Wheeled Excavators  
Highway Speed Truck Excavators  
Motor Graders  
Wheel Loaders  
Heavy Duty Dump Chassis  
Lowboy Tractors  
Lowboy Trailers  
Half Round End Dump  
Skid Steer Loader and Attachments  
Ride-on Industrial Boom Mowers  
Rubber Tire Roller  
Vibratory Roller

One-man Pothole Patchers  
Trailer Mount Mastic Patcher/Crack Sealer  
Trailer Mounted Patcher – Diesel  
Trailer Mounted Patcher – Air Compressor/Tools  
Chip Spreader  
Asphalt Distributor  
Asphalt Milling Attachments  
Asphalt Storage Tanks  
Backhoes  
Bulldozers  
Dump Bodies  
Road Wideners  
Ride On Industrial Boom Mowers

Time is of the essence in submitting bids and only bids received in the Association office by 10:00 a.m. Central Time on Tuesday, November 18, 2025 will be opened and considered. Bidders and any other interested individuals are invited to attend the bid opening.

## NOTICE OF BID OPENING PROCEDURES

All bids for Heavy Equipment will be opened and the name(s) of the bidders read aloud on the morning of the bid opening on Tuesday, November 18, 2025 at 10:00 a.m. at 2 North Jackson Street, Montgomery, AL. The specifics of each bid submitted will be compiled by the Association staff thereafter and will be available, upon written or emailed request, one week after the bid opening. Requests should be emailed to [jointbid@alabamacounties.org](mailto:jointbid@alabamacounties.org).

## THE INVITATION PACKAGE

The invitation package for each item to be bid includes: this invitation to bid, the written bid specifications for the particular item of heavy road equipment, and a Bid Submittal Form to be used in submitting a bid for that particular item. Bidders should verify that they have received all pages of the invitation package. If there are any omissions, the bidder should contact Kenya Howard in the Association office by mail, fax, or e-mail ([jointbid@alabamacounties.org](mailto:jointbid@alabamacounties.org)) to request missing pages. It is the responsibility of the bidder to make this request in sufficient time to prepare and submit the bid in time for the bid opening. Bidders should carefully read and comply with all parts of the invitation package, including all attachments and/or any addendum.

## **PREPARING AND SUBMITTING BIDS**

All bids must be typed or handwritten in ink on the attached Bid Submittal Form. The completed Bid Submittal Form shall be placed in front of and separated from all other documents included in the bid packet, such that it will be the first document viewed upon opening the bid packet.

Bids submitted in pencil and bids not submitted on the Bid Submittal Form **will not** be considered. All bids shall include a current catalog or model specification document for the equipment model number being offered for consideration. Bids submitted without such documentation **will not** be considered. Only information contained on the attached Bid Submittal Form and in the model specification document will be considered in evaluating bids.

Each separate requirement in the bid specification includes a block for indicating whether or not the item bid meets the specification. The bidder shall indicate compliance with each requirement by checking "Yes" or "No" in the block to the right of each bid specification. In addition, the bidder shall indicate the page number in the supplied manufacturer's equipment literature on which compliance with the specification can be verified. Failure to complete this portion of the bid form may result in the subject bid not being considered.

Each bid for one of the heavy equipment items included in the bid package must be submitted on the Bid Submittal Form for that item and forwarded in a separate envelope with the bid item and item number clearly identified on the outside of the envelope. Envelopes containing a "no bid" shall also include the words "NO BID" on the outside of the envelope. Facsimiles and e-mails will not be accepted. Bids submitted by "Express/Oversight" services must be in a separate inner envelope or package sealed and identified as stated above. All bids must be received in the Association office prior to the bid opening. Bids received after the deadline will be returned unopened.

The County Joint Bid Program reserves the right to require a performance bond from successful bidders as permitted under Alabama law. However, **no bid bond is required for this bid offering.**

All bids should be mailed or hand-delivered to:

**ATTN: Alabama County Joint Bid Program**  
**Association of County Commissions of Alabama or ACCA**  
**2 North Jackson Street, FL 7, Montgomery, Alabama 36104 (Physical Address)**  
**P.O. Box 5040, Montgomery, Alabama 36103 (Mailing Address)**

## **BID SPECIFICATIONS**

Please note that each piece of heavy equipment available for bid may include several different sizes and categories of machines. You should read each set of specifications very carefully as the differences vary depending upon the piece and size of equipment.

The award will be based on the total cost of the **Standard Machine** bid by the lowest responsible bidder. Each Bid shall include a **Manufacturer's Suggested Retail Price Sheet (MSRP)** for each machine bid. The percent difference between the Manufacturer's Suggested Retail Price (MSRP) for the standard machine as specified by these bid specifications and the actual price bid by the vendor will be calculated and that percentage discount shall be applied to any options an individual county may choose to add to the machine.

**Both parties agree that the Vendor SHALL extend to ALL counties purchasing this equipment any factory discounts, incentives or rebates that become available during the Contract Period; provided that there are no alterations from the bid specifications for this item required in order to receive the discount, incentive, or rebate. FURTHER, BOTH PARTIES AGREE THAT THE VENDOR SHALL EXTEND TO ALL COUNTIES PURCHASING THIS EQUIPMENT THE SAME PURCHASE PRICE AND DISCOUNTS AS THEY ARE AWARDED ON ANY OTHER NATIONAL PURCHASING COOPERATIVE APPROVED BY THE DEPARTMENT OF EXAMINERS OF PUBLIC ACCOUNTS FOR USE BY ALABAMA COUNTIES.**

Once the bids have been awarded, any county participant purchasing under this program may, at its discretion, add any of the vendor's available options at the same discount off the Manufacturer's Suggested Retail Price Sheet as was applied to the Standard Machine Price Bid.

Any use of specific names and/or model numbers in the attached specifications is not intended to restrict the bidder or any seller or manufacturer, but is included solely for the purpose of indicating the type, size, and quality of materials, product services, or equipment considered best adapted to the use of the counties participating in the joint bid program.

## **ACQUISITION AND FINANCING OPTIONS**

The awarded Vendor will provide the equipment, including any options required by the purchaser, at the awarded price as contracted through the Joint Bid Program. The purchaser may secure its own financing to acquire the equipment or execute any financial options available under Alabama law with the awarded Vendor in order to acquire the equipment.

## **BIDDER QUALIFICATIONS**

All bidders and all program participants must be in compliance with any applicable federal, state, county and municipal laws, regulations, resolutions and ordinances, including but not limited to, licensing, permitting, and taxation requirements. All bidders should be prepared to submit evidence or documentation as proof that they are properly licensed and permitted under any applicable laws upon request. Such evidence or documentation may be submitted with the bid. **Additionally, all bidders shall provide proof that they are in compliance with the E-Verify requirements of Alabama's Immigration Law (Ala. Code § 31-13-1 et seq.). All bidders shall also affirm that they are in compliance with, and will comply with, Alabama's anti-boycott law (Ala. Code § 41-16-5) and anti-economic boycott law (Ala. Code § 41-16-160 et seq.).**

## **BID AWARD**

The Houston County Commission will serve as the awarding authority for all bids and will award all contracts at a regular meeting of the Houston County Commission. Any and all bids submitted in compliance with this invitation to bid shall be considered, and award will be made to the lowest responsible bidder meeting bid specifications as determined by the awarding authority in compliance with Alabama law. All bids will be reviewed and evaluated by a committee created for that purpose, which committee will make comments and recommendations to the awarding authority regarding the award. All factors contained in each invitation package will be evaluated in determining the successful bidder, and any omissions of the stated requirements may be cause for rejection of the bid submitted. The awarding authority reserves the right to reject any and all bids, to waive any informality in bids, and to accept in whole or in part such bid or bids solely at its discretion.

**The contract period will be six (6) months with an option to renew each six (6) months not to exceed a period of three (3) years under identical price, terms, and conditions upon the mutual consent of the vendor and the awarding authority.** Any renewal contract shall be approved in writing by the vendor and the awarding authority no later than **60 days** prior to the expiration of the existing contract.

## **CONTACT REGARDING BIDS AND INVITATION**

Contact initiated by a potential bidder with any county official, county employee, or member of the Association staff shall only be as specifically set out in this Invitation to Bid. Any questions related to the bid or the County Joint Bid Program shall be directed to Association staff in writing under the procedures set out in this Invitation to Bid. Additionally, a bidder may contact the Association in writing to request an appointment to review bid specifications following the bid opening. However, there shall be no communication with any county official or county employee regarding this bid between the date of this invitation and the date of bid award. Any contact other than as set out here shall be deemed as an attempt to unduly influence the bid award, and shall be grounds for rejection of the bid submitted by the bidder initiating such other contact.

Any questions or problems related to downloading or obtaining copies of this Invitation to Bid should be directed to Kenya Howard at [jointbid@alabamacounties.org](mailto:jointbid@alabamacounties.org) or 334-263-7594.

Any other questions or requests for additional information regarding this invitation or the bid specifications shall be submitted **in writing** no later than five (5) days prior to bid opening to:

**ATTN: Patrick McDougald  
Association of County Commissions of Alabama  
P.O. Box 5040  
Montgomery, Alabama 36104**

**OR**

**Patrick McDougald  
Email: [pattymackdaddy@gmail.com](mailto:pattymackdaddy@gmail.com)**